

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0014442911

Status:

Active

Overview:

cgrid_sl_products

Description:

2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 11 Circuits

Documents:

3D Model

Drawing (PDF)

Product Specification PS-70400 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	Ribbon Cable / Wire Trap Connectors
Series	70475
Comments	Terminals Preloaded
Component Type	Housing
Glow-Wire Compliant	No
Overview	cgrid_sl_products
Product Name	SL™

Physical	
Circuits (Loaded)	11
Durability (mating cycles max)	50
Entry Angle	Vertical
Flammability	94V-0
Lock to Mating Part	None
Number of Rows	1
PCB Retention	None
Packaging Type	Tube
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Polarized to Mating Part	No
Stackable	Yes
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-40°C to +105°C
Wire Insulation Diameter	1.35mm (.053") max.
Wire Size AWG	26
Wire/Cable Type	Discrete Wire, Ribbon Cable

Electrical	
Current - Maximum per Contact	1.8A
Voltage - Maximum	250V

Material Info

Reference - Drawing Numbers	
Product Specification	PS-70400




image - Reference only

Series

EU RoHS

China RoHS

Compliance Status

Not Reviewed

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

70475Series

Mates With

70004 Interim Clip (Single Row), 70013 Interim Clip (Dual Row)


Use With

7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG



OPTION D

NOTES:

- 1) TO BE USED WITH (26) AWG. STRANDED WIRE WITH (1.35)/.053 DIA. MAX. INSULATION.
- 2) SEE CHART FOR CIRCUIT SIZES.
- 3) STANDARD PACKAGING PER PK-70873-0001. OPTIONAL PACKAGING MAY BE AVAILABLE, REQUEST DWG. PK-70475.
- 4) PARTS STACKABLE END TO END ON (2.54)/.100 CENTERS.
- 5) REFER TO PRODUCT SPECIFICATION: PS-70475.
- 6) SEE DWG. SDA-70475-**** (SHT.3) FOR OPTIONAL HOUSING DETAILS.
- 7) 4 CIRCUIT SHOWN. 3 - 25 CKT'S. HAVE (2) RIBS.
- 8) TO MATE WITH MOLEX PART NO'S.: 70018-****, 70022-****, 70104-****.
- 9) 2 CIRCUIT ASSEMBLIES SUPPLIED AS GROUPED PAIRS.



SECTION C-C



HOUSING PART NO. 70066-****
MATERIAL: G.F. POLYESTER, 94V-0

TERMINAL PART NO. 70110-****
MATERIAL: PHOSPHOR BRONZE
PLATING PER ES-88-***

30 GOLD - .000030 MINIMUM GOLD IN SELECT AREA WITH
.000075 MINIMUM TIN
IN SELECT AREA OVER .000050 MINIMUM NICKEL
OVER-ALL.

*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.

I.D. SLOT CODE TO WIRE GAUGE CHART	
I.D. SLOT CODE	WIRE GAUGE
B	26 AWG.

PLATING CODE (STRIPE ON CARRIER STRIP)	
PLATING	COLOR
30 GOLD	RED

CKT. SIZE	A	B	EDP. NO.	ENG. NO.
2	(2.54) 1.00	(5.05) 1.99	14-44-2902	A-70475-1296
3	(5.08) 2.00	(7.59) 2.99	14-44-2903	A-70475-1297
4	(7.62) 3.00	(10.13) 3.99	14-44-2904	A-70475-1298
5	(10.16) 4.00	(12.67) 4.99	14-44-2905	A-70475-1299
6	(12.70) 5.00	(15.21) 5.99	14-44-2906	A-70475-1300
7	(15.24) 6.00	(17.75) 6.99	14-44-2907	A-70475-1301
8	(17.78) 7.00	(20.29) 7.99	14-44-2908	A-70475-1302
9	(20.32) 8.00	(22.83) 8.99	14-44-2909	A-70475-1303
10	(22.86) 9.00	(25.37) 9.99	14-44-2910	A-70475-1304
11	(25.54) 1.00	(27.91) 1.09	14-44-2911	A-70475-1305
12	(27.94) 1.00	(30.45) 1.99	14-44-2912	A-70475-1306
13	(30.48) 1.20	(32.99) 1.29	14-44-2913	A-70475-1307
14	(33.02) 1.30	(35.53) 1.39	14-44-2914	A-70475-1308
15	(35.56) 1.40	(38.07) 1.49	14-44-2915	A-70475-1309
16	(38.01) 1.50	(40.61) 1.59	14-44-2916	A-70475-1310
17	(40.64) 1.60	(43.15) 1.69	14-44-2917	A-70475-1311
18	(43.18) 1.70	(45.69) 1.79	14-44-2918	A-70475-1312
19	(45.72) 1.80	(48.23) 1.89	14-44-2919	A-70475-1313
20	(48.26) 1.90	(50.77) 1.99	14-44-2920	A-70475-1314
21	(50.80) 2.00	(53.31) 2.09	14-44-2921	A-70475-1315
22	(53.34) 2.10	(55.85) 2.19	14-44-2922	A-70475-1316
23	(55.88) 2.20	(58.39) 2.29	14-44-2923	A-70475-1317
24	(58.42) 2.30	(60.93) 2.39	14-44-2924	A-70475-1318
25	(60.96) 2.40	(63.47) 2.49	14-44-2925	A-70475-1319

		D		REVISED PER ECR NO. U82124 10/17/88 MGB		DIMENSIONS SHOWN METRIC INCH UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR $\pm 1/2^\circ$		▽ = ▽ = REVISE ONLY ON CAD SYSTEM	
E		LEAD FREE UCP2004-1769 RWWHITE 04/03/24		C		REVISE PER ECR # U81370 5/20/88 MUM		TITLE ASSEMBLY, SL CONNECTOR (SINGLE ROW- (2,54), 100 GRID)	
DI		ADD CARRIER CHAMF ECN = J011998-0280 05/20/98 LMCGRATH		B		REDRAWN ON CAD ECR# 8842 5/9/86 W.Z.		MOLEX INCORPORATED SHEET NO. DATE LISLE, ILL. 69532 U.S.A. 1 10/13/84	
L.T.R.		REVISIONS		L.T.R.		REVISIONS		PART NO. DRWG. NO. SEE CHART SDA-70475-1296-1319	
L.T.R.		REVISIONS		L.T.R.		REVISIONS		FILE NAME DIV. SIZE 74075X08 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	