

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0014600099

Status:

Active

Description:

2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26, 3.81µm (150µ") Tin/Lead (SnPb), 9 Circuits

Documents:

3D Model

Drawing (PDF)

Product Specification PS-70400 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR19980

UL

E29179

General

Product Family

Series

Comments

Component Type

Glow-Wire Compliant

Product Name

Ribbon Cable / Wire Trap Connectors

70400

Terminals Preloaded

Housing

No

SL™

Physical

Circuits (Loaded)

Color - Resin

Durability (mating cycles max)

Entry Angle

Flammability

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Number of Rows

PCB Retention

Packaging Type

Pitch - Mating Interface (in)

Pitch - Mating Interface (mm)

Plating min: Mating (µin)

Plating min: Mating (µm)

Plating min: Termination (µin)

Plating min: Termination (µm)

Polarized to Mating Part

Stackable

Surface Mount Compatible (SMC)

Temperature Range - Operating

Termination Interface: Style

Wire Insulation Diameter

Wire Size AWG

Wire/Cable Type

9

Black

25

Vertical

94V-0

None

Phosphor Bronze

Tin

Tin

Polyester Alloy

1

None

Tube

0.100 In

2.54 mm

150

3.75

75

1.875

Yes

Yes

N/A

-40°C to +105°C

IDT or Pierce

1.35mm (.053") max.

26

Discrete Wire, Ribbon Cable

Electrical

Current - Maximum per Contact

Voltage - Maximum

1.8A

250V

Material Info




image - Reference only

Series

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

70400Series

Mates With

70544, 70546, 70554 , 70556

Use With

7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global	
Description	Product #
Hawk Semi-Automatice Discrete Wire Terminator for SL - Rebuilt US*	0011201337

Reference - Drawing Numbers

Product Specification
Sales Drawing

PS-70400
SDA-70400-0211-0234



Hawk™ Ribbon Cable Terminator for SL without Break-off	<u>0623003000</u>
Hawk™ Semi-Automatic Discrete Wire Terminator for SL	<u>0623003100</u>
Hawk™ Flat Flex Cable Terminator for SL with Break-off	<u>0623005200</u>
Hawk™ Ribbon Cable Terminator with for SL Break-off	<u>0623005300</u>
Hawk™ Semi-Automatic Discrete Wire Terminator for SL - Rebuilt CE Approved*	<u>0623004900</u>

This document was generated on 03/30/2010
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

OPTION C

NOTES:

- 1) TO BE USED WITH (26) AWG. STRANDED WIRE WITH (1.35)/.053 DIA. MAX. INSULATION.
- 2) SEE CHART FOR CIRCUIT SIZES.
- 3) STANDARD PACKAGING PER PK-70400-0001. OPTIONAL PACKAGING MAY BE AVAILABLE, REQUEST DWG. PK-70400
- 4) PARTS STACKABLE END TO END ON (2.54)/.100 CENTERS.
- 5) REFER TO PRODUCT SPECIFICATION: PS-70400.
- 6) SEE DWG. SDA-70400-**** (SHT. 5) FOR OPTIONAL HOUSING DETAILS.
- 7) 4 CIRCUIT SHOWN. 4 - 25 CKT.'S. HAVE (2) RIBS.
- 8) TO MATE WITH MOLEX PART NO.'S.: A-70374-****, A-70376-****, A-70390-****, A-70392-****, A-70544-****, A-70554-****, A-70542-****, A-70552-****, A-70546-****, A-70556-****.
- 9) 2 CIRCUIT ASSEMBLIES SUPPLIED AS GROUPED PAIRS.



I.D. SLOT CODE TO WIRE GAUGE CHART	
I.D. SLOT CODE	WIRE GAUGE
B	26 AWG.

PLATING CODE (STRIPE ON CARRIER STRIP)	
PLATING	COLOR
TIN	NONE


HOUSING PART NO. 70066-****
MATERIAL: G.F. POLYESTER, 94V-0

TERMINAL PART NO. 70028-****
MATERIAL: PHOSPHOR BRONZE
PLATING PER ES-88-***


TIN - .000150 MIN. TIN OVER
.000050 MIN. NICKEL PLATE.



SECTION C-C



PRE-LOADED ASSEMBLY



FINAL ASSEMBLY

WIRE (SEE NOTE 1)

*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO ROHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.

CKT. SIZE	A	B	EDP. NO.	ENG. NO.
2	(2.54) .100	(5.05) .199	14-60-0029	A-70400-0211
3	(5.08) .200	(7.59) .299	14-60-0039	A-70400-0212
4	(7.62) .300	(10.13) .399	14-60-0049	A-70400-0213
5	(10.16) .400	(12.67) .499	14-60-0059	A-70400-0214
6	(12.70) .500	(15.21) .599	14-60-0069	A-70400-0215
7	(15.24) .600	(17.75) .699	14-60-0079	A-70400-0216
8	(17.78) .700	(20.29) .799	14-60-0089	A-70400-0217
9	(20.32) .800	(22.83) .899	14-60-0099	A-70400-0218
10	(22.86) .900	(25.37) .999	14-60-0109	A-70400-0219
11	(25.54) 1.000	(27.91) 1.099	14-60-0119	A-70400-0220
12	(27.94) 1.100	(30.45) 1.199	14-60-0129	A-70400-0221
13	(30.48) 1.200	(32.99) 1.299	14-60-0139	A-70400-0222
14	(33.02) 1.300	(35.53) 1.399	14-60-0149	A-70400-0223
15	(35.56) 1.400	(38.07) 1.499	14-60-0159	A-70400-0224
16	(38.01) 1.500	(40.61) 1.599	14-60-0169	A-70400-0225
17	(40.64) 1.600	(43.15) 1.699	14-60-0179	A-70400-0226
18	(43.18) 1.700	(45.69) 1.799	14-60-0189	A-70400-0227
19	(45.72) 1.800	(48.23) 1.899	14-60-0199	A-70400-0228
20	(48.26) 1.900	(50.77) 1.999	14-60-0209	A-70400-0229
21	(50.80) 2.000	(53.31) 2.099	14-60-0219	A-70400-0230
22	(53.34) 2.100	(55.85) 2.199	14-60-0229	A-70400-0231
23	(55.88) 2.200	(58.39) 2.299	14-60-0239	A-70400-0232
24	(58.42) 2.300	(60.93) 2.399	14-60-0249	A-70400-0233
25	(60.96) 2.400	(63.47) 2.499	14-60-0259	A-70400-0234

G	LEAD FREE UCP2004-1769 RWHITE 04/03/17		E	REVISED PER ECR NO. U82110 10-17-88 BJS		DIMENSIONS SHOWN (METRIC) INCH UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°		▽ = 0 ▼ = 0		REVISE ONLY ON CAD SYSTEM													
						TITLE ASSEMBLY, SL CONNECTOR (SINGLE ROW - (2.54)/.100 GRID)																	
F1	ADD CARRIER CHAMF ECN *UDT1998-0280 05/20/98 LMCGRATH		D	REVISE PER ECR *U80110 2/3/88 MJM		<table><tr><td>3 PLACE</td><td>INCH</td><td>METRIC</td></tr><tr><td>± .010</td><td>---</td><td>---</td></tr><tr><td>2 PLACE</td><td>± .014</td><td>± 0.25</td></tr><tr><td>1 PLACE</td><td>---</td><td>± 0.35</td></tr></table>		3 PLACE	INCH	METRIC	± .010	---	---	2 PLACE	± .014	± 0.25	1 PLACE	---	± 0.35	MOLEX INCORPORATED LITSE, ILL. 60532 U.S.A.		SHEET NO.	DATE
	3 PLACE	INCH		METRIC																			
± .010	---	---																					
2 PLACE	± .014	± 0.25																					
1 PLACE	---	± 0.35																					
F	164 PLATING WAS 102 PER ECR * U30941 07/07/93 REED		C	REDRAWN ON CAD ECR* 8842 5/8/86 W.Z.		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		PART NO. SEE CHART		SDA-70400-0211-0234													
								FILE NAME 704000XC2		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.													
LTR.	REVISIONS		LTR.	REVISIONS		DRWG. BY WAZ		CHK'D. BY WAZ		DIV. DA													
						APP'D. BY		SCALE 4 : 1		SIZE C													