

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0015800061

Status:

Active

Overview:

cgrid_sl_products

Description:

2.54mm (.100") Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 6 Circuits, Tin (Sn) Plating

Documents:

3D Model

Drawing (PDF)

Packaging Specification (PDF)

Product Specification PS-70567 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL

E29179

General

Product Family

Series

Application

Overview

Product Name

PCB Headers

70567

Wire-to-Board

cgrid_sl_products

C-Grid®

Physical

Breakaway

Circuits (Loaded)

Circuits Detail

Color - Resin

First Mate / Last Break

Flammability

Glow-Wire Compliant

Guide to Mating Part

Keying to Mating Part

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Number of Rows

Orientation

PC Tail Length (in)

PC Tail Length (mm)

PCB Locator

PCB Retention

PCB Thickness Recommended (in)

PCB Thickness Recommended (mm)

Packaging Type

Pitch - Mating Interface (in)

Pitch - Mating Interface (mm)

Pitch - Term. Interface (in)

Pitch - Term. Interface (mm)

Plating min: Mating (µin)

Plating min: Mating (µm)

Plating min: Termination (µin)

Plating min: Termination (µm)

Polarized to Mating Part

Polarized to PCB

Shrouded

No

6

6

Black

No

94V-0

No

No

None

Yes

Brass, Phosphor Bronze

Tin

Tin

High Temperature Thermoplastic

2

Vertical

0.130 In

3.30 mm

No

Yes

0.093 In

2.40 mm

Tube

0.100 In

2.54 mm

0.100 In

2.54 mm

150

3.75


150

3.75

Yes

No

Fully



EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

70567Series

Mates With

70450 Crimp Housing

Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-55°C to +105°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	2.5A
Voltage - Maximum	250V

Solder Process Data

Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	SMC & Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	245

Material Info

Old Part Number	70567-0001
-----------------	------------





Reference - Drawing Numbers

Packaging Specification	PK-70873-0018
Product Specification	PS-70567
Sales Drawing	SDA-70567-****


This document was generated on 05/24/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

OPTION A





PCB LAYOUT: COMPONENT SIDE
TYPICAL PCB THICKNESS: 2.36/.093



NOTES:

- MATERIAL: SHROUDED WAFER: GLASS FILLED, LIQUID CRYSTAL POLYMER, COLOR: BLACK, 94V-0.
- PLATING:
 - TIN 0.000381/.000150 MINIMUM TIN, OVER NICKEL UNDERPLATE OVERALL
 - 15 GOLD 0.000381/.000015 MINIMUM GOLD PLATE IN SELECTED AREA
 - 0.00191/.000075 MINIMUM TIN IN SELECTED AREA
 - OVER NICKEL UNDERPLATE OVERALL
 - 30 GOLD 0.00076/.000030 MINIMUM GOLD PLATE IN SELECTED AREA
 - 0.00191/.000075 MINIMUM TIN IN SELECTED AREA,
 - OVER NICKEL UNDERPLATE OVERALL
- PRODUCT SPECIFICATION: PS-70567.
- PACKAGING: SEE CHARTS
- MEASURE POINT FOR PLATING THICKNESS.
- PIN PUSHOUT FORCE: 4 LBS. MINIMUM IN DIRECTION INDICATED.
- FOR ILLUSTRATION PURPOSES, 20 (DUAL 10) CIRCUIT SIZE HEADER SHOWN.
- PIN SOLDERABILITY PER MOLEX SPEC. SMES-152.
- WINDOW NOT AVAILABLE ON 6 OR 8 CIRCUIT SIZE.
- THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.



MODIFY HOUSING WALL		DESCRIPTION	REV
EC NO:	DATE		
UCP2010-1587	2010/01/12	DRWN:MS BARRA	2010/01/12
CHXD:BARRA	2010/01/12	APPR:SMILLER	2010/03/31







QUALITY SYMBOLS	
▽=0	
▽=0	
▽=0	

GENERAL TOLERANCES (UNLESS SPECIFIED)	
mm	INCH
4 PLACES ± .005	± .005
3 PLACES ± .005	± .005
2 PLACES ± .010	± .010
1 PLACE ± .025	± .025
ANGULAR ± 1/2°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	


SCALE 4:1	DESIGN UNITS INCH	 THIRD ANGLE PROJECTION
TITLE 4 SIDES SHROUDED HEADER HIGH TEMP, (2.54)/.100 GRID W/ (.064)/.025 PINS		
 MOLEX INCORPORATED		
DOCUMENT NO. SDA-70567-****		SHEET NO. 1 OF 5
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

CKT	DIM A	DIM B	DIM L	DIM M	DIM N
06	8.43	5.08	1.68	1.68	
	.332	.200	.066	.066	
08	10.97	7.62	1.68	1.68	
	.432	.300	.066	.066	
10	13.51	10.16	1.68	4.22	
	.532	.400	.066	.166	
12	16.05	12.70	1.68	4.22	
	.632	.500	.066	.166	
14	18.59	15.24	1.68	6.76	
	.732	.600	.066	.266	
16	21.13	17.78	1.68	6.76	
	.832	.700	.066	.266	
18	23.67	20.32	1.68	9.30	
	.932	.800	.066	.366	
20	26.21	22.86	1.68	1.68	19.46
	1.032	.900	.066	.066	.766
22	28.75	25.40	1.68	1.68	22.00
	1.132	1.000	.066	.066	.866
24	31.29	27.94	1.68	1.68	24.54
	1.232	1.100	.066	.066	.966
26	33.83	30.48	1.68	1.68	27.08
	1.332	1.200	.066	.066	1.066
28	36.37	33.02	1.68	1.68	29.62
	1.432	1.300	.066	.066	1.166
30	38.91	35.56	1.68	1.68	32.16
	1.532	1.400	.066	.066	1.266
32	41.45	38.10	1.68	1.68	34.70
	1.632	1.500	.066	.066	1.366
34	43.99	40.64	1.68	1.68	37.24
	1.732	1.600	.066	.066	1.466
36	46.53	43.18	1.68	1.68	39.78
	1.832	1.700	.066	.066	1.566
38	49.07	45.72	1.68	1.68	42.32
	1.932	1.800	.066	.066	1.666
40	51.61	48.26	1.68	1.68	44.86
	2.032	1.900	.066	.066	1.766
42	54.15	50.80	1.68	1.68	47.40
	2.132	2.000	.066	.066	1.866
44	56.69	53.34	1.68	1.68	49.94
	2.232	2.100	.066	.066	1.966
46	59.23	55.88	1.68	1.68	52.48
	2.332	2.200	.066	.066	2.066
48	61.77	58.42	1.68	1.68	55.02
	2.432	2.300	.066	.066	2.166
50	64.31	60.96	1.68	1.68	57.56
	2.532	2.400	.066	.066	2.266
52	66.85	63.50	1.68	1.68	60.10
	2.632	2.500	.066	.066	2.366
54	69.39	66.04	1.68	1.68	62.64
	2.732	2.600	.066	.066	2.466
56	71.93	68.58	1.68	1.68	65.18
	2.832	2.700	.066	.066	2.566
58	74.47	71.12	1.68	1.68	67.72
	2.932	2.800	.066	.066	2.666
60	77.01	73.66	1.68	1.68	70.26
	3.032	2.900	.066	.066	2.766
62	79.55	76.20	1.68	1.68	72.80
	3.132	3.000	.066	.066	2.866
64	82.09	78.74	1.68	1.68	75.34
	3.232	3.100	.066	.066	2.966
66	84.63	81.28	1.68	1.68	77.88
	3.332	3.200	.066	.066	3.066
68	87.17	83.82	1.68	1.68	80.42
	3.432	3.300	.066	.066	3.166
70	89.71	86.36	1.68	1.68	82.96
	3.532	3.400	.066	.066	3.266
72	92.25	88.90	1.68	1.68	85.50
	3.632	3.500	.066	.066	3.366

OPTION B



PCB LAYOUT: COMPONENT SIDE
TYPICAL PCB THICKNESS: 2.36/.093



SECTION Y-Y

- NOTES:
1. MATERIAL: SHROUDED WAFER: 30% G.F. LCP, COLOR: BLACK, 94V-0. PINS: COPPER ALLOY.
 2. PLATING:
TIN - (0.00381)/.000150 MINIMUM TIN OVER NICKEL UNDERPLATE OVERALL
15 GOLD - (0.000381)/.000015 MINIMUM GOLD PLATE IN SELECTED AREA
(0.00191)/.000075 MINIMUM TIN IN SELECTED AREA,
OVER NICKEL UNDERPLATE OVERALL
30 GOLD - (0.000761)/.000030 MINIMUM GOLD PLATE IN SELECTED AREA
(0.00191)/.000075 MINIMUM TIN IN SELECTED AREA,
OVER NICKEL UNDERPLATE OVERALL
 3. PRODUCT SPECIFICATION: PS-70567.
 4. PACKAGING: SEE CHARTS
 5. PIN PUSHOUT FORCE: 4 LBS. MIN IN DIRECTION INDICATED.
 6. FOR ILLUSTRATION PURPOSES, 20 (DUAL 10) CIRCUIT SIZE HEADER SHOWN.
 7. PIN SOLDERABILITY PER MOLEX SPEC. SMES-152.
 8. MEASURE POINT FOR PLATING THICKNESS.
 9. WINDOW IS NOT AVAILABLE ON 6 CIRCUIT.
 10. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.
 11. SEE SHEET 1 FOR ALL OTHER DIMENSIONS

CKT	DIM A	DIM B	DIM L	DIM M	DIM N
06	12.70 .500	5.08 .200	3.81 .150	3.81 .150	---
08	15.24 .600	7.62 .300	3.81 .150	3.81 .150	---
10	17.78 .700	10.16 .400	3.81 .150	6.35 .250	---
12	20.32 .800	12.70 .500	3.81 .150	6.35 .250	---
14	22.86 .900	15.24 .600	3.81 .150	8.89 .350	---
16	25.40 1.000	17.78 .700	3.81 .150	8.89 .350	---
18	27.94 1.100	20.32 .800	3.81 .150	11.43 .450	---
20	30.48 1.200	22.86 .900	3.81 .150	3.81 .150	21.59 .850
22	33.02 1.300	25.40 1.000	3.81 .150	3.81 .150	24.13 .950
24	35.56 1.400	27.94 1.100	3.81 .150	3.81 .150	26.67 1.050
26	38.10 1.500	30.48 1.200	3.81 .150	3.81 .150	29.21 1.150
28	40.64 1.600	33.02 1.300	3.81 .150	3.81 .150	31.75 1.250
30	43.18 1.700	35.56 1.400	3.81 .150	3.81 .150	34.29 1.350
32	45.72 1.800	38.10 1.500	3.81 .150	3.81 .150	36.83 1.450
34	48.26 1.900	40.64 1.600	3.81 .150	3.81 .150	39.37 1.550
36	50.80 2.000	43.18 1.700	3.81 .150	3.81 .150	41.91 1.650
38	53.34 2.100	45.72 1.800	3.81 .150	3.81 .150	44.45 1.750
40	55.88 2.200	48.26 1.900	3.81 .150	3.81 .150	46.99 1.850
42	58.42 2.300	50.80 2.000	3.81 .150	3.81 .150	49.53 1.950
44	60.96 2.400	53.34 2.100	3.81 .150	3.81 .150	52.07 2.050
46	63.50 2.500	55.88 2.200	3.81 .150	3.81 .150	54.61 2.150
48	66.04 2.600	58.42 2.300	3.81 .150	3.81 .150	57.15 2.250
50	68.58 2.700	60.96 2.400	3.81 .150	3.81 .150	59.69 2.350
52	71.12 2.800	63.50 2.500	3.81 .150	3.81 .150	62.23 2.450
54	73.66 2.900	66.04 2.600	3.81 .150	3.81 .150	64.77 2.550
56	76.20 3.000	68.58 2.700	3.81 .150	3.81 .150	67.31 2.650
58	78.74 3.100	71.12 2.800	3.81 .150	3.81 .150	69.85 2.750
60	81.28 3.200	73.66 2.900	3.81 .150	3.81 .150	72.39 2.850
62	83.82 3.300	76.20 3.000	3.81 .150	3.81 .150	74.93 2.950
64	86.36 3.400	78.74 3.100	3.81 .150	3.81 .150	77.47 3.050
66	88.90 3.500	81.28 3.200	3.81 .150	3.81 .150	80.01 3.150
68	91.44 3.600	83.82 3.300	3.81 .150	3.81 .150	82.55 3.250
70	93.98 3.700	86.36 3.400	3.81 .150	3.81 .150	85.09 3.350
72	96.52 3.800	88.90 3.500	3.81 .150	3.81 .150	87.63 3.450

MODIFY HOUSING WALL		QUALITY SYMBOLS		GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE		DESIGN UNITS		THIRD ANGLE PROJECTION	
REV	DESCRIPTION	SYMBOL	VALUE	mm	INCH	MM/IN	DATE	4:1	INCH	INCH	INCH	INCH	INCH
1	DRWN:MS BARA 2010/01/12	▽=0	0	± .005	± .005	EIK	1988/03/10	4 SIDES SHROUDED HEADER HIGH TEMP, (2.54)/.100 GRID W/ (.064)/.025 PINS MOLEX INCORPORATED SDA-70567-**** SHEET NO. 2 OF 5					
2	CHKD:BBARKER 2010/01/12	▽=0	0	± .010	± .010	EIK	1988/03/10						
3	APPR:SMILLER 2010/03/31	▽=0	0	± .025	± .025	SMILLER	2010/03/31						
4	APPR:SMILLER 2010/03/31	▽=0	0	± .025	± .025	SMILLER	2010/03/31						
				ANGULAR ± 1/2°		MATERIAL NO.		DOCUMENT NO.					
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					

NO. OF CKTS	OPTION "A"		OPTION "A"		OPTION "A"		OPTION "A"		OPTION "A"		OPTION "A"								NO. OF CKTS
	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER			
06	IS-80-006I	A-70567-000I	70567-003S	A-70567-003S	IS-80-006B	A-70567-006B	70567-0103	A-70567-0103	IS-80-006S	A-70567-0137	70567-017I	A-70567-017I						06	
08	IS-80-008I	A-70567-000I	70567-003B	A-70567-003B	IS-80-008B	A-70567-0070	70567-0104	A-70567-0104	IS-80-008S	A-70567-0138	70567-0172	A-70567-0172						08	
10	IS-80-010I	A-70567-0003	70567-0037	A-70567-0037	IS-80-0103	A-70567-0071	70567-0105	A-70567-0105	IS-80-010S	A-70567-0139	70567-0173	A-70567-0173						10	
12	IS-80-012I	A-70567-0004	70567-0038	A-70567-0038	IS-80-0123	A-70567-0072	70567-0106	A-70567-0106	IS-80-012S	A-70567-0140	70567-0174	A-70567-0174						12	
14	IS-80-014I	A-70567-0005	70567-0039	A-70567-0039	IS-80-0143	A-70567-0073	70567-0107	A-70567-0107	IS-80-014S	A-70567-0141	70567-0175	A-70567-0175						14	
16	IS-80-016I	A-70567-0006	70567-0040	A-70567-0040	IS-80-0163	A-70567-0074	70567-0108	A-70567-0108	IS-80-016S	A-70567-0142	70567-0176	A-70567-0176						16	
18	IS-80-018I	A-70567-0007	70567-0041	A-70567-0041	IS-80-0183	A-70567-0075	70567-0109	A-70567-0109	IS-80-018S	A-70567-0143	70567-0177	A-70567-0177						18	
20	IS-80-020I	A-70567-0008	70567-0042	A-70567-0042	IS-80-0203	A-70567-0076	70567-0110	A-70567-0110	IS-80-020S	A-70567-0144	70567-0178	A-70567-0178						20	
22	IS-80-022I	A-70567-0009	70567-0043	A-70567-0043	IS-80-0223	A-70567-0077	70567-0111	A-70567-0111	IS-80-022S	A-70567-0145	70567-0179	A-70567-0179						22	
24	IS-80-024I	A-70567-0010	70567-0044	A-70567-0044	IS-80-0243	A-70567-0078	70567-0112	A-70567-0112	IS-80-024S	A-70567-0146	70567-0180	A-70567-0180						24	
26	IS-80-026I	A-70567-0011	70567-0045	A-70567-0045	IS-80-0263	A-70567-0079	70567-0113	A-70567-0113	IS-80-026S	A-70567-0147	70567-0181	A-70567-0181						26	
28	IS-80-028I	A-70567-0012	70567-0046	A-70567-0046	IS-80-0283	A-70567-0080	70567-0114	A-70567-0114	IS-80-028S	A-70567-0148	70567-0182	A-70567-0182						28	
30	IS-80-030I	A-70567-0013	70567-0047	A-70567-0047	IS-80-0303	A-70567-0081	70567-0115	A-70567-0115	IS-80-030S	A-70567-0149	70567-0183	A-70567-0183						30	
32	IS-80-032I	A-70567-0014	70567-0048	A-70567-0048	IS-80-0323	A-70567-0082	70567-0116	A-70567-0116	IS-80-032S	A-70567-0150	70567-0184	A-70567-0184						32	
34	IS-80-034I	A-70567-0015	70567-0049	A-70567-0049	IS-80-0343	A-70567-0083	70567-0117	A-70567-0117	IS-80-034S	A-70567-0151	70567-0185	A-70567-0185						34	
36	IS-80-036I	A-70567-0016	70567-0050	A-70567-0050	IS-80-0363	A-70567-0084	70567-0118	A-70567-0118	IS-80-036S	A-70567-0152	70567-0186	A-70567-0186						36	
38	IS-80-038I	A-70567-0017	70567-0051	A-70567-0051	IS-80-0383	A-70567-0085	70567-0119	A-70567-0119	IS-80-038S	A-70567-0153	70567-0187	A-70567-0187						38	
40	IS-80-040I	A-70567-0018	70567-0052	A-70567-0052	IS-80-0403	A-70567-0086	70567-0120	A-70567-0120	IS-80-040S	A-70567-0154	70567-0188	A-70567-0188						40	
42	IS-80-042I	A-70567-0019	70567-0053	A-70567-0053	IS-80-0423	A-70567-0087	70567-0121	A-70567-0121	IS-80-042S	A-70567-0155	70567-0189	A-70567-0189						42	
44	IS-80-044I	A-70567-0020	70567-0054	A-70567-0054	IS-80-0443	A-70567-0088	70567-0122	A-70567-0122	IS-80-044S	A-70567-0156	70567-0190	A-70567-0190						44	
46	IS-80-046I	A-70567-0021	70567-0055	A-70567-0055	IS-80-0463	A-70567-0089	70567-0123	A-70567-0123	IS-80-046S	A-70567-0157	70567-0191	A-70567-0191						46	
48	IS-80-048I	A-70567-0022	70567-0056	A-70567-0056	IS-80-0483	A-70567-0090	70567-0124	A-70567-0124	IS-80-048S	A-70567-0158	70567-0192	A-70567-0192						48	
50	IS-80-050I	A-70567-0023	70567-0057	A-70567-0057	IS-80-0503	A-70567-0091	70567-0125	A-70567-0125	IS-80-050S	A-70567-0159	70567-0193	A-70567-0193						50	
52	IS-80-052I	A-70567-0024	70567-0058	A-70567-0058	IS-80-0523	A-70567-0092	70567-0126	A-70567-0126	IS-80-052S	A-70567-0160	70567-0194	A-70567-0194						52	
54	IS-80-054I	A-70567-0025	70567-0059	A-70567-0059	IS-80-0543	A-70567-0093	70567-0127	A-70567-0127	IS-80-054S	A-70567-0161	70567-0195	A-70567-0195						54	
56	IS-80-056I	A-70567-0026	70567-0060	A-70567-0060	IS-80-0563	A-70567-0094	70567-0128	A-70567-0128	IS-80-056S	A-70567-0162	70567-0196	A-70567-0196						56	
58	IS-80-058I	A-70567-0027	70567-0061	A-70567-0061	IS-80-0583	A-70567-0095	70567-0129	A-70567-0129	IS-80-058S	A-70567-0163	70567-0197	A-70567-0197						58	
60	IS-80-060I	A-70567-0028	70567-0062	A-70567-0062	IS-80-0603	A-70567-0096	70567-0130	A-70567-0130	IS-80-060S	A-70567-0164	70567-0198	A-70567-0198						60	
62	IS-80-062I	A-70567-0029	70567-0063	A-70567-0063	IS-80-0623	A-70567-0097	70567-0131	A-70567-0131	IS-80-062S	A-70567-0165	70567-0199	A-70567-0199						62	
64	IS-80-064I	A-70567-0030	70567-0064	A-70567-0064	IS-80-0643	A-70567-0098	70567-0132	A-70567-0132	IS-80-064S	A-70567-0166	70567-0200	A-70567-0200						64	
66	IS-80-066I	A-70567-0031	70567-0065	A-70567-0065	IS-80-0663	A-70567-0099	70567-0133	A-70567-0133	IS-80-066S	A-70567-0167	70567-0201	A-70567-0201						66	
68	IS-80-068I	A-70567-0032	70567-0066	A-70567-0066	IS-80-0683	A-70567-0100	70567-0134	A-70567-0134	IS-80-068S	A-70567-0168	70567-0202	A-70567-0202						68	
70	IS-80-070I	A-70567-0033	70567-0067	A-70567-0067	IS-80-0703	A-70567-0101	70567-0135	A-70567-0135	IS-80-070S	A-70567-0169	70567-0203	A-70567-0203						70	
72	IS-80-072I	A-70567-0034	70567-0068	A-70567-0068	IS-80-0723	A-70567-0102	70567-0136	A-70567-0136	IS-80-072S	A-70567-0170	70567-0204	A-70567-0204						72	

lb_frame.D_P_AM_T Rev. F. 2009/06/17	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
---	----	----	----	----	----	----	----	----	----	----	---	---	---	---	---	---	---	---	---

	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1			
M	ENGINEERING NUMBER A-70567	MANUFACTURE RELEASE STATUS					E REF.	C ±.015 (0.38)				CONNECTOR END PLATING		P.C. BOARD END PLATING		PACKAGING INFORMATION PK-70873-							
												TYPE		D MEAS.	TYPE								F MEAS.
L	-0205/-0238	R.F.M.					.130 (3.30)	.315 (8.00)				TIN		.100 (2.54)	TIN		.050 (1.27)	0018					
	-0239/-0272	R.F.M.					.200 (5.08)	.315 (8.00)				TIN		.100 (2.54)	TIN		.050 (1.27)	0018					
	-0273/-0306	R.F.M.					.130 (3.30)	.315 (8.00)				15 GOLD		.100 (2.54)	TIN		.050 (1.27)	0018					
	-0307/-0340	R.F.M.					.200 (5.08)	.315 (8.00)				15 GOLD		.100 (2.54)	TIN		.050 (1.27)	0018					
K	-0341/-0374	R.F.M.					.130 (3.30)	.315 (8.00)				30 GOLD		.100 (2.54)	TIN		.050 (1.27)	0018					
	-0375/-0408	R.F.M.					.200 (5.08)	.315 (8.00)				30 GOLD		.100 (2.54)	TIN		.050 (1.27)	0018					
J																							

NO. OF CKTS	OPTION "B"		OPTION "B"		OPTION "B"		OPTION "B"		OPTION "B"		OPTION "B"		OPTION "B"								NO. OF CKTS
	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	EDP NUMBER	ENG NUMBER	
06	IS-80-0067	A-70567-0205	70567-0239	A-70567-0239	IS-80-0069	A-70567-0273	70567-0307	A-70567-0307	IS-80-1061	A-70567-0341	70567-0375	A-70567-0375									06
08	IS-80-0087	A-70567-0206	70567-0240	A-70567-0240	IS-80-0089	A-70567-0274	70567-0308	A-70567-0308	IS-80-1081	A-70567-0342	70567-0376	A-70567-0376									08
10	IS-80-0107	A-70567-0207	70567-0241	A-70567-0241	IS-80-0109	A-70567-0275	70567-0309	A-70567-0309	IS-80-1101	A-70567-0343	70567-0377	A-70567-0377									10
12	IS-80-0127	A-70567-0208	70567-0242	A-70567-0242	IS-80-0129	A-70567-0276	70567-0310	A-70567-0310	IS-80-1121	A-70567-0344	70567-0378	A-70567-0378									12
14	IS-80-0147	A-70567-0209	70567-0243	A-70567-0243	IS-80-0149	A-70567-0277	70567-0311	A-70567-0311	IS-80-1141	A-70567-0345	70567-0379	A-70567-0379									14
16	IS-80-0167	A-70567-0210	70567-0244	A-70567-0244	IS-80-0169	A-70567-0278	70567-0312	A-70567-0312	IS-80-1161	A-70567-0346	70567-0380	A-70567-0380									16
18	IS-80-0187	A-70567-0211	70567-0245	A-70567-0245	IS-80-0189	A-70567-0279	70567-0313	A-70567-0313	IS-80-1181	A-70567-0347	70567-0381	A-70567-0381									18
20	IS-80-0207	A-70567-0212	70567-0246	A-70567-0246	IS-80-0209	A-70567-0280	70567-0314	A-70567-0314	IS-80-1201	A-70567-0348	70567-0382	A-70567-0382									20
22	IS-80-0227	A-70567-0213	70567-0247	A-70567-0247	IS-80-0229	A-70567-0281	70567-0315	A-70567-0315	IS-80-1221	A-70567-0349	70567-0383	A-70567-0383									22
24	IS-80-0247	A-70567-0214	70567-0248	A-70567-0248	IS-80-0249	A-70567-0282	70567-0316	A-70567-0316	IS-80-1241	A-70567-0350	70567-0384	A-70567-0384									24
26	IS-80-0267	A-70567-0215	70567-0249	A-70567-0249	IS-80-0269	A-70567-0283	70567-0317	A-70567-0317	IS-80-1261	A-70567-0351	70567-0385	A-70567-0385									26
28	IS-80-0287	A-70567-0216	70567-0250	A-70567-0250	IS-80-0289	A-70567-0284	70567-0318	A-70567-0318	IS-80-1281	A-70567-0352	70567-0386	A-70567-0386									28
30	IS-80-0307	A-70567-0217	70567-0251	A-70567-0251	IS-80-0309	A-70567-0285	70567-0319	A-70567-0319	IS-80-1301	A-70567-0353	70567-0387	A-70567-0387									30
32	IS-80-0327	A-70567-0218	70567-0252	A-70567-0252	IS-80-0329	A-70567-0286	70567-0320	A-70567-0320	IS-80-1321	A-70567-0354	70567-0388	A-70567-0388									32
34	IS-80-0347	A-70567-0219	70567-0253	A-70567-0253	IS-80-0349	A-70567-0287	70567-0321	A-70567-0321	IS-80-1341	A-70567-0355	70567-0389	A-70567-0389									34
36	IS-80-0367	A-70567-0220	70567-0254	A-70567-0254	IS-80-0369	A-70567-0288	70567-0322	A-70567-0322	IS-80-1361	A-70567-0356	70567-0390	A-70567-0390									36
38	IS-80-0387	A-70567-0221	70567-0255	A-70567-0255	IS-80-0389	A-70567-0289	70567-0323	A-70567-0323	IS-80-1381	A-70567-0357	70567-0391	A-70567-0391									38
40	IS-80-0407	A-70567-0222	70567-0256	A-70567-0256	IS-80-0409	A-70567-0290	70567-0324	A-70567-0324	IS-80-1401	A-70567-0358	70567-0392	A-70567-0392									40
42	IS-80-0427	A-70567-0223	70567-0257	A-70567-0257	IS-80-0429	A-70567-0291	70567-0325	A-70567-0325	IS-80-1421	A-70567-0359	70567-0393	A-70567-0393									42
44	IS-80-0447	A-70567-0224	70567-0258	A-70567-0258	IS-80-0449	A-70567-0292	70567-0326	A-70567-0326	IS-80-1441	A-70567-0360	70567-0394	A-70567-0394									44
46	IS-80-0467	A-70567-0225	70567-0259	A-70567-0259	IS-80-0469	A-70567-0293	70567-0327	A-70567-0327	IS-80-1461	A-70567-0361	70567-0395	A-70567-0395									46
48	IS-80-0487	A-70567-0226	70567-0260	A-70567-0260	IS-80-0489	A-70567-0294	70567-0328	A-70567-0328	IS-80-1481	A-70567-0362	70567-0396	A-70567-0396									48
50	IS-80-0507	A-70567-0227	70567-0261	A-70567-0261	IS-80-0509	A-70567-0295	70567-0329	A-70567-0329	IS-80-1501	A-70567-0363	70567-0397	A-70567-0397									50
52	IS-80-0527	A-70567-0228	70567-0262	A-70567-0262	IS-80-0529	A-70567-0296	70567-0330	A-70567-0330	IS-80-1521	A-70567-0364	70567-0398	A-70567-0398									52
54	IS-80-0547	A-70567-0229	70567-0263	A-70567-0263	IS-80-0549	A-70567-0297	70567-0331	A-70567-0331	IS-80-1541	A-70567-0365	70567-0399	A-70567-0399									54
56	IS-80-0567	A-70567-0230	70567-0264	A-70567-0264	IS-80-0569	A-70567-0298	70567-0332	A-70567-0332	IS-80-1561	A-70567-0366	70567-0400	A-70567-0400									56
58	IS-80-0587	A-70567-0231	70567-0265	A-70567-0265	IS-80-0589	A-70567-0299	70567-0333	A-70567-0333	IS-80-1581	A-70567-0367	70567-0401	A-70567-0401									58
60	IS-80-0607	A-70567-0232	70567-0266	A-70567-0266	IS-80-0609	A-70567-0300	70567-0334	A-70567-0334	IS-80-1601	A-70567-0368	70567-0402	A-70567-0402									60
62	IS-80-0627	A-70567-0233	70567-0267	A-70567-0267	IS-80-0629	A-70567-0301	70567-0335	A-70567-0335	IS-80-1621	A-70567-0369	70567-0403	A-70567-0403									62
64	IS-80-0647	A-70567-0234	70567-0268	A-70567-0268	IS-80-0649	A-70567-0302	70567-0336	A-70567-0336	IS-80-1641	A-70567-0370	70567-0404	A-70567-0404									64
66	IS-80-0667	A-70567-0235	70567-0269	A-70567-0269	IS-80-0669	A-70567-0303	70567-0337	A-70567-0337	IS-80-1661	A-70567-0371	70567-0405	A-70567-0405									66
68	IS-80-0687	A-70567-0236	70567-0270	A-70567-0270	IS-80-0689	A-70567-0304	70567-0338	A-70567-0338	IS-80-1681	A-70567-0372	70567-0406	A-70567-0406									68
70	IS-80-0707	A-70567-0237	70567-0271	A-70567-0271	IS-80-0709	A-70567-0305	70567-0339	A-70567-0339	IS-80-1701	A-70567-0373	70567-0407	A-70567-0407									70
72	IS-80-0727	A-70567-0238	70567-0272	A-70567-0272	IS-80-0729	A-70567-0306	70567-0340	A-70567-0340	IS-80-1721	A-70567-0374	70567-0408	A-70567-0408									72

B	SEE SHEETS 1 & 2 EC NO: UCP2010-1587 DRAWN BY: BARBARA 2010/01/12 CHECKED BY: BARBARA 2010/01/12 APPROVED BY: MILLER 2010/03/31										QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	B																														
	mm		INCH		DRAWN BY DATE		TITLE		MOLEX	SDA-70567-****		SHEET NO. 4 OF 5																																					
	4 PLACES ± --- ± ---		EIK 1988/03/10		CHECKED BY DATE		4 SIDES SHROUDED HEADER HIGH TEMP. (2.54)/.100 GRID W/ (.064)/.025 PINS																																										
	3 PLACES ± --- ± .005		EIK 1988/03/10		APPROVED BY DATE		MOLEX INCORPORATED																																										
A	2 PLACES ± 0.13 ± .010		SMILLER 2010/03/31		MATERIAL NO.		DOCUMENT NO.																																										
	1 PLACE ± 0.25 ± ---		ANGULAR ±1/2°		SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																										
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS																																																	
th_frame.D_P_AM_T Rev. F 2009/06/17												19		18		17		16		15		14		13		12		11		10		9		8		7		6		5		4		3		2		1	

