

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0015453408

Status:

Active

Overview:

cgrid_sl_products

Description:

2.54mm (.100") Pitch C-Grid® PCB Connector, Surface Mount, High Profile, Dual Row, Vertical, 8 Circuits

Documents:	
3D Model	Product Specification PS-71395 (PDF)
Drawing (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E29179

General


Product Family	PCB Receptacles
Series	71395
Application	Board-to-Board
Overview	cgrid_sl_products
Product Name	C-Grid®

Physical

Circuits (Loaded)	8
Color - Resin	Black
Durability (mating cycles max)	25
Flammability	94V-0
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	No
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Rows	2
Orientation	Vertical
PC Tail Length (in)	0.058 In
PC Tail Length (mm)	1.47 mm
PCB Locator	Yes
PCB Retention	Yes
Packaging Type	Tray
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Plating min: Mating (µin)	150
Plating min: Mating (µm)	3.75
Plating min: Termination (µin)	150
Plating min: Termination (µm)	3.75
Polarized to PCB	No
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Surface Mount

Electrical

Current - Maximum per Contact	2.5A
Grounding to PCB	No
Voltage - Maximum	250V



Series
image - Reference only

EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

71395Series

Mates With

8624 C-Grid® Breakaway Header, 70246 Straight Header, 70247 Right Angle Header, 70287 C-Grid® Header, 70227 Dual Row C-Grid® Header, 70567 C-Grid® Header, 70280 C-Grid® Breakaway Header, 70524 C-Grid® Breakaway Header, 7

Solder Process Data

Lead-free Process Capability	Reflow Capable (SMT only)
Process Temperature max. C	260

Material Info


Old Part Number	713950008
-----------------	-----------

Reference - Drawing Numbers

Application Specification	AS-71395-001
Packaging Specification	PK-70873-0662
Product Specification	PS-71395
Sales Drawing	SDA-71395-0***

This document was generated on 05/31/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



I3		I2		I1		I0		9		8		7		6		71395		4		3		2		1	
J																									
NO. OF CKTS.		TIN PLATING			15 GOLD PLATING			30 GOLD PLATING																	
PER ROW	TOTAL	E.D.P. NO.	ENG. NO.	STANDARD PACKAGING	E.D.P. NO.	ENG. NO.	STANDARD PACKAGING	E.D.P. NO.	ENG. NO.	STANDARD PACKAGING	DIM. INCH	"A" MM	DIM. INCH	"B" MM	DIM. INCH	"C" MM									
4	8	I5-45-3408	A-71395-0008	PK-70873-0662	I5-45-3508	A-71395-0108	PK-70873-0662	I5-45-3608	A-71395-0208	PK-70873-0662	.300	7,62	.399	10,13	.200	5,08									
5	10	I5-45-3410	A-71395-0010	PK-70873-0662	I5-45-3510	A-71395-0110	PK-70873-0662	I5-45-3610	A-71395-0210	PK-70873-0662	.400	10,16	.499	12,67	.300	7,62									
6	12	I5-45-3412	A-71395-0012	PK-70873-0662	I5-45-3512	A-71395-0112	PK-70873-0662	I5-45-3612	A-71395-0212	PK-70873-0662	.500	12,70	.599	15,21	.400	10,16									
7	14	I5-45-3414	A-71395-0014	PK-70873-0662	I5-45-3514	A-71395-0114	PK-70873-0662	I5-45-3614	A-71395-0214	PK-70873-0662	.600	15,24	.699	17,75	.500	12,70									
8	16	I5-45-3416	A-71395-0016	PK-70873-0662	I5-45-3516	A-71395-0116	PK-70873-0662	I5-45-3616	A-71395-0216	PK-70873-0662	.700	17,78	.799	20,29	.600	15,24									
9	18	I5-45-3418	A-71395-0018	PK-70873-0662	I5-45-3518	A-71395-0118	PK-70873-0662	I5-45-3618	A-71395-0218	PK-70873-0662	.800	20,32	.899	22,83	.700	17,78									
10	20	I5-45-3420	A-71395-0020	PK-70873-0662	I5-45-3520	A-71395-0120	PK-70873-0662	I5-45-3620	A-71395-0220	PK-70873-0662	.900	22,86	.999	25,37	.800	20,32									
11	22	I5-45-3422	A-71395-0022	PK-70873-0662	I5-45-3522	A-71395-0122	PK-70873-0662	I5-45-3622	A-71395-0222	PK-70873-0662	1.000	25,40	1.099	27,91	.900	22,86									
12	24	I5-45-3424	A-71395-0024	PK-70873-0662	I5-45-3524	A-71395-0124	PK-70873-0662	I5-45-3624	A-71395-0224	PK-70873-0662	1.100	27,94	1.199	30,45	1.000	25,40									
13	26	I5-45-3426	A-71395-0026	PK-70873-0662	I5-45-3526	A-71395-0126	PK-70873-0662	I5-45-3626	A-71395-0226	PK-70873-0662	1.200	30,48	1.299	32,99	1.100	27,94									
14	28	I5-45-3428	A-71395-0028	PK-70873-0662	I5-45-3528	A-71395-0128	PK-70873-0662	I5-45-3628	A-71395-0228	PK-70873-0662	1.300	33,02	1.399	35,53	1.200	30,48									
15	30	I5-45-3430	A-71395-0030	PK-70873-0662	I5-45-3530	A-71395-0130	PK-70873-0662	I5-45-3630	A-71395-0230	PK-70873-0662	1.400	35,56	1.499	38,07	1.300	33,02									
16	32	I5-45-3432	A-71395-0032	PK-70873-0662	I5-45-3532	A-71395-0132	PK-70873-0662	I5-45-3632	A-71395-0232	PK-70873-0662	1.500	38,10	1.599	40,61	1.400	35,56									
17	34	I5-45-3434	A-71395-0034	PK-70873-0662	I5-45-3534	A-71395-0134	PK-70873-0662	I5-45-3634	A-71395-0234	PK-70873-0662	1.600	40,64	1.699	43,15	1.500	38,10									
18	36	I5-45-3436	A-71395-0036	PK-70873-0662	I5-45-3536	A-71395-0136	PK-70873-0662	I5-45-3636	A-71395-0236	PK-70873-0662	1.700	43,18	1.799	45,69	1.600	40,64									
19	38	I5-45-3438	A-71395-0038	PK-70873-0662	I5-45-3538	A-71395-0138	PK-70873-0662	I5-45-3638	A-71395-0238	PK-70873-0662	1.800	45,72	1.899	48,23	1.700	43,18									
20	40	I5-45-3440	A-71395-0040	PK-70873-0662	I5-45-3540	A-71395-0140	PK-70873-0662	I5-45-3640	A-71395-0240	PK-70873-0662	1.900	48,26	1.999	50,77	1.800	45,72									
21	42	I5-45-3442	A-71395-0042	PK-70873-0662	I5-45-3542	A-71395-0142	PK-70873-0662	I5-45-3642	A-71395-0242	PK-70873-0662	2.000	50,80	2.099	53,31	1.900	48,26									
22	44	I5-45-3444	A-71395-0044	PK-70873-0662	I5-45-3544	A-71395-0144	PK-70873-0662	I5-45-3644	A-71395-0244	PK-70873-0662	2.100	53,34	2.199	55,85	2.000	50,80									
23	46	I5-45-3446	A-71395-0046	PK-70873-0662	I5-45-3546	A-71395-0146	PK-70873-0662	I5-45-3646	A-71395-0246	PK-70873-0662	2.200	55,88	2.299	58,39	2.100	53,34									
24	48	I5-45-3448	A-71395-0048	PK-70873-0662	I5-45-3548	A-71395-0148	PK-70873-0662	I5-45-3648	A-71395-0248	PK-70873-0662	2.300	58,42	2.399	60,93	2.200	55,88									
25	50	I5-45-3450	A-71395-0050	PK-70873-0662	I5-45-3550	A-71395-0150	PK-70873-0662	I5-45-3650	A-71395-0250	PK-70873-0662	2.400	60,96	2.499	63,47	2.300	58,42									
26	52	I5-45-3452	A-71395-0052	PK-70873-0662	I5-45-3552	A-71395-0152	PK-70873-0662	I5-45-3652	A-71395-0252	PK-70873-0662	2.500	63,50	2.599	66,01	2.400	60,96									
27	54	I5-45-3454	A-71395-0054	PK-70873-0662	I5-45-3554	A-71395-0154	PK-70873-0662	I5-45-3654	A-71395-0254	PK-70873-0662	2.600	66,04	2.699	68,55	2.500	63,50									
28	56	I5-45-3456	A-71395-0056	PK-70873-0662	I5-45-3556	A-71395-0156	PK-70873-0662	I5-45-3656	A-71395-0256	PK-70873-0662	2.700	68,58	2.799	71,09	2.600	66,04									
29	58	I5-45-3458	A-71395-0058	PK-70873-0662	I5-45-3558	A-71395-0158	PK-70873-0662	I5-45-3658	A-71395-0258	PK-70873-0662	2.800	71,12	2.899	73,63	2.700	68,58									
30	60	I5-45-3460	A-71395-0060	PK-70873-0662	I5-45-3560	A-71395-0160	PK-70873-0662	I5-45-3660	A-71395-0260	PK-70873-0662	2.900	73,66	2.999	76,17	2.800	71,12									
31	62	I5-45-3462	A-71395-0062	PK-70873-0662	I5-45-3562	A-71395-0162	PK-70873-0662	I5-45-3662	A-71395-0262	PK-70873-0662	3.000	76,20	3.099	78,71	2.900	73,66									
32	64	I5-45-3464	A-71395-0064	PK-70873-0662	I5-45-3564	A-71395-0164	PK-70873-0662	I5-45-3664	A-71395-0264	PK-70873-0662	3.100	78,74	3.199	81,25	3.000	76,20									
33	66	I5-45-3466	A-71395-0066	PK-70873-0662	I5-45-3566	A-71395-0166	PK-70873-0662	I5-45-3666	A-71395-0266	PK-70873-0662	3.200	81,28	3.299	83,79	3.100	78,74									
34	68	I5-45-3468	A-71395-0068	PK-70873-0662	I5-45-3568	A-71395-0168	PK-70873-0662	I5-45-3668	A-71395-0268	PK-70873-0662	3.300	83,82	3.399	86,33	3.200	81,28									
35	70	I5-45-3470	A-71395-0070	PK-70873-0662	I5-45-3570	A-71395-0170	PK-70873-0662	I5-45-3670	A-71395-0270	PK-70873-0662	3.400	86,36	3.499	88,87	3.300	83,82									
36	72	I5-45-3472	A-71395-0072	PK-70873-0662	I5-45-3572	A-71395-0172	PK-70873-0662	I5-45-3672	A-71395-0272	PK-70873-0662	3.500	88,90	3.599	91,41	3.400	86,36									
37	74	I5-45-3474	A-71395-0074	PK-70873-0662	I5-45-3574	A-71395-0174	PK-70873-0662	I5-45-3674	A-71395-0274	PK-70873-0662	3.600	91,44	3.699	93,95	3.500	88,90									
38	76	I5-45-3476	A-71395-0076	PK-70873-0662	I5-45-3576	A-71395-0176	PK-70873-0662	I5-45-3676	A-71395-0276	PK-70873-0662	3.700	93,98	3.799	96,49	3.600	91,44									
39	78	I5-45-3478	A-71395-0078	PK-70873-0662	I5-45-3578	A-71395-0178	PK-70873-0662	I5-45-3678	A-71395-0278	PK-70873-0662	3.800	96,52	3.899	99,03	3.700	93,98									
40	80	I5-45-3480	A-71395-0080	PK-70873-0662	I5-45-3580	A-71395-0180	PK-70873-0662	I5-45-3680	A-71395-0280	PK-70873-0662	3.900	99,06	3.999	101,57	3.800	96,52									
PLATING:																									
TIN (3.75 MICROMETER)/150 MICROINCH MINIMUM TIN OVER (1.25 MICROMETER)/50 MICROINCH MINIMUM NICKEL OVERALL.																									
15 GOLD (0.37 MICROMETER)/15 MICROINCH MINIMUM SELECTIVE GOLD IN THE CONTACT AREA; (1.88 MICROMETER)/75 MICROINCH MINIMUM SELECTIVE TIN IN THE PC TAIL AREA OVER (1.25 MICROMETER)/50 MICROINCH MINIMUM NICKEL OVERALL.																									
30 GOLD (0.75 MICROMETER)/30 MICROINCH MINIMUM SELECTIVE GOLD IN THE CONTACT AREA; (1.88 MICROMETER)/75 MICROINCH MINIMUM SELECTIVE TIN IN THE PC TAIL AREA OVER (1.25 MICROMETER)/50 MICROINCH MINIMUM NICKEL OVERALL.																									
*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.																									
- VERSION WITH PCB RETENTION PEGS -																									
J I H G E B A LTR. REVISIONS LTR. REVISIONS																									
DIMENSIONS SHOWN (METRIC) INCH UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°																									
3 PLACE ± --- --- 2 PLACE ± --- ± --- 1 PLACE --- ± ---																									
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS																									
DRWG. BY J L CHK'D. BY R B																									
APPR'D. BY SCALE :																									
TITLE CONNECTOR DUAL ROW VERTICAL SURFACE MOUNT TOP ENTRY ON .100 GRID																									
PART NO. MOLEX INCORPORATED LITSEJILL. 60532 SHEET NO. 2 DATE 12 / 18 / 85																									
SEE CHART SDA-71395-0***																									
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																									
I3 I2 I1 I0 9 8 7 6 5 4 3 2 1																									