


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0082186009](#)
Status: **Active**
Description: 3.96mm (.156") Pitch Round Conductor Flat Cable - 18 AWG (7 x 26) Stranded, Tinned, 9 Circuits, Reel 30.48m (100.0') Length



Documents:
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA	LR61126
UL	E61522

General

Product Family	Cable
Series	40174
Crimp Quality Equipment	Yes
Geographic Area	Asia
Product Name	Ribbon

Physical

Cable Length	30.48m (100.0')
Circuits (Loaded)	9
Flammability	VW-1
Insulation	PVC
Packaging Type	Reel
Pitch - Term. Interface (in)	0.156 In
Pitch - Term. Interface (mm)	3.96 mm
Temperature Range - Operating	-20°C to +105°C
Wire Size AWG	18
Wire/Cable Type	(7x26) Stranded, Tinned

Electrical

Current - Maximum per Contact	N/A
Voltage - Maximum	300V

Material Info

Old Part Number	40174-09-100B
-----------------	---------------

Reference - Drawing Numbers

Sales Drawing	SD-40174-001
---------------	--------------

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Halogen-Free
Status
Not Reviewed

China RoHS




Need more information on product environmental compliance?
Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)
Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[40174Series](#)

Use With
[7674](#) KK® IDT Trifurcon Contact. [7675](#) KK® IDT Double Cantilever Contact

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



- NOTE :**
1. THE CABLE SHALL HAVE A MINIMUM OF 0.178mm. (.007") THICKNESS INSULATION AT ANY POINT
 2. RIP TEST:
 - THE 0.13mm. (.005") ZIPPING GROOVE SHALL BE CAPABLE OF BEING RIPPED BY HAND WITHIN THE RECESS, WITHOUT EXPOSING THE ADJACENT CONDUCTORS
 3. RoHS AND LEAD FREE COMPLIANT
 4. SPECIAL REQUIREMENT: N/A

B	B-07-0748	B ₁ : ADD NON-OPERATING TEMP.	07/11/23
A	N/A	INITIAL DRAFT	06/08/09
REV. HISTORY	EC NO.	DETAIL	DATE

SEE CHANGE DETAIL. EC NO: THL2008-0015 DRWN:CPANSAKHOM 2007/11/28 CHKD:DNARINTARA 2007/11/29 APPR:SVIRATJAPOL 2007/12/04	QUALITY SYMBOLS ▽=3 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE MM/IN		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION										
			mm	INCH	DRAWN BY CPANSAKHOM	DATE 2006/08/09	TITLE FCB ROUND CONDUCTOR 3.96MM(.156)CENTERS PVC. 18AWG STRANDED TINNED												
		4 PLACES	± ---	± ---	CHECKED BY PMEECHAI	DATE 2006/08/09													
		3 PLACES	± ---	± ---	APPROVED BY SVIRATJAPOL		DATE 2006/08/09		molex MOLEX INCORPORATED										
		2 PLACES	± ---	± ---															
		1 PLACE	± ---	± ---	MATERIAL NO. SEE CHART					DOCUMENT NO. SD-40174-001					SHEET NO. 1 OF 3				
		ANGULAR ± ---°																	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SIZE A4					THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
REV	DESCRIPTION																		

7 6 5 4 3 2 1

CHART A				SHIPPED ON	
DIMENSIONS MM. (INCHES)				100 FT. REELS	
ENG. NO.	NO.OF COND.	DIMENSION S	DIM. W (REF)	ENGINEERING NO.	ORDER NO.
40174- 2	2	3.96±0.13 (.156±.005)	7.92 (.312)	40174-02-100B	82-18-6002
40174- 3	3	7.92±0.25 (.312±.010)	11.89 (.468)	▲ -03- ▲	▲ 03
40174- 4	4	11.89±0.38 (.468±.015)	15.85 (.624)	-04-	04
40174- 5	5	15.85±0.38 (.624±.015)	19.81 (.780)	-05-	05
40174- 6	6	19.81±0.38 (.780±.015)	23.77 (.936)	-06-	06
40174- 7	7	23.77±0.38 (.936±.015)	27.74 (1.092)	-07-	07
40174- 8	8	27.74±0.38 (1.092±.015)	31.70 (1.248)	-08-	08
40174- 9	9	31.70±0.38 (1.248±.015)	35.66 (1.404)	-09-	09
40174-10	10	35.66±0.38 (1.404±.015)	39.62 (1.560)	-10-	10
40174-11	11	39.62±0.38 (1.560±.015)	43.59 (1.716)	-11-	11
40174-12	12	43.59±0.38 (1.716±.015)	47.55 (1.872)	-12-	12
40174-13	13	47.55±0.38 (1.872±.015)	51.51 (2.028)	-13-	13
40174-14	14	51.51±0.38 (2.028±.015)	55.47 (2.184)	-14-	14
40174-15	15	55.47±0.38 (2.184±.015)	59.44 (2.340)	-15-	15
40174-16	16	59.44±0.38 (2.340±.015)	63.40 (2.496)	▼ -16- ▼	▼ 16

ENGINEERING NO.

40174-XX-XXXX

A B C D

A : CABLE 3.96mm. (.156") CENTERS 18 AWG STRANDED TINNED

B : CONDUCTOR SIZE (AVAILABILITY 2 THROUGH 16)

C : CABLE LENGTH 100FT. (30.48M.)

D : A = INCHES

B = FEET

SEE CHANGE DETAIL EC NO: THL2008-0015 DRWN:CPANSAKHOM 2007/11/28 CHKD:DNARINTARA 2007/11/29 APPR:SVIRATJAPOL 2007/12/04	DESCRIPTION REV	QUALITY SYMBOLS ▽ = C =	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE MM/IN		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
				mm	INCH	DRAWN BY	DATE	TITLE FCB ROUND CONDUCTOR 3.96MM(.156)CENTERS PVC. 18AWG STRANDED TINNED MOLEX INCORPORATED				
			4 PLACES	± ---	± ---	CPANSAKHOM	2006/08/09					
			3 PLACES	± ---	± ---	CHECKED BY	DATE					
			2 PLACES	± ---	± ---	PMEECHAI	2006/08/09					
			1 PLACE	± ---	± ---	APPROVED BY	DATE	MOLEX INCORPORATED				
			ANGULAR ± ---°			SVIRATJAPOL	2006/08/09					
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			MATERIAL NO.		DOCUMENT NO.		SHEET NO.		
						SEE CHART		SD-40174-001		3 OF 3		
						SIZE A 4	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					