molex
one company > a world of innovation

This document was generated on 03/26/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0082244424

Status: Active

Description: 2.00mm (.079") Pitch Round Conductor Flat Cable - 24 AWG (7 x 32) Stranded, Topcoat, 24 Circuits, Reel 30.48m (100.0') Length




image - Reference only

Documents:
Drawing (PDF)
RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR61126
UL	E61522

General

Product Family	Cable
Series	24472
Crimp Quality Equipment	Yes
Geographic Area	Asia
Product Name	Ribbon

Physical

Cable Length	30.48m (100.0')
Circuits (Loaded)	24
Insulation	PVC
Packaging Type	Reel
Pitch - Term. Interface (in)	0.079 In
Pitch - Term. Interface (mm)	2.00 mm
Temperature Range - Operating	-20°C to +105°C
Wire Size AWG	24
Wire/Cable Type	(7x32) Stranded, Topcoat

Electrical

Current - Maximum per Contact	N/A
Voltage - Maximum	300V

Material Info

Old Part Number	24472-24-100B

Reference - Drawing Numbers

Sales Drawing	SD-24472-001

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here


Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
24472Series

Use With
52484 Wire-to-Board, IDT Receptacle Housing

This document was generated on 03/26/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



NOTE :
1. THE CABLE SHALL HAVE A MINIMUM OF 0.178mm. (.007") THICKNESS INSULATION AT ANY POINT
2. RIP TEST:
   - THE 0.13mm. (.005") ZIPPING GROOVE SHALL BE CAPABLE OF BEING RIPPED BY HAND WITHIN THE RECESS,WITHOUT EXPOSING THE ADJACENT CONDUCTORS
3. RoHS AND LEAD FREE COMPLIANT
4. SPECIAL REQUIREMENT: N/A

REV. HISTORY	EC NO.	DETAIL	DATE
B	E-07-0748	B_2: ADD NON-OPERATING TEMP. B_1: ADD SOLDERING CONDITION	07/10/01
A	N/A	NEW RELEASE	06/08/09

SEE CHANGE DETAIL
EC NO: THL2008-0015
DRWN:CPANSAKHOM 2007/11/28
CH'KD:DNARINTARA 2007/11/29
APPR:SVIRATJAPOL 2007/12/04
DESCRIPTION
B
REV

QUALITY SYMBOLS
▼=3
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
SCALE: NTS
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

DRAWN BY: CPANSAKHOM DATE: 2006/08/09
CHECKED BY: PMEECHAI DATE: 2006/08/09
APPROVED BY: SVIRATJAPOL DATE: 2006/08/09

TITLE: FCB ROUND CONDUCTOR 2.00MM(.079)CENTERS PVC. 24AWG STRANDED TOPCOATED

molex MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-24472-001
SHEET NO.: 1 OF 3
SIZE: A4

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SPECIFICATIONS

PHYSICAL

CONDUCTOR SPACING	2.00 (.079") ℄ TO ℄
WIRE GAUGE	24 AWG(7/32) STRANDED TOPCOATED
INSULATION	P.V.C GRAY (LEAD FREE)

AGENCY

U.L. STYLE NO.	2651
TEMPERATURE RATING	-20°C TO 105°C
VOLTAGE RATING	300V.MAX.
FLAMMABILITY RATING	VW-1

ELECTRICAL

CONDUCTOR RESISTANCE (D.C.)	24.0 m OHMS/FT. MAX.
CHARACTERISTIC IMPEDANCE	148 OHMS NOM. (GS) 106 OHMS NOM. (GSG)
CAPACITANCE	8.5 pF/FT. NOM. (GS) 13.4 pF/FT. NOM. (GSG)
PROPAGATION DELAY	1.4 ns/FT. NOM.
INSULATION RESISTANCE	10M OHMS (10FT. SAMPLE)
DIELECTRIC WITHSTAND VOLTAGE	2000 VRMS/MINUTE

GENERAL

△B2 NON-OPERATING TEMPERATURE	-20°C TO 105°C
FAULTS AND/OR SPLICES	1/REEL MAX. 100^{+3}_{-0}FT. ($30.48^{+0.914}_{-0}$ M.)/REEL 20FT. (6.096M.) MIN. LENGTH

△B1 SOLDERING CONDITION

SOLDER TEMPERATURE	260°C. MAX.
SOLDERING TIME	3 SECOND, MAX.
INSULATION SHRINK	2MM. NOM

SEE CHANGE DETAIL
EC NO: THL2008-0015
DRWN:CPANSAKHOM 2007/11/28
CH'KD:DNARINTARA 2007/11/29
APPR:SVIRATJAPOL 2007/12/04
DESCRIPTION
B
REV

QUALITY SYMBOLS
▼ =
△C =

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
SCALE: NTS
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

DRAWN BY	CPANSAKHOM	DATE 2006/08/09
CHECKED BY	PMEECHAI	DATE 2006/08/09
APPROVED BY	SVIRATJAPOL	DATE 2006/08/09

TITLE: FCB ROUND CONDUCTOR 2.00MM(.079)CENTERS PVC. 24AWG STRANDED TOPCOATED

molex MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-24472-001
SHEET NO.: 2 OF 3

SIZE A4

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

CHART A				
DIMENSIONS MM. (INCHES)				
DIM. W (REF.)	DIMENSION S	NO. OF CONDUCTOR	ORDER NO.	ENGINEERING NO.
4.00 (.157)	2.00±0.08 (.079±.003)	2	82-24-4402	24472-02-100B
6.00 (.236)	4.00±0.15 (.157±.006)	3	03	-03-
8.00 (.315)	6.00±0.23 (.236±.009)	4	04	-04-
10.00 (.394)	8.00±0.28 (.315±.011)	5	05	-05-
12.00 (.472)	10.00±0.28 (.394±.011)	6	06	-06-
14.00 (.551)	12.00±0.28 (.472±.011)	7	07	-07-
16.00 (.630)	14.00±0.28 (.551±.011)	8	08	-08-
18.00 (.709)	16.00±0.28 (.630±.011)	9	09	-09-
20.00 (.787)	18.00±0.28 (.709±.011)	10	10	-10-
22.00 (.866)	20.00±0.28 (.787±.011)	11	11	-11-
24.00 (.945)	22.00±0.28 (.866±.011)	12	12	-12-
26.00 (1.024)	24.00±0.28 (.945±.011)	13	13	-13-
28.00 (1.102)	26.00±0.28 (1.024±.011)	14	14	-14-
30.00 (1.181)	28.00±0.28 (1.102±.011)	15	15	-15-
32.00 (1.260)	30.00±0.28 (1.181±.011)	16	16	-16-
34.00 (1.339)	32.00±0.28 (1.260±.011)	17	17	-17-
36.00 (1.417)	34.00±0.28 (1.339±.011)	18	18	-18-
38.00 (1.496)	36.00±0.28 (1.417±.011)	19	19	-19-
40.00 (1.575)	38.00±0.28 (1.496±.011)	20	20	-20-
42.00 (1.654)	40.00±0.28 (1.575±.011)	21	21	-21-
44.00 (1.732)	42.00±0.28 (1.654±.011)	22	22	-22-
46.00 (1.811)	44.00±0.28 (1.732±.011)	23	23	-23-
48.00 (1.890)	46.00±0.28 (1.811±.011)	24	24	-24-
50.00 (1.969)	48.00±0.28 (1.890±.011)	25	25	-25-
52.00 (2.047)	50.00±0.28 (1.969±.011)	26	26	-26-
54.00 (2.126)	52.00±0.28 (2.047±.011)	27	27	-27-
56.00 (2.205)	54.00±0.28 (2.126±.011)	28	82-24-4428	24472-28-100B

ENGINEERING NO.

24472-XX-XXXX
A B C D

A : CABLE 2.00mm. (.079") CENTERS 24AWG STRANDED TOPCOATED
B : CONDUCTOR SIZE (AVAILABILITY 2 THROUGH 28)
C : CABLE LENGTH (100FT.)
D : A = INCHES
B = FEET

SEE CHANGE DETAIL
EC NO: THL2008-0015
DRWN:CPANSAKHOM 2007/11/28
CH'KD:DNARINTARA 2007/11/29
APPR:SVIRATJAPOL 2007/12/04
DESCRIPTION
B
REV

QUALITY SYMBOLS
▼ =
Ⓒ =

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
SCALE: NTS
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

DRAWN BY: CPANSAKHOM DATE: 2006/08/09
CHECKED BY: PMEECHAI DATE: 2006/08/09
APPROVED BY: SVIRATJAPOL DATE: 2006/08/09

TITLE: FCB ROUND CONDUCTOR 2.00MM(.079)CENTERS PVC. 24AWG STRANDED TOPCOATED

MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-24472-001
SHEET NO.: 3 OF 3
SIZE: A4

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION