This document was generated on 06/01/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0192520155
Status: Active
Overview: wire_management_products
Description: 368.30mm (14.500") UV Black Cable Tie, 50 Pound Tensile Strength, 100/Bag



Series image - Reference only

Documents:
Drawing (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	Accessories
Series	19252
Application Tooling Part Link	192940002
Comments	Maximum bundle diameter = 108.97mm (4.29"). Engineering Number N-14-50-0-C-LC
Component Type	Cable Tie
Overview	wire_management_products
Product Name	N/A

Physical

Circuits (Loaded)	N/A
Lock to Mating Part	None
Packaging Type	Bag
Temperature Range - Operating	105°C

Material Info

Old Part Number	N-14-50-0-C-LC

Reference - Drawing Numbers

Sales Drawing	SD-19252-001

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
19252Series

Application Tooling | **FAQ**
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.
Global

Description	Product #
ServiceGrade™ Economy Cable Tie Tool	0192940002

This document was generated on 06/01/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



N-07-50-MH-9-C-XX

(D) N = CABLE TIES

CABLE TIE LENGTH
INCHES
(ROUNDED)

TENSILE STRENGTH
18 = 18 LBS
40 = 40 LBS
50 = 50 LBS
120 = 120 LBS

TIE TYPE
(BLANK) = STANDARD TIE
ID = IDENTIFICATION
MH = MOUNTING HOLE

COLORS
0 = UV BLACK
9 = NATURAL
30 = HEAT STABILIZED

AMOUNT PER PACKAGE
C = 100
D = 500
M = 1000

INTERNAL DESIGNATOR

SALES DRAWING

REMOVE BASE INFO
EC NO: ETC2007-0295
DRWN: TBONANNO 2007/02/13
CH'KD: J.MACNEIL 2007/02/13
APPR: J.MACNEIL 2007/02/14
DESCRIPTION
D
REV

QUALITY SYMBOLS
▼ = 0
▽C = 0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

SCALE	DESIGN UNITS
NTS	INCH

DIMENSION STYLE: IN/MM

THIRD ANGLE PROJECTION

REVISE ON CAD ONLY

DRAWN BY	DATE
B.ENDERL	04/05/11
CHECKED BY	DATE
H.BEITZL	04/05/11
APPROVED BY	DATE
R.DEROSS	04/05/11

TITLE
19252 SERIES
ENGINEERING NUMBERS
CABLE TIES

MOLEX INCORPORATED

MATERIAL NO.	DOCUMENT NO.	SHEET NO.
SEE CHART	SD-19252-001	1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

B