

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0197124001](#)
Status: **Active**
Description: PCB Tab Quick Disconnect, Male, for Wire, Box, Tab 2.79mm (.110") x 0.51mm (.020")

Documents:
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

UL E79133

General

Product Family Quick Disconnects
Series [19712](#)
Crimp Quality Equipment Yes
Product Name PCB Tab
Type Quick Disconnect

Physical

Barrel Type Closed
Gender Male
Glow-Wire Compliant No
Insulation None
Lock to Mating Part None
Material - Plating Mating Tin
Material - Plating Termination Tin
Orientation PCB Straight Tab
Packaging Type Bag
Plating min: Mating (µin) 150
Plating min: Mating (µm) 3.75
Plating min: Termination (µin) 150
Plating min: Termination (µm) 3.75
Polarized to Mating Part No
Tab Thickness 0.51mm (.020")
Tab Width 2.79mm (.110")
Termination Interface: Style Through Hole
Wire Insulation Diameter N/A
Wire Size AWG N/A

Electrical

Voltage - Maximum N/A

Material Info



Series
image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free
Status
Not Reviewed

China RoHS




Need more information on product environmental compliance?
Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)
Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[19712Series](#)


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

©



ISOMETRIC VIEW

RECOMMENDED P.W.B.
HOLE LAYOUT



CUSTOMER
REELING DIRECTION

CUSTOMER DRAWING

E	ADD FINGER ETC200-0-007 BRE 05/21-2000
D	LOGD ORIENTATION ETC200-0-017 05/25/00 JH
	ADDED ORIENTATION ETC200-0-008 8/16/2000 BRE
B	REMOVE NON-PLATED PARTS FROM CHART 100353 07/05 JH
A	RELEASE TO CUSTOMER ET000076 05/05 JH

NOTES:

1. BARE EDGES PERMISSIBLE AT CARRIER CUT OFF.
2. MATERIAL: BRASS.
3. MATERIAL THICKNESS: .020 +.001/-.051 +.003
4. TAB CONFORMS TO NEMA SPECIFICATIONS.
5. ALL DIMENSIONS AND NOTES ARE REFERENCE ONLY UNLESS NOTED.
6. PLATING: 90/10 TIN LEAD (50u in(.31u)m) MIN THICKNESS.
7. FINISH: MATTE

[illegible]