





03 030798-2

Circular connectors with threaded joint M16 acc. to IEC 61076-2-106, IP40/IP67/IP68



SWUM™ chassis socket acc. to IEC 61076-2-106 and AISG specification, IP 68/67, with threaded joint and ground contact, for printed circuit boards, manual soldering, for back side mounting

03 030798-2



Environmental conditions

Temperature range -40 °C/+85 °C

Materials

Insulating body	PA, V-2 according to UL94
Contact bush	CuZn, silver-plated and flash gold-plated, tin-plated in solder area
Ground contact	CuZn, pre-nickel and tin-plated
Housing	Zn diecast, pre-copper and nickel-plated
Ring screw	CuZn, nickel-plated
Seal	NBR

Mechanical data

Insertion force/contact	≤ 5,0 N ¹
Withdrawal force/contact	≥ 1,2 N ¹
Protection class	IP68/67 ²

¹ measured with a polished steel pin, nominal thickness 1,5 mm

² according to IEC 60529/DIN EN 60529

IP68: sealed in locked position; pair of appropriate connectors in locked position is sealed against ingress of dust and moisture.

IP67: sealed when unmated (SWUM™); no dust or moisture can ingress into the inside of the device through an unmated connector accidentally left unprotected.
IPX8 requirements under agreement between user and manufacturer

Electrical data (at T_{amb} 20 °C)

Contact resistance	≤ 5 mΩ
Rated current	5 A (T _{amb} 40 °C)
Rated voltage	60 V
Rated impulse voltage	1 kV/60 s
Material group	II (IEC)/I (UL) (CTI ≥ 450)
Overvoltage category	I
Insulation resistance	> 100 MΩ

Associated products





Counterparts

☞ 0331	☞ 0332	☞ 0332-1
☞ 033200	☞ 0365	☞ 036500

Accessories


☞ 0322 C 16	☞ 0381	☞ 038199
☞ 0384	☞ 0385	☞ 038799

03 030798-2




08-a

- 030798-2 06-1 030798-2 08-1



030798-2 06-1



08-a

030798-2 08-1

- *a nut enclosed separately
- *b for bore hole in printed circuit board $\varnothing 1$ mm
- *c mounting direction
- *d O-ring gasket
- *e ground contact
- *f flat gasket
- *g port in mounting plate
- *h anti-rotation, alternative execution

03 030798-2

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
030798-2 06-1	6	50	100
030798-2 08-1	8	50	100

Packaging:

in a cardboard box