



NOTES:

1. MATERIALS & FINISHES:
BODY = BRASS, NICKEL PLATED
CONTACT = PHOSPHOR BRONZE, GOLD PLATED
INSULATOR = DELRIN
4. PACKAGED IN BAG 999-336.
5. USE AMPHENOL CRIMP TOOL #CTL-2.
6. NON-CAPTIVATED CONTACT, .016 WIRE ENTRY.
7. 3 PC. (BODY, FERRULE, CONTACT).
8. DO NOT SCALE THIS DRAWING.
9. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE AFTER PLATING.

31-71014-RFX

REVISIONS

DRAWING NO.	REV	DESCRIPTION	DATE	ECO	APPR
THIRD ANGLE PROJ. 	--	RELEASE TO MFG.			
	B	SEE SHEET 1	7/28/99	43068	CPM/



RECOMMENDED CABLE
STRIPPING DIM'S

CUSTOMER OUTLINE DRAWING

ENGLISH [METRIC]

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL ±.015 (0,381 mm) 3 PLACE DECIMAL ±.005 (0,127 mm) ANGLES ± 1°	MATERIAL	DRAWN C. McGRATH	DATE 7/8/99	TITLE BNC CRIMP JACK FOR RG-179, 187 CABLE 75 OHM	Amphenol Amphenol Corporation RF/Microwave Operations Danbury, Conn. U.S.A. 06810			
		ENGINEER T. AUBIN	DATE 7/8/99					
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	REFERENCE	APPROVED	DATE					
		CAD FILE H: \DEPT611\BNC\031\ASSY\71014\RFXSH2		CODE ID 74868	DWG SIZE B	DRAWING NO. 31-71014-RFX		REV B