

## Han 3HPR-HBM-SL-black chrome



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 09 40 003 0311                                                                        |
| Specification      | Han 3HPR-HBM-SL-black chrome                                                          |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09400030311">https://b2b.harting.com/09400030311</a> |

### Identification

|                             |                          |
|-----------------------------|--------------------------|
| Category                    | Hoods/Housings           |
| Series of hoods/housings    | Han <sup>®</sup> HPR     |
| Type of hood/housing        | Bulkhead mounted housing |
| Description of hood/housing | Straight                 |

### Version

|                      |                                               |
|----------------------|-----------------------------------------------|
| Locking type         | Screw locking                                 |
| Size                 | 3 A                                           |
| Field of application | Hoods/housings for harsh outdoor environments |
| Pack contents        | With seal screw                               |

### Technical characteristics

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Tightening torque (screw locking)      | 2 Nm                                           |
| Limiting temperature                   | -40 ... +125 °C                                |
| Degree of protection acc. to IEC 60529 | IP65<br>IP68<br>IP69 / IPX9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                                  |

### Material properties

|                         |               |
|-------------------------|---------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing)  | Chromated     |



Pushing Performance

## Material properties

|                             |                      |
|-----------------------------|----------------------|
| Colour (hood/housing)       | RAL 9005 (jet black) |
| Material (seal)             | NBR                  |
| RoHS                        | compliant            |
| ELV status                  | compliant            |
| China RoHS                  | e                    |
| REACH Annex XVII substances | No                   |
| REACH ANNEX XIV substances  | No                   |
| REACH SVHC substances       | No                   |

## Specifications and approvals

|           |                                                            |
|-----------|------------------------------------------------------------|
| Approvals | DNV GL                                                     |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE        | Yes                                                        |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 45 g                                     |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |