




Pushing Performance

Han 24HPR VarioShell-HBMA-SCL-4xM32



Part number	09 40 124 2443
Specification	Han 24HPR VarioShell-HBMA-SCL-4xM32
HARTING eCatalogue	https://b2b.harting.com/09401242443

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] HPR VarioShell
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	Angled

Version

Size	24 HPR
Cable entry	for 1x 24 HPR 4x M32
Field of application	Hoods/housings for harsh outdoor environments

Technical characteristics

Tightening torque	4 Nm Mounting cover 12 Nm Fixing screws 12 Nm PE screw
Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP66 IP67 IP68 IP69

Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)



Pushing Performance

Material properties

Material (seal)	NBR
-----------------	-----

Specifications and approvals

CE	Yes
----	-----

Commercial data

Packaging size	1
Net weight	1,416 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors