

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0901512310

Status:

Active

Overview:

cgrid_sl_products

Description:

2.54mm (.100") Pitch C-Grid III™ PC Board Connector, Dual Row, Vertical, 10 Circuits

Documents:

3D Model

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

General

Product Family

Series

Application

Overview

Product Name

PCB Receptacles

90151

Board-to-Board

cgrid_sl_products

C-Grid III™

Physical

Circuits (Loaded)

Color - Resin

Glow-Wire Compliant

Guide to Mating Part

Keying to Mating Part

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Number of Rows

Orientation

PC Tail Length (in)

PC Tail Length (mm)

PCB Locator

PCB Retention

PCB Thickness Recommended (in)

PCB Thickness Recommended (mm)

Packaging Type

Pitch - Mating Interface (in)

Pitch - Mating Interface (mm)

Plating min: Mating (µin)

Plating min: Mating (µm)

Plating min: Termination (µin)

Plating min: Termination (µm)

Polarized to PCB

Temperature Range - Operating

Termination Interface: Style

10

Black

No

No

None

No

Phosphor Bronze

Gold

Tin

Polyester

2

Vertical

0.114 In

2.90 mm

No

None

0.062 In

1.60 mm

Tube

0.100 In

2.54 mm

30.4

0.76

120

3

No

-55°C to +125°C

Through Hole

Electrical

Current - Maximum per Contact

Grounding to PCB

Voltage - Maximum

3A

No

350V

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-free Process Capability

Max. Cycles at Max. Process Temperature


Process Temperature max. C

5

Wave Capable (TH only)

1

230



Series
image - Reference only

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

90151Series

Mates With

0.64mm (.025") square pins

Material Info





Reference - Drawing Numbers

Sales Drawing


SDA-90151

This document was generated on 05/24/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



SECTION C-C



SECTION C-C

NOTES

- 1) CONTACT-PLATED PHOSPHOR BRONZE.
- 2) HOUSING-15% GLASS FILLED POLYESTER. COLOUR-BLACK.
- 3) COMPATIBLE WITH PCB HOLE PATTERN.
- 4) FOR (0.635)/.025 SQ. MALE PINS THE LENGTH MUST BE (5.65)/.222 MIN & (7.00)/.276 MAX. TO ENSURE GOOD CONNECTION WITH CONTACT.

ADD INSET FOR GATE EC NO: E2009-0250 DRWN:BMAGUIRE CHKD: APPR:BMAGUIRE AH		QUALITY SYMBOLS =0 =0		GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
						DRAWN BY DB		TITLE C-GRID III DUAL ROW VERTICAL P.C. BOARD CONNECTOR		
						CHECKED BY		DATE		
						APPROVED BY		DATE		
REV		DESCRIPTION		4 PLACES ± --- ± ---		21/07/86		MOLEX INCORPORATED SDA-90151 1 OF 5		
				3 PLACES ± --- ± ---						
				2 PLACES ± 0.05 ± ---						
				1 PLACE ± 0.10 ± ---						
				ANGULAR ± ---°		MATERIAL NO.		DOCUMENT NO.		SHEET NO.
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART				
						SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

PART NO.	SEE CHART
DWG. NO.	SDA-90151

PART NO. STRAIGHT PINS	PART NO. KINKED PINS	NO.OF CKTS.	DIM." A"	DIM." B" (^{+0.00} _{-0.30})(^{+0.000} _{-0.012})	QTY. PER TUBE
90151-2X04	90151-3X04	4	(2.54) .100	(5.08) .200	105
▲ ▲ 06	▲ ▲ 06	6	(5.08) .200	(7.62) .300	72
08	08	8	(7.62) .300	(10.16) .400	52
10	10	10	(10.16) .400	(12.70) .500	44
12	12	12	(12.70) .500	(15.24) .600	36
14	14	14	(15.24) .600	(17.78) .700	30
16	16	16	(17.78) .700	(20.32) .800	26
18	18	18	(20.32) .800	(22.86) .900	24
20	20	20	(22.86) .900	(25.40)1.000	22
22	22	22	(25.40)1.000	(27.94)1.100	20
24	24	24	(27.94)1.100	(30.48)1.200	18
26	26	26	(30.48)1.200	(33.02)1.300	16
28	28	28	(33.02)1.300	(35.56)1.400	14
30	30	30	(35.56)1.400	(38.10)1.500	14
32	32	32	(38.10)1.500	(40.64)1.600	13
34	34	34	(40.64)1.600	(43.18)1.700	12
36	36	36	(43.18)1.700	(45.72)1.800	12
38	38	38	(45.72)1.800	(48.26)1.900	11
40	40	40	(48.26)1.900	(50.80)2.000	11
42	42	42	(50.80)2.000	(53.34)2.100	11
44	44	44	(53.34)2.100	(55.88)2.200	10
46	46	46	(55.88)2.200	(58.42)2.300	10
48	48	48	(58.42)2.300	(60.96)2.400	9
50	50	50	(60.96)2.400	(63.50)2.500	8
52	52	52	(63.50)2.500	(66.04)2.600	8
54	54	54	(66.04)2.600	(68.58)2.700	8
56	56	56	(68.58)2.700	(71.12)2.800	7
58	58	58	(71.12)2.800	(73.66)2.900	7
60	60	60	(73.66)2.900	(76.20)3.000	7
▼ ▼ 62	▼ ▼ 62	62	(76.20)3.000	(78.74)3.100	7
90151-2X64	90151-3X64	64	(78.74)3.100	(81.28)3.200	6

90151-XX YY

INDICATES NO. OF CIRCUITS.

- SEE CHART

PLATING CODE.

I = VERSION A.

2 = VERSION E.

3 = VERSION F.

4 = VERSION N.

FOR PREVIOUS
DRAWING ISSUES
SEE MRI.

LEAD FREE CONVERSION NEW BORDER ADDED EC NO. E2004-0610 DRWN: PS-EAHAN 06/01/2004 CHK: APPR: AH	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES: (UNLESS SPECIFIED)		SCALE	DESIGN UNITS ☒ mm ☐ INCH	 THIRD ANGLE PROJECTION	☐ mm INCH ☐ mm INCH ☐ mm ONLY	REVISION ON CAD ONLY	
		MAJOR 	☐ mm ☐ INCH	DRAWN BY & DATE DB 14/ 7/87		TITLE: C-GRID III DUAL ROW VERTICAL P.C. BOARD CONNECTOR				
		CRITICAL 		CHECKED BY & DATE						
				APPROVED BY & DATE		 MOLEX INCORPORATED				
			ANGULAR: ± °		CAD FILENAME SA90151X2 DGN	MATERIAL NO. SEE CHART	DRAWING NO. SDA-90151	SHEET NO. 20F		
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.				SIZE B

PLATING VERSION A

PRE-PLATED HOT DIP TIN

1.0 TO 2.5 μm (.000040" TO .000100").

PLATING VERSION E

1.27 TO 1.78 um (.000050" TO .000070") NICKEL

OVERALL, 0.38 TO 0.64 μm (.000015" TO .000025")

GOLD ON CONTACT AREA (OVER NICKEL).

3 TO 5 μm (.000120" TO .000200") TIN

ON SOLDER TAILS (OVER NICKEL).

PLATING VERSION F.

1.27 TO 1.78 um (.000050" TO .000070") NICKEL

OVERALL, 0.76 TO 1.0 μm (.000030" TO .000040")

GOLD ON CONTACT AREA (OVER NICKEL).

3 TO 5 μm (.000120" TO .000200") TIN

ON SOLDER TAILS (OVER NICKEL).

PLATING VERSION G.

1.27 TO 1.78 um (.000050" TO .000070") NICKEL

OVERALL, 0.125 um MIN. (.000005" MIN.) GOLD FLASH

ON CONTACT AREA (OVER NICKEL).

3 TO 5 μm (.000120" TO .000200") TIN

ON SOLDER TAILS (OVER NICKEL).

PLATING VERSION N.

1.27 TO 1.78 μm (.000050" TO .000070") NICKEL

OVERALL: 0.76 TO 2.6 μm (.000030" TO .000100")

GOLD ON CONTACT AREA (OVER NICKEL).

4 μm (.000120") MINIMUM TIN

ON SOLDER TAILS (OVER NICKEL).

STANDARD PRODUCTS

7132-1283	10	9	8	7	6	5	4	3	2	1
-----------	----	---	---	---	---	---	---	---	---	---