

© COPYRIGHT - By -

1470-19 (3/11)

THIS DRAWING IS UNPUBLISHED.
RELEASED FOR PUBLICATION
ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
HB		-		P	LYR	DESCRIPTION	DATE
				-	-	SEE SHEET 1	-

1-1721768-6	PCH-105L2M-WG	5V	PCH-105L2M-WG	107-79046(TUBE)	p	ACTIVE
1-1721768-5	PCH-124L2M-WG	24V	PCH-124L2M-WG	107-79046(TUBE)	o	ACTIVE
1-1721768-4	PCH-148L2M-WG	48V	PCH-148L2M-WG	107-79019(TRM)	n	OBSOLETE
1-1721768-3	PCH-124L2M-WG	24V	PCH-124L2M-WG	107-79019(TRM)	m	OBSOLETE
1-1721768-2	PCH-112L2M-WG	12V	PCH-112L2M-WG	107-79019(TRM)	l	OBSOLETE
1-1721768-1	PCH-109L2M-WG	9V	PCH-109L2M-WG	107-79019(TRM)	k	OBSOLETE
1-1721768-0	PCH-106L2M-WG	6V	PCH-106L2M-WG	107-79019(TRM)	j	OBSOLETE
1721768-9	PCH-105L2M-WG	5V	PCH-105L2M-WG	107-79019(TRM)	i	OBSOLETE
1721768-8	PCH-103L2M-WG	3V	PCH-103L2M-WG	107-79019(TRM)	h	OBSOLETE
1721768-7	PCH-148L2M-WG	48V	PCH-148L2M-WG	107-79019(TRM)	g	ACTIVE
1721768-6	PCH-124L2M-WG	24V	PCH-124L2M-WG	107-79019(TRM)	f	ACTIVE
1721768-5	PCH-112L2M-WG	12V	PCH-112L2M-WG	107-79019(TRM)	e	ACTIVE
1721768-4	PCH-109L2M-WG	9V	PCH-109L2M-WG	107-79019(TRM)	d	ACTIVE
1721768-3	PCH-106L2M-WG	6V	PCH-106L2M-WG	107-79019(TRM)	c	ACTIVE
1721768-2	PCH-105L2M-WG	5V	PCH-105L2M-WG	107-79019(TRM)	b	ACTIVE
1721768-1	PCH-103L2M-WG	3V	PCH-103L2M-WG	107-79019(TRM)	a	ABSOLUTE
TE PART NO	TE TYPE NAME	PART B	PART A	PACKAGE SPEC	TYPE	P/N STATUS

RELAY TYPE

NOTES:
1.LAST SUFFIX
NON : WASHABLE TYPE
2.LOT NO SYSTEM AS FOLLOWING:
□□□□
WEEK
YEAR

- 3.TERMINAL DIMENSION IS BEFORE SOLDER DIP;
4.FOR THE TIN-PLATING OF THE PINS:
+0.1mm FOR WIDTH,THICKNESS AND DIAMETER.
+0.5mm FOR LENGTH.
5.MARKING FROM INK TO LASER.

6.ADD LOT NO. SYSTEM AS FOLLOWING;

- I, DIGITS FOR DAY OF THE WEEK
1...MONDAY IN THIS WEEK;
2...TUESDAY IN THIS WEEK;
7...SUNDAY IN THIS WEEK
II, DIGITS FOR SHIFT OF THE DAY
1...DAY SHIFT IN THIS DAY;
2...NIGHT SHIFT IN THIS DAY;
III, ONE CHARACTER DISTINGUISH THE LINE IDENTITY, SUCH AS: A,B,...Z

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	KY.DU
DIMENSIONS: mm		CHK	N.Funayama
TOLERANCES UNLESS OTHERWISE SPECIFIED: mm		APVD	C.H.Hsu
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC	
MATERIAL -		APPLICATION SPEC	
FINISH -		WEIGHT	-
		CUSTOMER DRAWING	

TE Connectivity		PCH-L2M(H)-WG CUSTOMER DRAWING	
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C=1721768	-
SCALE 5:1		SHEET 2 of 2	REV D1

		UV RESIN	UV SEAL	16
		EPOXY RESIN	SEAL	15
CLASS F (A)		MW79(A)	MAGNETIC WIRE	14
	SOLDER DIP	CP WIRE	COIL TERMINAL	13
		Ag ALLOY	STATIONARY CONTACT	12
		Ag ALLOY	MOVABLE CONTACT	11
		Cu ALLOY	HINGE SPRING	10
	SOLDER DIP	Cu ALLOY	NO TERMINAL	9
	SOLDER DIP	Cu ALLOY	MOVABLE SPRING	8
UL 94V-0		LCP	CARD	7
UL 94V-0		PET	CASE	6
UL 94HB		PA NYLON	BOBBIN	5
UL 94V-0		PET	BASE	4
	Ni PLATED	STEEL	CORE	3
	CuNi PLATED	STEEL	ARMATURE	2
	CuNi PLATED	STEEL	YOKE	1
INCOMBUSTIBILITY	TREATMENT	MATERIAL	DESCRIPTION	ITEM