


Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du propietaire.
Propriete de c FCI. Droits de reproduction FCI.









SECTION A–A

NOTES:
1. MATERIAL
   1) HOUSING : HIGH TEMP THERMOPLASTIC UL94V-0 (COLOR: BLACK)
   2) TERMINAL : COPPER ALLOY
   3) HOLD DOWN : COPPER ALLOY
2. FINISH
   1) TERMINAL : Au PLATING (CONTACT POINT) OVER 50u" NICKEL
   2) SOLDER TAIL : 50u" min MATT TIN OVER 50u" NICKEL
3. THE HOUSING WILL WITHSTAND EXPOSURE TO 260C FOR 10 SEC. IN A WAVE SOLDER APPLICATION WITH A 1.6MM PCB
4. PRODUCT SPEC: GS-12-494
   PACKING SPEC: GS-14-1283
5. PRODUCT NUMBERING
   10080211 – X 0 0 X LF
   - LF: LEAD FREE
   - 1: TRAY PACKING
   - X: 0: 5u" Au PLATING; 1: G/F Au PLATING; 2: 15u" Au PLATING; 3: 30u" Au PLATING





RECOMMENDED PCB LAYOUT
PCB THICKNESS : 1.6mm

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY	FCI www.fciconnect.com	
ltr	ecn no	dr	date		.X ± 0.38				
A	T08-1073	S.Lin	04/16/08	linear	.XX ± 0.25		projection	title	MICRO S-ATA RECEP R/A, DIP TYPE
B	T08-1167	S.Lin	10/01/08		.XXX ± 0.15				
				angles	0° ±2°				
				dr	STERLING LIN	04/16/08	MM	product family SATA	code TWN
				engr	STERLING LIN	04/16/08		size A4 dwg no 10080211	
				chr	STERLING LIN	04/16/08	scale NA		sheet 1 of 1
				appd	MINERVA WANG	04/16/08			
sheet index	revision sheet	B 1						cage code	

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor.
Property of FCI. Copyright FCI.

Printed: Jul 21, 2010
STATUS Released
PDM: Rev:B

ACAD