Coupler connector - PRC 3-FC-FS6 8-21 HR - 1017635

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Circular connectors (cable-side), Coupler connector, type: Release with tool or by hand (see accessories), Housing material: PPE, color: black, number of positions: 3, Min. wire cross section: 1.5 mm², Max. conductor cross section: 6 mm², nom. voltage: 690 V AC, Rated current: 35 A, Connection method: Screw connection, Type of contact: Socket, Min. cable diameter: 8 mm, Max. cable diameter: 21 mm

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	4 055626 500775
GTIN	4055626500775

Technical data

General data

Number of positions	3
Protection class	II
Color	black
Locking type	Snap-in locking
Insertion/withdrawal cycles	100
Pull-out-force	150 N ± 50 N
Insertion force	30 N ±10 N
Degree of protection (when plugged in)	IP66 / IP68 (2m / 24h) / IP69K

Connection data

Rated current	35 A (With 6 mm² conductor cross section in accordance with IEC 61984)
	35 A (With 6 mm²/AWG 10, in accordance with UL 2238)
Nominal voltage ATD	690 V AC (in accordance with IEC 61984)
	600 V AC (In accordance with UL 2238)
Rated voltage (III/2)	690 V
Conductor cross section flexible min.	1.5 mm²
Conductor cross section flexible max.	6 mm²

Coupler connector - PRC 3-FC-FS6 8-21 HR - 1017635

Technical data

Connection data

Conductor cross section solid min.	1.5 mm²
Conductor cross section solid max.	6 mm²
Stripping length	12 mm
Torque	max. 1 Nm (Contact screw)
Type of contact	Socket
Stripping length of the sheath	50 mm

Material data

Contact material	Cu
Contact surface material	silver-plated
Contact carrier material	PPE
Flammability rating according to UL 94	V0

Standards and Regulations


Flammability rating according to UL 94	V0

Environmental Product Compliance


REACh SVHC	Lead 7439-92-1

Drawings

Diagram




Dimensional drawing




Coupler connector - PRC 3-FC-FS6 8-21 HR - 1017635

Schematic diagram



Connector pin assignment

Schematic diagram



Schematic design

Phoenix Contact 2019 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com