Online data sheet



# IME12-08NNOZW2S

## IME

**INDUCTIVE PROXIMITY SENSORS**

SICK
Sensor Intelligence.



Illustration may differ

## Ordering information

| Type | Part no. |
|---|---|
| IME12-08NN0ZW2S | 1040793 |

Other models and accessories ➜ www.sick.com/IME

## Detailed technical data

### Features

| | |
|---|---|
| **Housing** | Cylindrical thread design |
| **Housing** | Standard |
| **Thread size** | M12<br>1 |
| **Diameter** | Ø 12 mm |
| **Sensing range $S_n$** | 8 mm |
| **Safe sensing range $S_a$** | 6.48 mm |
| **Installation type** | Non-flush |
| **Switching frequency** | 2,000 Hz |
| **Connection type** | Cable, 3-wire, 2 m |
| **Switching output** | NPN |
| **Output function** | NC |
| **Electrical wiring** | DC 3-wire |
| **Enclosure rating** | IP67 [1] |

[1] According to EN 60529.

### Mechanics/electronics

| | |
|---|---|
| **Supply voltage** | 10 V DC ... 30 V DC |
| **Ripple** | ≤ 10 % |
| **Voltage drop** | ≤ 2 V [1] |
| **Current consumption** | ≤ 10 mA [2] |
| **Time delay before availability** | ≤ 100 ms |

[1] At $I_a$ max.
[2] Without load.
[3] Ub and Ta constant.
[4] Of Sr.

| | |
|---|---|
| **Hysteresis** | 5 % ... 15 % |
| **Reproducibility** | ≤ 2 % [3) 4)] |
| **Temperature drift (of $S_r$)** | ± 10 % |
| **EMC** | According to EN 60947-5-2 |
| **Continuous current $I_a$** | ≤ 200 mA |
| **Cable material** | PVC |
| **Short-circuit protection** | ✓ |
| **Reverse polarity protection** | ✓ |
| **Power-up pulse protection** | ✓ |
| **Shock and vibration resistance** | 30 g, 11 ms/10 Hz ... 55 Hz, 1 mm |
| **Ambient operating temperature** | –25 °C ... +75 °C |
| **Housing material** | Metal, Nickel-plated brass |
| **Sensing face material** | Plastic, Plastic |
| **Housing length** | 63 mm |
| **Thread length** | 43 mm |
| **Tightening torque, max.** | ≤ 12 Nm |
| **UL File No.** | NRKH.E181493 |

[1)] At $I_a$ max.
[2)] Without load.
[3)] Ub and Ta constant.
[4)] Of Sr.

## Reduction factors

| | |
|---|---|
| **Note** | The values are reference values which may vary |
| **St37 steel (Fe)** | 1 |
| **Stainless steel (V2A, 304)** | Approx. 0.8 |
| **Aluminum (Al)** | Approx. 0.45 |
| **Copper (Cu)** | Approx. 0.4 |
| **Brass (Br)** | Approx. 0.4 |

## Installation note

| | |
|---|---|
| **Remark** | Associated graphic see "Installation" |
| **A** | 12 mm |
| **B** | 24 mm |
| **C** | 12 mm |
| **D** | 24 mm |
| **E** | 16 mm |
| **F** | 64 mm |


## Classifications


| | |
|---|---|
| **ECl@ss 5.0** | 27270101 |
| **ECl@ss 5.1.4** | 27270101 |
| **ECl@ss 6.0** | 27270101 |
| **ECl@ss 6.2** | 27270101 |

| | |
|---|---|
| **ECl@ss 7.0** | 27270101 |
| **ECl@ss 8.0** | 27270101 |
| **ECl@ss 8.1** | 27270101 |
| **ECl@ss 9.0** | 27270101 |
| **ETIM 5.0** | EC002714 |
| **ETIM 6.0** | EC002714 |
| **UNSPSC 16.0901** | 39122230 |

## Installation note


Non-flush installation





## Connection diagram

cd-003




## Dimensional drawing (Dimensions in mm (inch))

IME12 standard, cable, non-flush




① Connection
② Indication LED
③ Fastening nuts (2x); width across 17, metal

## Recommended accessories

Other models and accessories ➜ www.sick.com/IME

| | Brief description | Type | Part no. |
|---|---|---|---|
| Universal bar clamp systems | | | |
|  | Universal bar clamp for mounting bars with 12 mm diameter, Zinc diecast, without mounting plate and screws | BEF-KHS-KH3 | 5322626 |
| Mounting brackets and plates | | | |
|  | Mounting plate for M12 sensors, steel, zinc coated, without mounting hardware | BEF-WG-M12 | 5321869 |
|  | Mounting bracket for M12 sensors, steel, zinc coated, without mounting hardware | BEF-WN-M12 | 5308447 |
| Terminal and alignment brackets | | | |
|  | Clamping block for round sensors M12, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included | BEF-KH-M12 | 2051479 |
| | Clamping block for round sensors M12, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included | BEF-KHF-M12 | 2051480 |

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

# WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com