




precip-dip

## DIL SOCKETS

**SERIES**  
**110**

**110-PP-628-41-001101**  
2.54 mm, Solder tail

Open frame standard low profile DIL Sockets



### TECHNICAL SPECS.:

|                     |                                            |
|---------------------|--------------------------------------------|
| Insulator           | Black glass filled polyester PCT-GF30-FR   |
| Flammability        | UL 94V-O                                   |
| Sleeve              | Brass CuZn36Pb3 (C36000)                   |
| Contact             | Clip (4 finger): Beryllium copper (C17200) |
| Accepted pin Ø      | 0.40 to 0.56 mm                            |
| Insertion Forces    | 2 N typ.                                   |
| Withdrawal Forces   | 1 N typ. (polished steel gauge Ø 0.43 mm)  |
| Mechanical life     | Min. 100 cycles                            |
| Rated current       | 1 A                                        |
| Contact resistance  | Max. 10 m                                  |
| Dielectric strength | Min. 1000 V RMS                            |

### ORDERING INFORMATION:

|                 |        |              |
|-----------------|--------|--------------|
| PP Plating code | Sleeve | Clip         |
| 87              | Tin    | Gold flash   |
| 83              | Tin    | Gold 0.75 µm |

### ADVANCED INFORMATION:

| Order Codes          | Poles | A    | B    | C    | D | E | See |
|----------------------|-------|------|------|------|---|---|-----|
| 110-PP-210-41-001101 | 10    | 12.6 | 5.08 | 7.6  |   |   |     |
| 110-PP-304-41-001101 | 4     | 5.0  | 7.62 | 10.1 |   |   |     |
| 110-PP-306-41-001101 | 6     | 7.6  | 7.62 | 10.1 |   |   |     |
| 110-PP-308-41-001101 | 8     | 10.1 | 7.62 | 10.1 |   |   |     |

|                      |     |      |       |      |
|----------------------|-----|------|-------|------|
| 110-PP-310-41-001101 | 10  | 12.6 | 7.62  | 10.1 |
| 110-PP-312-41-001101 | 12  | 15.2 | 7.62  | 10.1 |
| 110-PP-314-41-001101 | 14  | 17.7 | 7.62  | 10.1 |
| 110-PP-316-41-001101 | 16  | 20.3 | 7.62  | 10.1 |
| 110-PP-318-41-001101 | 18* | 22.8 | 7.62  | 10.1 |
| 110-PP-320-41-001101 | 20* | 25.3 | 7.62  | 10.1 |
| 110-PP-322-41-001101 | 22* | 27.8 | 7.62  | 10.1 |
| 110-PP-324-41-001101 | 24* | 30.4 | 7.62  | 10.1 |
| 110-PP-328-41-001101 | 28  | 35.5 | 7.62  | 10.1 |
| 110-PP-420-41-001101 | 20  | 25.4 | 10.16 | 12.6 |
| 110-PP-422-41-001101 | 22  | 27.8 | 10.16 | 12.6 |
| 110-PP-424-41-001101 | 24  | 30.4 | 10.16 | 12.6 |
| 110-PP-428-41-001101 | 28  | 35.5 | 10.16 | 12.6 |
| 110-PP-432-41-001101 | 32  | 40.6 | 10.16 | 12.6 |
| 110-PP-610-41-001101 | 10  | 12.7 | 15.24 | 17.7 |
| 110-PP-624-41-001101 | 24* | 30.5 | 15.24 | 17.7 |
| 110-PP-628-41-001101 | 28* | 35.5 | 15.24 | 17.7 |
| 110-PP-632-41-001101 | 32* | 40.6 | 15.24 | 17.7 |
| 110-PP-636-41-001101 | 36  | 45.7 | 15.24 | 17.7 |
| 110-PP-640-41-001101 | 40* | 50.8 | 15.24 | 17.7 |
| 110-PP-642-41-001101 | 42  | 53.3 | 15.24 | 17.7 |
| 110-PP-648-41-001101 | 48* | 60.9 | 15.24 | 17.7 |
| 110-PP-650-41-001101 | 50  | 63.5 | 15.24 | 17.7 |
| 110-PP-652-41-001101 | 52  | 66.0 | 15.24 | 17.7 |
| 110-PP-950-41-001101 | 50  | 63.5 | 22.86 | 25.3 |
| 110-PP-952-41-001101 | 52  | 66.0 | 22.86 | 25.3 |
| 110-PP-964-41-001101 | 64  | 81.2 | 22.86 | 25.3 |

# TECHNICAL ASSISTANCE

## GENERAL SPECIFICATIONS:

The values listed below are general specs applying for PRECI-DIP DIL sockets. Please see individual catalog page for additional and product specific technical data.

|                             |                  |
|-----------------------------|------------------|
| Operating temperature range | -55 ... +125 °C  |
| Climatic category (IEC)     | 55/125/21        |
| Operating humidity range    | annual mean 75 % |
| Max working voltage         | 100 VRMS/150 VDC |

PRECI-DIP sockets are recognized by Underwriters Laboratories Inc. and listed under "Connectors for Use in Data, Signal, Control and Power Applications", File Nr. E174442.

## MECHANICAL CHARACTERISTICS:

|                                   |                                                       |
|-----------------------------------|-------------------------------------------------------|
| Clip retention                    | Min. 40 N (no displacement under axial force applied) |
| Contact (sleeve / clip) retention | Min. 3.3 N acc. to MIL-DTL-83734, pt 4.6.4.2          |

## ELECTRICAL CHARACTERISTICS:

|                                                              |                                                  |
|--------------------------------------------------------------|--------------------------------------------------|
| Insulation resistance between any two adjacent contacts      | Min. 10'000 M at 500 V AC                        |
| Capacitance between any two adjacent contacts                | Max. 1 pF                                        |
| Air and creepage distances between any two adjacent contacts | Min. 0.6 mm (Min. 0.2 mm FOR SHRINK-DIP SOCKETS) |

## ENVIRONMENTAL CHARACTERISTICS:

The sockets withstand the following environmental tests without mechanical and electrical defects:

- Dry heat steady state IEC 60512-11-9.11i / 60068-2-2.Bb: 125 °C, 16h
- Damp heat cyclic IEC 60512-11-12.11m / 60068-2-30.Db: 25/55 °C, 90 – 100 %rH, 1 cycle of 24 h
- Cold steady state IEC 60512-11-10.11j / 60068-2-1.A: -55 °C, 2 h
- Thermal shock IEC 60512-11-4.11d / 60068-2-14.Na: -55/125 °C, 5 cycles 30 min
- Sinusoidal vibrations IEC 60512-6-4.6d / 60068-2-6.Fc: 10 to 500 Hz, 10 g, 1 octave/min, 10 cycles for each axis
- Shock IEC 60512-6-3.6c / 60068-2-27.Ea: 50 g, 11 ms, 3 shocks in three axis

During the above two tests no contact interruption >50 ns does appear.

- Solderability J-STD-002A, Test A, 245°C, 5 s solder alloy SnAg3.8Cu0.7
- Resistance to soldering heat J-STD-0020C, 260°C, 20 s
- Moisture sensitivity J-STD-020C level 1
- Resistance to corrosion :
  - 1) Salt spray test IEC 60068-2-11.Ka: 48 h
  - 2) Sulfur dioxide (SO<sub>2</sub>) test IEC 60068-2-42 Kc: 96 h at 25 ppm SO<sub>2</sub>, 25 °C, 75 %rH
  - 3) Hydrogen sulfide (H<sub>2</sub>S) test IEC 60068-2-43 Kd: 96 h at 12 ppm H<sub>2</sub>S, 25 °C, 75 %rH

## SOLDERLESS COMPLIANT PRESS-FIT CHARACTERISTICS:

### PRESS-FIT CHARACTERISTICS MEASURED ACC. TO IEC 60352-5

- Press-in force: 90 N max. (at min. hole dia.) / 65 N typ.
- Push-out force: 30 N min. (at max. hole dia.) / 50 N typ.
- Push-out 3rd cycle: 20 N min. (at max. hole dia.)

### PCB HOLE DIMENSIONS

- 2.54 mm grid: Finished hole Ø: 1 + 0.09/-0.06 mm | Drilled hole Ø: 1.15 ± 0.02 mm

## **PCB HOLE PLATING**

- PCB surface finish: Hole plating
- Tin: 5-15 µm tin over min. 25 µm copper
- Copper: min. 25 µm copper
- Gold over nickel: 0.05-0.2 µm gold over 2.5-5 µm nickel over min. 25 µm copper

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Preci-dip:

[110-83-628-41-001101](#) [110-87-628-41-001101](#)