
ADELS contact

Screw-Screwless Connectors

900-07 RZ/ 1



Terminal Block, 1 pole, Fixing: Catch Pin, Clamping Units per Pole: 2, Voltage Rating: 450 V, Current Rating: 17.5 A, Cross-Section Rating External: 2.5 mm², Cross-Section Rating Internal: 1.5 mm²

Order Info

Reference Number (ref. no.)	114801
Applications	Lighting, Electrical Appliances
PU	500
EAN	4028012104864

Type

Type	Terminal Block
Number of poles	1 pole
Clamping Units per Pole	2
Colour	white
Cross-Section	1.5 / 2.5 mm²
Connection Type	Screw-screwless

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Spring Steel, Steel
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Assembly Contact Screw	0.8x4.0 / ↻ 0.5 Nm
Internal Core Cross-Section max.	2.5 mm²
Internal Stripping Length	7.0-7.5 mm
External Stripping Length	8.0-8.5 mm
Fixing	Catch Pin
Internal Core Cross-Section min.	0.5 mm²
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes
Cross-Section Rating External	2.5 mm²
Cross-Section Rating Internal	1.5 mm²

Accessories

ZEL 110	196420