






1.25mm (0.049") PITCH CONNECTOR

Wire-to-Board
Housing

12505HS Series



TERMINAL ASSEMBLY DRAWING



AWG : #28 ~ #32

Material

I/NO	DESCRIPTION	TITLE	MATERIAL
1	HOUSING	12505HS	PA66, UL 94V Grade

Available Pin

PARTS NO.	A	B	C
12505HS-02000	4.25	2.95	1.25
12505HS-03000	5.50	4.20	2.50
12505HS-04000	6.75	5.45	3.75
12505HS-05000	8.00	6.70	5.00
12505HS-06000	9.25	7.95	6.25
12505HS-07000	10.50	9.20	7.50
12505HS-08000	11.75	10.45	8.75
12505HS-09000	13.00	11.70	10.00
12505HS-10000	14.25	12.95	11.25
12505HS-11000	15.50	14.20	12.50
12505HS-12000	16.75	15.45	13.75
12505HS-13000	18.00	16.70	15.00
12505HS-14000	19.25	17.95	16.25
12505HS-15000	20.50	19.20	17.50

Specification

ITEM	SPEC
Voltage Rating	AC/DC 125V
Current Rating	AC/DC 1A
Operating Temperature	-25℃~+85℃
Contact Resistance	30mΩ MAX
Withstanding Voltage	AC250V/1min
Insulation Resistance	100MΩ MIN
Applicable Wire	AWG #28~#32
Applicable P.C.B	-
Applicable FPC/FFC	-
Solder Height	-
Crimp Tensile Strength	-
UL FILE NO	E108706

Application Terminal : 12505TS (32 Page)