# Housing - HC-B 10-TFL-N-M1PG16S - 1460038

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Sleeve housing, for single locking latch, height: 56 mm, with screw connection, 1 x Pg16, lateral cable outlet

RoHS

## Key Commercial Data

| | |
|---|---|
| Packing unit | 10 pc |
| GTIN | 4 046356 793186 |
| GTIN | 4046356793186 |

## Technical data

### Dimensions

| | |
|---|---|
| Height | 56 mm |
| Width | 43 mm |
| Length | 73 mm |
| Wrench size, union nut | 22 mm |
| External cable diameter | 7.5 mm ... 15 mm |

### Ambient conditions

| | |
|---|---|
| Degree of protection of housing (IP) | IP65 |
| Ambient temperature (operation) | -40 °C ... 125 °C |

### General

| | |
|---|---|
| Note | For contact inserts HC-B10, BB18, DD42, M, K8/24 |
| Size | B10 |
| Housing type | Sleeve housing |
| Locking type | for single locking latch |
| No. of cable outlets | 1 |
| Cable outlet | lateral |
| Screw connection | with |
| Type of the screw connection | 1x Pg16 |

# Housing - HC-B 10-TFL-N-M1PG16S - 1460038

## Technical data

### General

| | |
|---|---|
| Housing material | Aluminum die-cast |
| Housing surface material | Powder-coated, gray |
| Cable gland material | Nickel-plated brass |
| Cable seal material | NBR |

### Environmental Product Compliance

| | |
|---|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

## Drawings

Dimensional drawing




Dimensional drawing

## Approvals

### Approvals

Approvals

EAC

Ex Approvals

### Approval details

| | | |
|---|---|---|
| EAC | EAC | RU C-DE.AI30.B.01102 |

Phoenix Contact 2019 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com