ADELS contact

Connectors System AC 164
Panel Mounting

AC 164 EST/ 3 black



Plug, 3 pole, black, Coding: 1 (Mains), Voltage Rating: 250 V, Current Rating: 16 A, Cross-Section: 1.5 mm², Wall Thickness min.: 0.5 mm, Wall Thickness max.: 1.2 mm

Order Info

Reference Number (ref. no.)	148763
Applications	Lighting, Installation, Electrical Appliances
PU	200
EAN	4028012126460

Type

Type	Plug
Number of poles	3 pole
Clamping Units per Pole	1
Colour	black
Coding	1 (Mains)
Cross-Section	1.5 mm²
Connection Type	Screw
PE Function	yes
Protection Against Incorrect Plugging	yes
Latch	yes

Technical Data

Voltage Rating	250 V
Current Rating	16 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.5 mm²
Core Cross-Section max.	1.5 mm²
Impulse Voltage Rating	4.0 kV
Flammability Rating	V-2
max. Ambient Temperature Operation	70 °C
IP Code	IP20
IP Code when Plugged	IP40
Type of Conductor Solid	yes
Type of Conductor Flexible	yes

Type of Conductor Stranded	yes
Stripping Length	7.0 mm
Assembly Contact Screw	PZ 1 / ↻ 0.5 Nm
Wall Thickness min.	0.5 mm
Wall Thickness max.	1.2 mm
Approbation EN61535	AC 164_EN61535_20190125_DEKRA_ENEC_71-107174_web.pdf
Approbation UL	160_163_AC164_AC166_20011003_20170727_UL_E220480_Sec.1-(