




APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-	7790	RELEASED	5/10/07	
A		REVISED SPEC.	2/22/12	



RECOMMENDED
PCB LAYOUT

SPECIFICATIONS:

Material:

Insulator: Hi-temp thermoplastic, rated UL 94V-0

Insulator color: Natural

Contacts: Brass

Plating:

Tin over Nickel underplate overall

Electrical:

Operating voltage: 350 V AC/DC

Current rating: 3 V AC/DC

Contact resistance: 20 mohms max

Insulation resistance: 1000 Mohms min

Dielectric withstanding voltage: 500 VAC for 1 minute

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant.



Positions: 02 thru 15
A=.059 [1.50] X No. of (Positions -1)
B=.059 [1.50] X No. of (Positions -1) + .110 [2.80]

ADAM TECH

909 Railway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: MX1.5mm WAFER 90°, SURFACE MOUNT

2 THRU 15 POSITIONS

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED				ADAM TECH			
INCHES				909 Rahway Avenue, Union, NJ 07083			
HOLES				Phone: 908-687-5000 Fax: 908-687-5710			
.X	± .10	Ø.X	± .10	TITLE MX1.5mm WAFER 90°, SURFACE MOUNT 2 THRU 15 POSITIONS			
.XX	± .020	Ø.XX	± .015				
.XXX	± .015	Ø.XXX	± .010				
APPROVALS							
DRAWN	BW		5/10/07	SIZE	PART NO.		REV.
CHECKED				X	15SH-B-X-X-TR-SMT		A
APPROVED				REF:	SCALE: NTS	SHEET 1 OF 1	