

FEATURES :

- 2:1Wide Input Voltages Range
- High Efficiency up to 85%
- Regulated Output Types
- Low Ripple And Noise
- Internal SMD Construction
- Operating Temperature:-40~+85°C
- Industry Standard Pinout
- Continuous Short Circuit Protection With Current Foldback

Specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified

Part Number	Input Voltage	Output Voltage	Output Current	Efficiency
	Vdc	Vdc	mA	%TYP
16D-05D05RNL	5-9	±5	±100	60
16D-05D09RNL	5-9	±9	±56	70
16D-05D12RNL	5-9	±12	±42	70
16D-05D15RNL	5-9	±15	±34	70
16D-05D24RNL	5-9	±24	±21	70
16D-12D05RNL	9-18	±5	±100	70
16D-12D09RNL	9-18	±9	±56	80
16D-12D12RNL	9-18	±12	±42	80
16D-12D15RNL	9-18	±15	±34	80
16D-12D24RNL	9-18	±24	±21	80
16D-24D05RNL	18-36	±5	±100	75
16D-24D09RNL	18-36	±9	±56	80
16D-24D12RNL	18-36	±12	±42	80
16D-24D15RNL	18-36	±15	±34	80
16D-24D24RNL	18-36	±24	±21	80
16D-48D05RNL	36-72	±5	±100	70
16D-48D09RNL	36-72	±9	±56	80
16D-48D12RNL	36-72	±12	±42	80
16D-48D15RNL	36-72	±15	±34	80
16D-48D24RNL	36-72	±24	±21	80

Input Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Types	Vo, Io Nom			2:1	
Filter	Capacitor				

YUAN DEAN SCIENTIFIC



DC-DC Converter


16D-Dual SERIES

1Watt 1KV Isolated


2 : 1 Input Voltage Range

Dual Output

SIP8



Temperature Derating Graph



www.yds.com.tw



TEL : 886-6-3842899 FAX : 886-6-3843288
E-MAIL : ydsweb@yds.com.tw

Rev:1 2018/10/04

Output Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Tolerance	100% full load			±3	%
Short Circuit Protection	Continuous				
Line Regulation	Regulated			±0.5	%
Load Regulation	Regulated			±0.8	%
Ripple & Noise	Output:5-9V TYPES BW=DC To 20MHz			100	mVp-p
Ripple & Noise	Output:12-24V TYPES BW=DC To 20MHz		1% of Vout		mVp-p
Transient response setting time	50% load step change		350		us

General Specifications


Parameters	Conditions	Min	Typ	Max	Units
Isolation Resistance	500Vdc	1000			MΩ
Switching Frequency	Full load, nominal input		100		KHz
Operating Temperature		-40		85	°C
Humidity	Non Condensing			95	%
Cooling	Free air Convection				
Case material	DAP				
MTBF	MIL-HDBK-217F @25°C	1500000			Hours
Weight			4.5		g
Dimensions		21.8x9.2x11.1			mm

Part Number

16D - 05 D 05 R NL
A B C D E F


A:Series
B:Input Voltage
C: Dual Output
D: Output Voltage
E: Regulated(R)
F: RoHS Version

Recommended Test Circuit




1. When open or high impedance, the converter works well; When this pin is 'high', the converter shut down. It should be note that the input current should be between 5-10mA, exceeding the maximum 20mA will cau permanent damage to the converter.
2. To make sure the product work at perfect operation status with full loading external capacitor is necessary and it is recommended to use high frequency low resistance electrolytic capacitor.

Packaging



Size(mm)			
A	B	C	D
12.0	28.55	550	6.00

Markings and dimensions



PIN Connection

Pin	1	2	3	5	6	7	8
Dual	-Vin	+Vin	Ctrl-Control input can (can be left open)	NE-No external connection allowed	+Vout	COM	-Vout

www.yds.com.tw



TEL : 886-6-3842899 FAX : 886-6-3843288

E-MAIL : ydsweb@yds.com.tw

Rev:1 2018/10/04