Extract from the online catalog

# MSTB 2,5/ 3-ST BD: 1-3

Order No.: 1765344

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1765344

Plug component, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Connection type: Screw connection, Color: green

| Commercial data | |
|---|---|
| EAN | 4017918213015 |
| Pack | 50 pcs. |
| Customs tariff | 85366990 |
| Weight/Piece | 0.00542 KG |

Product notes

WEEE/RoHS-compliant since: 01/01/2003

http://www.download.phoenixcontact.com
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Certificates / Approvals

| | |
|---|---|
| Certification | CB, CSA, CUL, UL, VDE-PZI |

**CSA**

| | |
|---|---|
| Nominal voltage $U_N$ | 300 V |
| Nominal current $I_N$ | 10 A |
| AWG/kcmil | 28-12 |

**CUL**

| | |
|---|---|
| Nominal voltage $U_N$ | 300 V |
| Nominal current $I_N$ | 10 A |
| AWG/kcmil | 30-12 |

**UL**

| | |
|---|---|
| Nominal voltage $U_N$ | 300 V |
| Nominal current $I_N$ | 10 A |
| AWG/kcmil | 30-12 |

## Accessories

| Item | Designation | Description |
|---|---|---|
| **Bridges** | | |
| 1733172 | EBP 3- 5 | Insertion bridge, fully insulated, for plug connectors with 5.0 or 5.08 mm pitch, no. of positions: 3 |
| **General** | | |
| 1733169 | EBP 2- 5 | Insertion bridge, fully insulated, for plug connectors with 5.0 or 5.08 mm pitch, no. of positions: 2 |
| 1803947 | KGG-MSTB 2,5/ 3 | Cable housing, Number of positions: 3, Dimension a: 15 mm, Color: green |
| **Marking** | | |
| 1051993 | B-STIFT | Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm |
| 0804183 | SK 5/3,8:FORTL.ZAHLEN | Marker card, printed horizontally, self-adhesive, 12 identical decades marked 1-10, 11-20 etc. up to 91-(99)100, sufficient for 120 terminal blocks |
| 0805072 | SK 5/3,8:SO | Marker card, special printing, self-adhesive, labeled acc. to customer requirements, 12 identical marker strips per card, max. 25-position labeling per strip, color: white |
| 0805409 | SK 5/3,8:UNBEDRUCKT | Marker cards, unprinted, with pitch divisions, self-adhesive, 10-section marker strips, 12 strips per card, can be labeled with the M-PEN |
| **Plug/Adapter** | | |
| 1734634 | CP-MSTB | Keying profile, is inserted into the slot on the plug or inverted header, red insulating material |

**Tools**

| | | |
|---|---|---|
| 1205053 | SZS 0,6X3,5 | Screwdriver, bladed, matches all screw terminal blocks up to 4.0 mm² connection cross section, blade: 0.6 x 3.5 mm, without VDE approval |

## Additional products

| Item | Designation | Description |
|---|---|---|
| **General** | | |
| 0707112 | DFK-MSTB 2,5/ 3-G | Plug component, Nominal current: 12 A, Nom. voltage: 320 V, Nom. voltage: 320 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Direct mounting |
| 1899854 | EMSTBA 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Assembly: Press-in |
| 1914865 | EMSTBVA 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 200 V, Pitch: 5 mm, Number of positions: 3, Assembly: Press-in |
| 1762059 | MDSTB 2,5/ 3-G | Header, Nominal current: 10 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1736687 | MDSTB 2,5/ 3-G1 | Header, Nominal current: 10 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1846522 | MDSTBA 2,5/ 3-G | Header, Nominal current: 10 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Assembly: Soldering |
| 1763045 | MDSTBV 2,5/ 3-G | Header, Nominal current: 10 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1736726 | MDSTBV 2,5/ 3-G1 | Header, Nominal current: 10 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1845798 | MDSTBVA 2,5/ 3-G | Header, Nominal current: 10 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Assembly: Soldering |
| 1802427 | MDSTBW 2,5/ 3-G | Header, Nominal current: 10 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Assembly: Soldering |
| 1754452 | MSTB 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1768192 | MSTB 2,5/ 3-G-LA | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Assembly: Soldering |
| 1757488 | MSTBA 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1770494 | MSTBA 2,5/ 3-G-LA | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Assembly: Soldering |
| 1753453 | MSTBV 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1755529 | MSTBVA 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |

| | | |
|---|---|---|
| 1736108 | MSTBW 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1769243 | SMSTB 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |
| 1769816 | SMSTBA 2,5/ 3-G | Header, Nominal current: 12 A, Nom. voltage: 250 V, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly: Soldering |

## Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057,USA
Phone (800) 888-7388
Fax (717) 944-1625
http://www.phoenixcon.com

© 2010 Phoenix Contact
Technical modifications reserved;