

## Han 3A-HTE-M25 PC grey w. seal



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 20 003 0433                                                                        |
| Specification      | Han 3A-HTE-M25 PC grey w. seal                                                        |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19200030433">https://b2b.harting.com/19200030433</a> |

### Identification

|                             |                                              |
|-----------------------------|----------------------------------------------|
| Category                    | Hoods/Housings                               |
| Series of hoods/housings    | Han A <sup>®</sup>                           |
| Type of hood/housing        | Hood                                         |
| Description of hood/housing | for Han-Brid <sup>®</sup><br>With glued seal |

### Version

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| Locking type         | Single locking lever                                |
| Size                 | 3 A                                                 |
| Version              | Top entry                                           |
| Cable entry          | 1x M25                                              |
| Field of application | Standard Hoods/housings for industrial applications |

### Technical characteristics

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                             |
| Degree of protection acc. to IEC 60529 | IP44<br>IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                               |

### Material properties

|                         |                        |
|-------------------------|------------------------|
| Material (hood/housing) | Polycarbonate (PC)     |
| Colour (hood/housing)   | RAL 7032 (pebble grey) |



Pushing Performance

## Material properties

|                                           |           |
|-------------------------------------------|-----------|
| Material (seal)                           | NBR       |
| Material flammability class acc. to UL 94 | V-0       |
| RoHS                                      | compliant |
| ELV status                                | compliant |
| China RoHS                                | e         |
| REACH Annex XVII substances               | No        |
| REACH ANNEX XIV substances                | No        |
| REACH SVHC substances                     | No        |

## Specifications and approvals

|           |                                                            |
|-----------|------------------------------------------------------------|
| Approvals | DNV GL                                                     |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE        | Yes                                                        |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 10                                       |
| Net weight                     | 14.1 g                                   |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |