

## Han B Hood Top Entry HC M40 Black



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 30 716 0428                                                                        |
| Specification      | Han B Hood Top Entry HC M40 Black                                                     |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19307160428">https://b2b.harting.com/19307160428</a> |

### Identification

|                             |                    |
|-----------------------------|--------------------|
| Category                    | Hoods/Housings     |
| Series of hoods/housings    | Han <sup>®</sup> B |
| Type of hood/housing        | Hood               |
| Description of hood/housing | Black              |
| Type                        | High construction  |

### Version

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Locking type         | Double locking lever                              |
| Size                 | 16 B                                              |
| Version              | Top entry                                         |
| Cable entry          | 1x M40                                            |
| Field of application | Standard hoods/housings for industrial connectors |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65            |
|                                        | IP66            |
|                                        | IP67            |
| Type rating acc. to UL 50 / UL 50E     | 4               |
|                                        | 4X              |
|                                        | 12              |

### Material properties

|                         |                    |
|-------------------------|--------------------|
| Material (hood/housing) | Aluminium die-cast |
|-------------------------|--------------------|



Pushing Performance

## Material properties

|                             |                      |
|-----------------------------|----------------------|
| Surface (hood/housing)      | Powder-coated        |
| Colour (hood/housing)       | RAL 9005 (jet black) |
| RoHS                        | compliant            |
| ELV status                  | compliant            |
| China RoHS                  | e                    |
| REACH Annex XVII substances | No                   |
| REACH ANNEX XIV substances  | No                   |
| REACH SVHC substances       | No                   |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
| CE        | Yes    |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 206.9 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |