

Han 3M-eg-QB-M20



Image is for illustration purposes only. Please refer to product description.

Part number	19 37 003 1150
Specification	Han 3M-eg-QB-M20
HARTING eCatalogue	https://b2b.harting.com/19370031150

Identification

Category	Hoods/Housings
Series of hoods/housings	Han® M
Type of hood/housing	Screw mounted housing

Version

Locking type	Single locking lever
Size	3 A
Cable entry	1x M20
Field of application	Hoods/housings for rough environments
Pack contents	With seal screw

Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65 IP67

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (locking)	Stainless steel
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight



Pushing Performance

Material properties

ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	10
Net weight	57.67 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors