

Han 3M-HAE-M25



Image is for illustration purposes only. Please refer to product description.

Part number	19 37 003 1645
Specification	Han 3M-HAE-M25
HARTING eCatalogue	https://b2b.harting.com/19370031645

Identification

Category	Hoods/Housings
Series of hoods/housings	Han® M
Type of hood/housing	Hood

Version

Locking type	Single locking lever
Size	3 A
Version	Side entry
Cable entry	1x M25
Field of application	Hoods/housings for rough environments

Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP44 IP65 / IP67 with seal screw 09 20 000 9918

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
RoHS	compliant
ELV status	compliant
China RoHS	e



Pushing Performance

Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	1
Net weight	80.5 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors