

## Han 10HPR-Compact-HSE-HC-SCL-M40



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 40 510 0513                                                                        |
| Specification      | Han 10HPR-Compact-HSE-HC-SCL-M40                                                      |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19405100513">https://b2b.harting.com/19405100513</a> |

### Identification

|                          |                              |
|--------------------------|------------------------------|
| Category                 | Hoods/Housings               |
| Series of hoods/housings | Han <sup>®</sup> HPR Compact |
| Type of hood/housing     | Hood                         |
| Type                     | High construction            |

### Version

|                      |                                               |
|----------------------|-----------------------------------------------|
| Locking type         | Screw locking                                 |
| Size                 | 10 HPR                                        |
| Version              | Side entry                                    |
| Cable entry          | 1x M40                                        |
| Field of application | Hoods/housings for harsh outdoor environments |

### Technical characteristics

|                                        |                          |
|----------------------------------------|--------------------------|
| Tightening torque (screw locking)      | 3 Nm                     |
| Limiting temperature                   | -40 ... +125 °C          |
| Degree of protection acc. to IEC 60529 | IP65                     |
|                                        | IP68                     |
|                                        | IP6K9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E     | 4                        |
|                                        | 4X                       |
|                                        | 12                       |

### Material properties

|                         |                     |
|-------------------------|---------------------|
| Material (hood/housing) | Aluminium die-cast  |
|                         | Corrosion resistant |



Pushing Performance

## Material properties

|                        |                      |
|------------------------|----------------------|
| Surface (hood/housing) | Powder-coated        |
| Colour (hood/housing)  | RAL 9005 (jet black) |
| Material (locking)     | Stainless steel      |

## Specifications and approvals

|           |                                                            |
|-----------|------------------------------------------------------------|
| Approvals | DNV GL                                                     |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE        | Yes                                                        |

## Commercial data

|                   |                                          |
|-------------------|------------------------------------------|
| Packaging size    | 1                                        |
| Country of origin | China                                    |
| eCl@ss            | 27440202 Shell for industrial connectors |