

FEG) Thomas Sam.

SPECIFICATION


Device Name : IGBT MODULE

Type Name : 1MBI600S-120

Spec. No. : MS5F 5055

This material and the information herein is the property of
Fuji Electric Co., Ltd. They shall be neither reproduced, copied,
lent, or disclosed in any way whatsoever for the use of any
third party nor used for the manufacturing purposes without
the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.
Matsumoto Factory

		DATE	NAME	APPROVED	Fuji Electric Co., Ltd.		
DRAWN	Aug. -30-'01	J. Kobayashi			DWG. NO.	MS5F 5055	1/8
CHECKED	Aug. -30-'01	N. Kato					

H04-004-07

Revised Records

[illegible]

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, nor disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.

Fuji Electric Co., Ltd.

DWG.NO.


MS5F 5055

 $\frac{2}{8}$


H04-004-06

1MBI600S-120

1. Outline Drawing (Unit : mm)



2. Equivalent circuit



Fuji Electric Co., Ltd.

DWG. NO.

MS5F 5055

3/8

H04-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

3. Absolute Maximum Ratings (at $T_c = 25^\circ\text{C}$ unless otherwise specified)

Items	Symbols	Conditions		Maximum Ratings	Units
Collector-Emitter voltage	V_{CES}			1200	V
Gate-Emitter voltage	V_{GES}			± 20	V
Collector current	I_c	Continuous	$T_c=25^{\circ}\text{C}$	900	A
			$T_c=80^{\circ}\text{C}$	600	
	I_c pulse	1ms	$T_c=25^{\circ}\text{C}$	1800	
			$T_c=80^{\circ}\text{C}$	1200	
	$-I_c$			600	
	$-I_c$ pulse	1ms		1200	
Collector Power Dissipation	P_c	1 device		4150	W
Junction temperature	T_j			150	$^{\circ}\text{C}$
Storage temperature	T_{stg}			$-40-+125$	$^{\circ}\text{C}$
Isolation voltage ^(*)	V_{iso}	AC : 1min.		2500	V
Screw Torque	Mounting ^(*)			4.5	N·m
	Terminals ^(*)			11.0	
	Terminals ^(*)			1.7	

(*) All terminals should be connected together when isolation test will be done.

(*)2 Recommendable Value: Mounting $4.0 \pm 0.5\text{N}\cdot\text{m}$ (M6)

Terminal $10.0 \pm 1.0\text{N}\cdot\text{m}$ (M8), $1.5 \pm 0.2\text{N}\cdot\text{m}$ (M4)

4. Electrical characteristics (at $T_j = 25^\circ\text{C}$ unless otherwise specified)

Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	Max.	
Zero gate voltage Collector current	I_{CES}	$V_{GE} = 0\text{V}$, $V_{CE} = 1200\text{V}$	-	-	2.0	mA
Gate-Emitter leakage current	I_{GES}	$V_{CE} = 0\text{V}$, $V_{GE} = \pm 20\text{V}$	-	-	1.6	μA
Gate-Emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = 20\text{V}$, $I_c = 600\text{mA}$	5.5	7.2	8.5	V
Collector-Emitter saturation voltage	$V_{CE(sat)}$	$V_{GE} = 15\text{V}$	-	2.8	2.6	V
		$I_c = 600\text{A}$		2.8	-	
Input capacitance	C_{ies}	$V_{GE} = 0\text{V}$	-	72000	-	pF
Output capacitance	C_{oes}	$V_{CE} = 10\text{V}$	-	15000	-	
Reverse transfer capacitance	C_{res}	$f = 1\text{MHz}$	-	13200	-	
Turn-on time	t_{on}	$V_{ce} = 600\text{V}$	-	0.8	1.2	μs
	t_r	$I_c = 600\text{A}$	-	0.25	0.6	
	$t_{r(0)}$	$V_{GE} = \pm 15\text{V}$	-	0.1	-	
Turn-off time	t_{off}	$R_G = 1.5\Omega$	-	0.7	1.0	
	t_f		-	0.1	0.3	
			-	0.1	0.3	
Forward on voltage	V_F	$I_F = 600\text{A}$	-	2.8	3.4	V
		$T_j = 125^\circ\text{C}$		2.4	-	
Reverse recovery time	t_{rr}	$I_F = 600\text{A}$	-	-	0.35	μs

5. Thermal resistance characteristics

Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	Max.	
Thermal resistance (1 device)	$R_{th(j-c)}$	IGBT	-	-	0.03	$^\circ\text{C/W}$
		FWD	-	-	0.06	
Contact Thermal resistance	$R_{th(c-f)}$	with Thermal Compound ^(*)	-	0.0063	-	

* This is the value which is defined mounting on the additional cooling fin with thermal compound.

Fuji Electric Co., Ltd.


DWG. NO.

MS5F 5055

4/8

H04-004-03

6. Indication on module




7. Applicable category

This specification is applied to IGBT Module named 1MBI600S-120.

8. Storage and transportation notes

- The module should be stored at a standard temperature of 5 to 35°C and humidity of 45 to 75%.
- Store modules in a place with few temperature changes in order to avoid condensation on the module surface.
- Avoid exposure to corrosive gases and dust.
- Avoid excessive external force on the module.
- Store modules with unprocessed terminals.
- Do not drop or otherwise shock the modules when transporting.
- Please connect adequate fuse or protector of circuit between three-phase line and this product to prevent the equipment from causing secondary destruction.

9. Definitions of switching time



Fuji Electric Co., Ltd.







DWG. NO.

MS5F 5055

5 / 8

H04-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party without the express written consent of Fuji Electric Co., Ltd.



Fuji Electric Co., Ltd.

DWG. NO.


MS5F 5055

6/8


1104-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. It shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third person without the express written consent of Fuji Electric Co., Ltd.


Switching time vs. Collector current (typ.)
 $V_{CC}=600V$, $V_{GE}=+15V$, $R_g=1.5\Omega$, $T_j=25^\circ C$




Switching time vs. Collector current (typ.)
 $V_{CC}=600V$, $V_{GE}=+15V$, $R_g=1.5\Omega$, $T_j=125^\circ C$




Switching time vs. Gate resistance (typ.)
 $V_{CC}=600V$, $I_c=600A$, $V_{GE}=+15V$, $T_j=25^\circ C$




Switching loss vs. Collector current (typ.)
 $V_{CC}=600V$, $V_{GE}=+15V$, $R_g=1.5\Omega$



Switching loss vs. Gate resistance (typ.)
 $V_{CC}=600V$, $I_c=600A$, $V_{GE}=+15V$, $T_j=125^\circ C$



Reverse bias safe operating area
 $+V_{GE}=15V$, $-V_{GE}\leq 15V$, $R_g\geq 1.5\Omega$, $T_j\leq 125^\circ C$



Fuji Electric Co., Ltd.

DWG. NO.


MS5F 5055

7/8

H04-004-03


This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Forward current vs. Forward on voltage (typ)




Reverse recovery characteristics (typ)

$V_{od} = 800\text{V}$, $V_{GE} = -15\text{V}$, $R_g = 1.5\Omega$



Transient thermal resistance



Fuji Electric Co., Ltd.

DWG. NO.

MS5F 5055

8/8

H04-004-03