Wiha Insulated Open-Ended Spanners

NEW From Wiha

Insulation Test Standards:
Insulation according to ASTM F-1505-01, EN/IEC 60900, VDE 0680, DIN 7446



Insulation
High visibility, grip is double coated

Each tool individually tested to 10,000 volts and certified to 1000 Volt ac or 1500 Volt dc

Steel
Forged from chrome vanadium, meets - DIN 3110

Angled 15°

1000V



1000Volt SHOP

201 Inch Open-Ended Spanners, With Insulated Handle
Insulation According to VDE Specification 0680 and EN/IEC 60900, DIN 7446, up to 1000 Volt. Individually Tested. Chrome-vanadium steel, hardened. Angled 15°.

Item No.	MM Inch	OAL mm	OAL Inch	lbs.	pkg.
201 33	5/16	100	3.9	.05	1
201 35	3/8	105	4.1	.07	1
201 36	7/16	117	4.6	.09	1
201 37	1/2	140	5.5	.15	1
201 38	9/16	146	5.7	.15	1
201 40	5/8	158	6.2	.20	1
201 41	11/16	165	6.5	.23	1
201 42	3/4	178	7.0	.33	1
201 44	13/16	191	7.5	.42	1
201 45	7/8	192	7.6	.44	1
201 46	15/16	201	7.9	.51	1
201 47	1	213	8.4	.61	1
201 48	1-1/16	233	9.2	.79	1
201 49	1-1/8	233	9.2	.77	1

* Lengths are +/- 5% due to coating process

Warning!
Insulated tools are not intended for use on live or energized circuits. Always disconnect and de-energize all equipment & circuits. **NEVER!** work on live or energized circuits or equipment.

Use & Care Guide For Insulated Tools:
Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70° C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.



1000Volt SHOP

201 90 Set 14 Pcs. Insulated Inch Open End Insulated Spanners

Item No.		MM Inch	OAL Inch		MM Inch	OAL Inch	lbs.
201 90	201 33	5/16	3.9	201 42	3/4	7.0	3.0
	201 35	3/8	4.1	201 44	13/16	7.5	
	201 36	7/16	4.6	201 45	7/8	7.6	
	201 37	1/2	5.5	201 46	15/16	7.9	
	201 38	9/16	5.7	201 47	1	8.4	
	201 40	5/8	6.2	201 48	1-1/16	9.2	
	201 41	11/16	6.5	201 49	1-1/8	9.1	



1000Volt SHOP

201 92 Set 8 Pcs. Insulated Inch Open End Insulated Spanners

Item No.		MM Inch	OAL Inch		MM Inch	OAL Inch	lbs.
201 92	201 33	5/16	3.9	201 38	9/16	5.7	1.4
	201 35	3/8	4.1	201 40	5/8	6.2	
	201 36	7/16	4.6	201 41	11/16	6.5	
	201 37	1/2	5.5	201 42	3/4	7.0	

PREVIOUS NEXT

INDEX