SAW Bandpass Filter 205205B

1. Features

- IF Bandpass Filter
- Single-Ended Operation
- Ceramic Surface Mount Device (SMD) Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimensions



Package : S1365

Pad Configuration	
11	Input
5	Output
6, 12	Ground
Other	Case ground

Dimensions shown are nominal in millimeters

Body : Al_2O_3 Ceramic
Lid : Kovar, Ni Plated
Terminations : Au plating 0.3 ~ 1.0 um, Over a 1.27 ~ 8.89 um Ni Plating

3. Specifications

Fo = 65.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	65.0	-
Insertion Loss	dB	-	21.5	23.5
1dB Bandwidth	MHz	-	19.5	-
3dB Bandwidth	MHz	19.8	20.1	-
40dB Bandwidth	MHz	-	23.0	23.4
Amplitude Ripple (Fo +/- 9.4 MHz)	dB	-	0.7	1.0
Group Delay Variation (Fo +/- 9.4 MHz)	nsec	-	40	120
Absolute Delay	usec	-	1.33	-
Ultimate Rejection	dB	40	45	-
Temperature Coefficient of Frequency	ppm/°C	-	-86	-

Notes :

1) All specifications are based on the matching schematic shown below
2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
3) All attenuation measurements are measured relative to insertion loss

4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



C1 = 10 pF, C2 = 10 pF

5. Marking Configuration

ITF[1] 04A001[2]

205205B[3]

● [4]

1) Manufacturer name

2) Lot Number

3) Part Number

4) Pad Number 1 Index

6. Typical Performance (at +25℃)





SAW Bandpass Filter 205205B









Integrated Technology Future	**I T F Co., Ltd.** 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyounggi-Do, Korea 421-809	Part No.	205205B
		Rev. Date	2004-04-28
		Rev.	NI2016- CS02 5/5