

Power Cord with Contour Power (Mains) Plug 2-pole, Straight

new

**Description**

Power Supply Cord, Protection class II, Pin temperature 70 °C, Cable
- Substitute for type [4142](#)

Approvals

- VDE License Number: 45142

References

[General Product Information](#)

Weblinks

[Approvals](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Store](#),
[Distributor-Stock-Check](#), [Accessories](#)

Technical Data

Ratings IEC	16 A / 250 VAC; 50 Hz
Ratings UL/CSA	16 A / 250 VAC; 60 Hz
Dielectric Strength	> 2 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 2 acc. to IEC 61140
Terminal	moulded
Material: Housing	PVC, black or grey

Config. Code[Product Configurator](#)**2228 - R - Type - D - Length**

The characters are placeholders for the correspondingly keys of selections from the key tables.
Typ steht für die Dose bzw. 2. Seite, Länge ist die Leitungslänge in mm.

2228 - R - Type - D - Length = cord type

cord type	Configuration key
H03VV-F 2x0,75mm ²	A
H03VVH2-F 2x0,75mm ²	B
H05VV-F 2x0,75mm ²	D
H05VVH2-F 2x0,75mm ²	E
H05VV-F 2x1,0mm ²	F

Cord definition is detailed in general product information XXX

2228 - R - Type - D - Length = Cord end 2**Cord end 2**

zzzz, [0301](#), [2510](#), [2511](#), [3016](#), [3113](#), [3127](#), [3130](#), [4810](#), [9011](#)

2228 - R - Type - D - Length = Color

Color	Configuration key
jet black; RAL9005	A
silver grey; RAL7001	B
standard color: black	

2228 - R - Type - D - Length = Cord length**Cord length**

zzzz, 000500, 001000, 001500, 002000, 002500, 003000, 005000

Cord length in mm

Packaging unit 100 Pcs