DIN rail bus connectors - ME 17,5 TBUS 1,5/ 5-ST-3,81 KMGY - 2713645

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



DIN rail connector, nominal current: 8 A, number of positions: 5, pitch: 3.81 mm, color: light gray



Key Commercial Data

Packing unit	50 pc
GTIN	4 017918 914509
GTIN	4017918914509

Technical data

Dimensions

Width	3.5 mm
Pitch	3.81 mm
Width [w]	3.5 mm
Height	7.5 mm

General

Rated voltage (III/3)	125 V
Nominal current I_N	8 A
Maximum load current	8 A
Flammability rating according to UL 94	V0
Color	light gray
Number of positions	5

Standards and Regulations

Connection in acc. with standard	CUL
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e

DIN rail bus connectors - ME 17,5 TBUS 1,5/ 5-ST-3,81 KMGY - 2713645

Technical data

Environmental Product Compliance

	No hazardous substances above threshold values

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E118976-20151204

Nominal voltage UN	150 V
Nominal current IN	8 A

cUL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E118976-20151204

Nominal voltage UN	150 V
Nominal current IN	6 A

EAC B.01742

cULus Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm

Phoenix Contact 2018 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com