Inline connector - IB IL SCN-8-GY - 2862783

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Connector, unprinted, gray



RoHS

Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	4 017918 896416
GTIN	4017918896416

Technical data

Dimensions

Height	111.2 mm
Depth	41 mm
Width	12 mm

Connection data

Conductor cross section solid min.	0.08 mm²
Conductor cross section solid max.	1.5 mm²
Conductor cross section flexible min.	0.08 mm²
Conductor cross section flexible max.	1.5 mm²
Conductor cross section AWG min.	28
Conductor cross section AWG max.	16
Stripping length	8 mm

Standards and Regulations

Connection in acc. with standard	CUL

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e

Inline connector - IB IL SCN-8-GY - 2862783

Technical data

Environmental Product Compliance

	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27242692
eCl@ss 4.0	27250200
eCl@ss 4.1	27250200
eCl@ss 5.0	27259200
eCl@ss 5.1	27242600
eCl@ss 6.0	27249200
eCl@ss 7.0	27249290
eCl@ss 8.0	27249290
eCl@ss 9.0	27242692

ETIM

ETIM 2.0	EC000313
ETIM 3.0	EC000313
ETIM 4.0	EC002584
ETIM 5.0	EC002584
ETIM 6.0	EC002584
ETIM 7.0	EC002584

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121552
UNSPSC 18.0	32151602
UNSPSC 19.0	32151602
UNSPSC 20.0	32151602
UNSPSC 21.0	32151602

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Inline connector - IB IL SCN-8-GY - 2862783

Approvals

Ex Approvals

Approval details

UL Recognized	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324

Nominal voltage UN	24 V
Nominal current IN	10 A
mm²/AWG/kcmil	26-16

cUL Recognized	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324

Nominal voltage UN	24 V
Nominal current IN	10 A
mm²/AWG/kcmil	26-16

cULus Recognized

Phoenix Contact 2020 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com