Plug-in module - RIF-LV-48-60 UC - 2900943

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 48 ... 60 V AC/DC ±20 %

Key Commercial Data

Packing unit	10 pc
GTIN	4 046356 733243
GTIN	4046356733243

Technical data

Input data

Input voltage range	48 V AC/DC ... 60 V AC/DC ±20 %
Status display	Yellow LED
Protective circuit/component	Varistor

Standards and Regulations

Connection in acc. with standard	CSA

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”

Approvals

Approvals

Approvals

DNV GL / CSA / PRS / LR / UL Recognized / EAC

Plug-in module - RIF-LV-48-60 UC - 2900943

Approvals

Ex Approvals

Approval details

DNV GL	http://exchange.dnv.com/tari/	TAA000018V
CSA	http://www.csagroup.org/services-industries/product-listing/	2607057
PRS	http://www.prs.pl/	TE/2108/880590/16
LR	http://www.lr.org/en	15/20011
UL Recognized	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 113228
EAC		RU C-DE.A*30.B.01082

Phoenix Contact 2019 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com