SAMYANG ELECTRONICS

2A01G --- 2A07G

GLASS PASSIVATED RECTIFIERS

VOLTAGE RANGE: 50 --- 1000 V
CURRENT: 2.0 A


FEATURES

- ◇ Low cost
- ◇ Glass passivated junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon,Alcohil,Isopropanop and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇ Case:JEDEC DO-15,molded plastic
- ◇ Terminals: Axial lead ,solderable per MIL- STD-202,Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.014ounces,0.39grams
- ◇ Mounting position: Any

DO - 15



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25℃ ambient temperature unless otherwise specified.

Single phase,half wave,60 Hz,resistive or inductive load. For capacitive load,derate by 20%.

		2A01G	2A02G	2A03G	2A04G	2A05G	2A06G	2A07G	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current 9.5mm lead length, @T_A=75℃	$I_{F(AV)}$	2.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}	65.0							A
Maximum instantaneous forward voltage @2.0A DC	V_F	1.1							V
Maximum reverse current @T_A=25℃	I_R	5.0							μA
at rated DC blocking voltage @T_A=125℃		200							
Typical junction capacitance (Note1)	C_J	40							pF
Typical thermal resistance (Note2)	$R_{\theta JA}$	18							℃
Operating junction temperature range	T_J	- 55---- +175							℃
Storage temperature range	T_{STG}	- 55---- +175							℃

NOTE:1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
2. Thermal resistance from junction to ambient.

www.diode.co.kr

Download from alldatasheet.com

FIG.1 –TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2 –TYPICAL REVERSE CHARACTERISTICS




FIG.3–TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4–PEAK FORWARD SURGE CURRENT





FIG.5–TYPICAL JUNCTION CAPACITANCE



www.diode.co.kr

Download from alldatasheet.com