
High voltage silicon diodes

Reverse Voltage – 16kV

Forward Current –350mA



FEATURES

- High reliability

MECHANICAL DATA

- Case: Molded Plastic Body
- Epoxy meets UL 94V-0 flammability rating
- Terminals: Pure tin plated leads, solderable per J-STD-002 and JESD22-B102, E3 suffix for consumer grade, meet JESD201class 1A whisker test.
- Polarity: Color band denotes cathode end


Maximum rating (Ta=25°C unless otherwise noted)

Parameter		Symbol	2CL3516	Unit
Repetitive peak reverse voltage		V_{RRM}	16	KV
Average forward current	60Hz half-sine wave, Resistance load, Ta≤60°C	$I_{F(AV)}$	350	mA
Surge(Non-repetitive)forward current	60Hz half-sine wave,1cycle,T_a=25°C	I_{FSM}	30	A
Reverse surge current	Wp=1ms,Rectangular-wave,One-shot,Ta=25°C	I_{RSM}	100	mA
Peak forward voltage	I_{FM}=350mA	V_{FM}	≤12	V
Peak reverse current $V_{RM}=V_{RRM}$		I_{RRM1}	≤5	μA
Avalanche breakdown voltage	I_R=100uA	$V_{(BR)}$	≥16.5	KV
Storage Temperature Range		T_{stg}	-40 ~ +130	°C
Virtual junction temperature		$T_{(vj)}$	130	°C

Notes :Cooling Requirement: Cathode terminal is fastened to radiating fin that size is more than 50mm×50mm×0.6mm
Wind-cooled velocity is more than 0.5m/s.

Download from alldatasheet.com

Package outline dimensions



Summary of Packing Options

Package	Packing Description	Packing Quantity	Industry Standard
DO-722	BOX	5000	EIA-481-1

Download from alldatasheet.com