2CLG100KV/0.2A 200mA 100kV 100nS

High Voltage Medium Current Standard Rectifiers

INTRODUCE:

HVGT high voltage silicon rectifier assembly is made of high quality glass passivated chip and high reliability epoxy resin sealing structure, and through professional testing equipment inspection qualified after to customers.

FEATURES:

1. High reliability design.
2. High voltage design.
3. High frequency .
4. Conform to RoHS.
5. Epoxy resin molded in vacuumHave anticorrosion in the surface.

APPLICATIONS:

1. High frequency switching power supply.
2. Power supply of laser equipment .
3. General purpose high voltage rectifier.
4. Other.


MECHANICAL DATA:

1. Case: epoxy resin molding.
2. Terminal: welding axis.
3. Net weight: 7.2 grams (approx).

SHAPE DISPLAY:



SIZE: (Unit:mm) **HVGT NAME: HVS-080960H**




MAXIMUM RATINGS AND CHARACTERISTICS: (Absolute Maximum Ratings)


Items	Symbols	Condition	Data Value	Units
Repetitive Peak Renerse Voltage	V_{RRM}	T_A=25°C	100	kV
Average Forward Current Maximum	I_{FAVM}	T_A=40°C	200	mA
Suege Current	I_{FSM}	T_A=25°C; Half-Sine Wave; 8.3mS	6.0	A
Junction Temperature	T_J		125	°C
Allowable Operation Case Temperature	Tc		-40~+125	°C
Storage Temperature	T_{STG}		-40~+125	°C

ELECTRICAL CHARACTERISTICS: T_A=25°C (Unless Otherwise Specified)

Items	Symbols	Condition	Data value	Units
Maximum Forward Voltage Drop	V_F	at 25°C; at $I_{F(AV)}$	120	V
Maximum Reverse Current	I_R1	at 25°C; at V_{RRM}	2.0	uA
	I_R2	at 100°C; at V_{RRM}	50	uA
Maximum Reverse Recovery Time	T_{RR}	at 25°C; I_F=0.5I_R; I_R=I_{FAVM}; I_{RR}=0.25I_R	100	nS
Junction Capacitance	C_J	at 25°C; V_R=0V; f=1MHz	--	pF

Fig 1	Fig 2
Forward Current Derating Curve	**Reverse Recovery Measurement Waveform**






Typical data capture points: I_F =0.5I_R , I_R,I_{RR} =0.25I_R

Fig 3

Non-Repetitive Surge Current



Cycles (50Hz)