


N-CHANNEL ENHANCEMENT MODE FIELD EFFECT TRANSISTOR
Features

- Σ Low On-Resistance: $R_{DS(ON)}$
- Σ Low Gate Threshold Voltage
- Σ Low Input Capacitance
- Σ Fast Switching Speed
- Σ Low Input/Output Leakage
- Σ **Lead Free/RoHS Compliant (Note 2)**
- Σ **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Σ Case: SOT-23
- Σ Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Σ Moisture sensitivity: Level 1 per J-STD-020C
- Σ Terminals: Solderable per MIL-STD-202, Method 208
- Σ Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Σ Terminal Connections: See Diagram
- Σ Marking: K72, K7A, K7B (See Page 2)
- Σ Ordering & Date Code Information: See Page 2
- Σ Weight: 0.008 grams (approximate)



SOT-23		
Dim	Min	Max
A	0.37	0.51
B	1.20	1.40
C	2.30	2.50
D	0.89	1.03
E	0.45	0.60
G	1.78	2.05
H	2.80	3.00
J	0.013	0.10
K	0.903	1.10
L	0.45	0.61
M	0.085	0.180
a	0 ∞	8 ∞
All Dimensions in mm		

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Value	Units
Drain-Source Voltage	V_{DSS}	60	V
Drain-Gate Voltage $R_{GS} \leq 1.0\text{MW}$	V_{DGR}	60	V
Gate-Source Voltage	V_{GSS}	± 20	V
Continuous Pulsed		± 40	
Drain Current (Note 1)	I_D	115	mA
Continuous		73	
Continuous @ 100°C		800	
Total Power Dissipation (Note 1)	P_d	300	mW
Derating above $T_A = 25^\circ\text{C}$		2.4	
Thermal Resistance, Junction to Ambient	R_{QJA}	417	$^\circ\text{C/W}$
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

- Note:
1. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
 2. No purposefully added lead.

Electrical Characteristics @ T_A = 25°C unless otherwise specified


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 3)						
Drain-Source Breakdown Voltage	BV _{DSS}	60	70	æ	V	V _{GS} = 0V, I _D = 10mA
Zero Gate Voltage Drain Current @ T _C = 25°C @ T _C = 125°C	I _{DSS}	æ	æ	1.0 500	µA	V _{DS} = 60V, V _{GS} = 0V
Gate-Body Leakage	I _{GSS}	æ	æ	±10	nA	V _{GS} = ±20V, V _{DS} = 0V
ON CHARACTERISTICS (Note 3)						
Gate Threshold Voltage	V _{GS(th)}	1.0	æ	2.5	V	V _{DS} = V _{GS} , I _D = 250mA
Static Drain-Source On-Resistance @ T _J = 25°C @ T _J = 125°C	R _{DS (ON)}	æ	3.2 4.4	7.5 13.5	W	V _{GS} = 5.0V, I _D = 0.05A V _{GS} = 10V, I _D = 0.5A
On-State Drain Current	I _{D(ON)}	0.5	1.0	æ	A	V _{GS} = 10V, V _{DS} = 7.5V
Forward Transconductance	g _{FS}	80	æ	æ	mS	V _{DS} =10V, I _D = 0.2A
DYNAMIC CHARACTERISTICS						
Input Capacitance	C _{iss}	æ	22	50	pF	V _{DS} = 25V, V _{GS} = 0V f = 1.0MHz
Output Capacitance	C _{oss}	æ	11	25	pF	
Reverse Transfer Capacitance	C _{rss}	æ	2.0	5.0	pF	
SWITCHING CHARACTERISTICS						
Turn-On Delay Time	t _{D(ON)}	æ	7.0	20	ns	V _{DD} = 30V, I _D = 0.2A, R _L = 150W, V _{GEN} = 10V, R _{GEN} = 25W
Turn-Off Delay Time	t _{D(OFF)}	æ	11	20	ns	

Ordering Information (Note 4)

Device	Packaging	Shipping
2N7002-7-F	SOT-23	3000/Tape & Reel

- Notes:
3. Short duration test pulse used to minimize self-heating effect.
 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information









K7x = Product Type Marking Code, e.g. K72
 YM = Date Code Marking
 Y = Year ex: N = 2002
 M = Month ex: 9 = September

Date Code Key

Year	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009
Code	J	K	L	M	N	P	R	S	T	U	V	W

Month	Jan	Feb	March	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D



IMPORTANT NOTICE

Diodes, Inc. and its subsidiaries reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Diodes, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

The products located on our website at www.diodes.com are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the express written approval of Diodes Incorporated.