Ordering number : EN2063C

SANYO Semiconductors

DATA SHEET

An ON Semiconductor Company

2SB1143/2SD1683 — 50V/4A Switching Applications

PNP/NPN Epitaxial Planar Silicon Transistor

Applications

- Voltage regulators, relay drivers, lamp drivers, electrical equipment

Features

- Adoption of FBET, MBIT processes
- Large current capacity and wide ASO
- Low saturation voltage

Specifications ( ): 2SB1143

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	V_{CBO}		(–)60	V
Collector-to-Emitter Voltage	V_{CEO}		(–)50	V
Emitter-to-Base Voltage	V_{EBO}		(–)6	V
Collector Current	I_C		(–)4	A
Collector Current (Pulse)	I_{CP}		(–)6	A
Collector Dissipation	P_C		1.5	W
		Tc=25°C	10	W
Junction Temperature	Tj		150	°C
Storage Temperature	Tstg		–55 to +150	°C

Package Dimensions

unit : mm (typ)

7516A-002



Product & Package Information

- Package : TO-126ML
- JEITA, JEDEC : TO-126
- Minimum Packing Quantity : 200 pcs./bag

Marking



Electrical Connection



Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	I_{CBO}	V_{CB}=(−)40V, I_E=0A			(−)1	μA
Emitter Cutoff Current	I_{EBO}	V_{EB}=(−)4V, I_C=0A			(−)1	μA
DC Current Gain	$h_{FE}1$	V_{CE}=(−)2V, I_C=(−)100mA	100*		560*	
	$h_{FE}2$	V_{CE}=(−)2V, I_C=(−)3A	40			
Gain-Bandwidth Product	f_T	V_{CE}=(−)10V, I_C=(−)50mA		150		MHz
Output Capacitance	Cob	V_{CB}=(−)10V, f=1MHz		(39)25		pF
Collector-to-Emitter Saturation Voltage	V_{CE}(sat)	I_C=(−)2A, I_B=(−)100mA		(−350)190	(−700)500	mV
Base-to-Emitter Saturation Voltage	V_{BE}(sat)	I_C=(−)2A, I_B=(−)100mA		(−)0.94	(−)1.2	V
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	I_C=(−)10μA, I_E=0A	(−)60			V
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C=(−)1mA, R_{BE}=∞	(−)50			V
Emitter-to-Base Breakdown Voltage	$V_{(BR)EBO}$	I_E=(−)10μA, I_C=0A	(−)6			V
Turn-On Time	t_{on}	See specified Test Circuit.		(70)70		ns
Storage Time	t_{stg}			(450)650		ns
Fall Time	t_f			(30)35		ns

* : The 2SB1143/2SD1683 are classified by 100mA h_{FE} as follows :

Rank	R	S	T	U
h_{FE}	100 to 200	140 to 280	200 to 400	280 to 560

Switching Time Test Circuit



I_C=10I_{B1}= −10I_{B2}=1A
(For PNP, the polarity is reversed.)

Ordering Information

Device	Package	Shipping	memo
2SB1143S	TO-126ML	200pcs./bag	Pb Free
2SB1143T	TO-126ML	200pcs./bag	
2SD1683S	TO-126ML	200pcs./bag	
2SD1683T	TO-126ML	200pcs./bag	


IC – VCE
2SB1143
–200mA
–100mA
–50mA
–20mA
–10mA
–5mA
IB=0mA
Collector Current, IC – A
Collector-to-Emitter Voltage, VCE – V
ITR09047


IC – VCE
2SD1683
100mA
80mA
60mA
40mA
20mA
10mA
5mA
IB=0mA
Collector Current, IC – A
Collector-to-Emitter Voltage, VCE – V
ITR09048


IC – VCE
2SB1143
–14mA
–12mA
–10mA
–8mA
–6mA
–4mA
–2mA
IB=0mA
Collector Current, IC – A
Collector-to-Emitter Voltage, VCE – V
ITR09049


IC – VCE
2SD1683
8mA
7mA
6mA
5mA
4mA
3mA
2mA
1mA
IB=0mA
Collector Current, IC – A
Collector-to-Emitter Voltage, VCE – V
ITR09050


IC – VBE
2SB1143
VCE= –2V
Ta=75°C
25°C
–25°C
Collector Current, IC – A
Base-to-Emitter Voltage, VBE – V
ITR09051


IC – VBE
2SD1683
VCE=2V
Ta=75°C
25°C
–25°C
Collector Current, IC – A
Base-to-Emitter Voltage, VBE – V
ITR09052


hFE – IC
2SB1143
VCE= –2V
Ta=75°C
25°C
–25°C
DC Current Gain, hFE
Collector Current, IC – A
ITR09053


hFE – IC
2SD1683
VCE=2V
Ta=75°C
25°C
–25°C
DC Current Gain, hFE
Collector Current, IC – A
ITR09054


fT -- IC
2SB1143 / 2SD1683
VCE=10V
2SD1683
2SB1143
For PNP, the minus sign is omitted.
Gain-Bandwidth Product, fT – MHz
Collector Current, IC – A
ITR09055


Cob -- VCB
2SB1143 / 2SD1683
f=1MHz
2SB1143
2SD1683
For PNP, the minus sign is omitted.
Output Capacitance, Cob – pF
Collector-to-Base Voltage, VCB – V
ITR09056


VCE(sat) -- IC
2SB1143
IC / IB=20
25°C
Ta= –25°C
75°C
Collector-to-Emitter Saturation Voltage, VCE(sat) – mV
Collector Current, IC – A
ITR09057


VCE(sat) -- IC
2SD1642
IC / IB=20
25°C
Ta=75°C
–25°C
Collector-to-Emitter Saturation Voltage, VCE(sat) – mV
Collector Current, IC – A
ITR09058


VBE(sat) -- IC
2SB1143
IC / IB=20
25°C
Ta= –25°C
75°C
Base-to-Emitter Saturation Voltage, VBE(sat) – V
Collector Current, IC – A
ITR09059


VBE(sat) -- IC
2SD1683
IC / IB=20
25°C
Ta= –25°C
75°C
Base-to-Emitter Saturation Voltage, VBE(sat) – V
Collector Current, IC – A
ITR09060


A S O
2SB1143 / 2SD1683
ICP=6A
IC=4A
1ms
10ms
100ms
DC operation Tc=25°C
DC operation Ta=25°C
Tc=25°C
Single pulse
For PNP, the minus sign is omitted.
Collector Current, IC – A
Collector-to-Emitter Voltage, VCE – V
ITR09061


PC -- Ta
2SB1143 / 2SD1683
No heat sink
Collector Dissipation, PC – W
Ambient Temperature, Ta – °C
ITR09062

Bag Packing Specification

2SB1143S, 2SB1143T, 2SD1683S, 2SD1683T

1. Packing Format

Package Name	Maximum Number of devices contained (pcs)			Packing format	
	Bag	Inner box	Outer box	Inner BOX	Outer BOX
TO-126ML	200	4,000	12,000	B-1 20 bags contained Dimensions:mm (external) 445×225×55	A-2 3 inner boxes contained Dimensions:mm (external) 470×250×190

2. Bag dimensions

(unit:mm)



3. Bag label, Inner box label

(unit:mm)



NOTE (1)
The LEAD FREE ※ description shows that the surface treatment of the terminal is lead free.

Label	JEITA Phase
LEAD FREE 3	JEITA Phase 3A
LEAD FREE 4	JEITA Phase 3

4. Outer box label

(unit:mm)

It is a label at the time of factory shipments. The form of a label may change in physical distribution process.



Outline Drawing

2SB1143S, 2SB1143T, 2SD1683S, 2SD1683T



- Any and all SANYO Semiconductor Co.,Ltd. products described or contained herein are, with regard to "standard application", intended for the use as general electronics equipment. The products mentioned herein shall not be intended for use for any "special application" (medical equipment whose purpose is to sustain life, aerospace instrument, nuclear control device, burning appliances, transportation machine, traffic signal system, safety equipment etc.) that shall require extremely high level of reliability and can directly threaten human lives in case of failure or malfunction of the product or may cause harm to human bodies, nor shall they grant any guarantee thereof. If you should intend to use our products for new introduction or other application different from current conditions on the usage of automotive device, communication device, office equipment, industrial equipment etc. , please consult with us about usage condition (temperature, operation time etc.) prior to the intended use. If there is no consultation or inquiry before the intended use, our customer shall be solely responsible for the use.
- Specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Semiconductor Co.,Ltd. assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein.
- Regarding monolithic semiconductors, if you should intend to use this IC continuously under high temperature, high current, high voltage, or drastic temperature change, even if it is used within the range of absolute maximum ratings or operating conditions, there is a possibility of decrease reliability. Please contact us for a confirmation.
- SANYO Semiconductor Co.,Ltd. strives to supply high-quality high-reliability products, however, any and all semiconductor products fail or malfunction with some probability. It is possible that these probabilistic failures or malfunction could give rise to accidents or events that could endanger human lives, trouble that could give rise to smoke or fire, or accidents that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO Semiconductor Co.,Ltd. products described or contained herein are controlled under any of applicable local export control laws and regulations, such products may require the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written consent of SANYO Semiconductor Co.,Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO Semiconductor Co.,Ltd. product that you intend to use.
- Upon using the technical information or products described herein, neither warranty nor license shall be granted with regard to intellectual property rights or any other rights of SANYO Semiconductor Co.,Ltd. or any third party. SANYO Semiconductor Co.,Ltd. shall not be liable for any claim or suits with regard to a third party's intellectual property rights which has resulted from the use of the technical information and products mentioned above.

This catalog provides information as of September, 2012. Specifications and information herein are subject to change without notice.