

Silicon PNP Power Transistors

2SB1568

DESCRIPTION


- With TO-220F package
- Complement to type 2SD2399
- High DC current gain.
- Low saturation voltage.
- DARLINGTON

APPLICATIONS

- For power amplifier applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter



Absolute maximum ratings (Ta=25℃)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	-80	V
V_{CEO}	Collector-emitter voltage	Open base	-80	V
V_{EBO}	Emitter-base voltage	Open collector	-7	V
I_C	Collector current		-4	A
I_{CM}	Collector current-peak		-6	A
P_C	Collector dissipation	$T_C=25^\circ\text{C}$	30	W
			2	
T_j	Junction temperature		150	℃
T_{stg}	Storage temperature		-55~150	℃

Silicon PNP Power Transistors**2SB1568****CHARACTERISTICS**T_j=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =-1mA; I _B =0	-80			V
V _{(BR)CBO}	Collector-base breakdown voltage	I _C =-50μA; I _E =0	-80			V
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =-5mA; I _C =0	-7			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =-2A; I _B =-4mA		-1.0	-3.0	V
I _{CBO}	Collector cut-off current	V _{CB} =-80V; I _E =0			-100	μA
I _{EBO}	Emitter cut-off current	V _{EB} =-5V; I _C =0			-3.0	mA
h _{FE}	DC current gain	I _C =-2A; V _{CE} =-3V	1000		10000	
C _{OB}	Output capacitance	I _E =0; V _{CB} =-10V; f=1MHz		35		pF
f _T	Transition frequency	I _C =-0.5A; V _{CE} =-5V; f=10MHz		12		MHz

2SB1568