

SANYO

No.513H

2SB633/2SD613

PNP/NPN Epitaxial Planar Silicon Transistors

85V/6A, AF 25 to 35W Output
Applications**Features**

- High breakdown voltage $V_{CE0}85V$, high current 6A.
- AF25 to 35W output.

(): 2SB633

Absolute Maximum Ratings at $T_a = 25^\circ C$

			unit
Collector-to-Base Voltage	V_{CBO}	(-)100	V
Collector-to-Emitter Voltage	V_{CEO}	(-)85	V
Emitter-to-Base Voltage	V_{EBO}	(-)6	V
Collector Current	I_C	(-)6	A
Collector Current (Pulse)	I_{CP}	(-)10	A
Collector Dissipation	P_C	40	W
Junction Temperature	T_j	150	$^\circ C$
Storage Temperature	T_{stg}	-55 to +150	$^\circ C$

 $T_c = 25^\circ C$ **Electrical Characteristics at $T_a = 25^\circ C$**


			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = (-)40V, I_E = 0$			(-)0.1	mA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = (-)4V, I_C = 0$			(-)0.1	mA
DC Current Gain	$h_{FE}(1)$	$V_{CE} = (-)5V, I_C = (-)1A$	40*		320*	
	$h_{FE}(2)$	$V_{CE} = (-)5V, I_C = (-)3A$	20			
Gain-Bandwidth Product	f_T	$V_{CE} = (-)5V, I_C = (-)1A$		15		MHz
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)4A, I_B = (-)0.4A$			(-)2.0	V
B-E Rise Voltage	V_{BE}	$V_{CE} = (-)5A, I_C = (-)1A$			(-)1.5	V
Output Capacitance	C_{ob}	$V_{CB} = (-)10V, f = 1MHz$		(150)110		pF
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)5mA, I_E = 0$	(-)100			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)5mA, R_{BE} = \infty$	(-)85			V
	$V_{(BR)CEO}$	$I_C = (-)50mA, R_{BE} = \infty$	(-)85			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)5mA, I_C = 0$	(-)6			V
Turn-ON Time	t_{on}	See specified Test Circuit.	(0.16)0.28			μs
Fall Time	t_f	"	(0.33)0.50			μs
Storage Time	t_{stg}	"	(1.45)3.60			μs

* : The 2SB633/2SD613 are classified by 1A h_{FE} as follows.


40	C	80	60	D	120	100	E	200	160	F	320
----	---	----	----	---	-----	-----	---	-----	-----	---	-----

Switching Time Test Circuit









(For PNP, the polarity is reversed.)



**Package Dimensions 2010C**

(unit : mm)



SANYO Electric Co., Ltd. Semiconductor Business Headquarters
 TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of September, 1995. Specifications and information herein are subject to change without notice.