FO-55112-C

REV	DOCUMENT	CHANGED BY	CHECK
33	0056412	SJK 10SEP09	CMH
REDRAWN WITHOUT CHANGE IN PRO-E			

HONEYWELL PART NUMBER

SEE CHART



MILITARY STANDARD NUMBER 6	CATALOG LISTING 6	AVAILABLE LOCKING COMBINATIONS FOR CONFIGURATION SEE LETTERED DETAILS	7 CIRCUIT MADE WITH TOGGLE LEVER IN			MILITARY RATING (AMPS)								
			KEYWAY SIDE (1-2, 4-5)	CENTER (1-2, 4-5)	OPPOSITE KEYWAY (2-3, 5-6)	RESISTIVE LOAD DC VOLTS 28	125	250	RESISTIVE LOAD AC VOLTS 125	250	LAMP LOAD 28 VDC	LAMP LOAD 125 VAC	INDUCTIVE LOAD 28 VDC	INDUCTIVE LOAD 125 VAC
24659-21	2TL1-1	A,B,D,E,F,G,H,J,K,L,M,N,P	ON	OFF	ON	20	.75	.5	15	6	7	4	15	15
24659-22	2TL1-2	D,F,G	OFF	NONE	ON									
24659-23	2TL1-3	D,F,G	ON	NONE	ON									
24659-24	2TL1-21	E,F,K,M	NONE	OFF	ON									
24659-33	2TL1-31	E,F,K,M	NONE	ON	ON									
24659-29	2TL1-4	F	MOM OFF	NONE	ON	18	.75	.5	11	6	5	2	10	8
24659-31	2TL1-5	E,F,K,L,M,N	MOM ON	OFF	ON									
24659-30	2TL1-6	F	MOM ON	NONE	OFF									
24659-27	2TL1-7	E,L,N	MOM ON	OFF	MOM ON									
24659-26	2TL1-8	F	MOM ON	NONE	ON									
24659-32	2TL1-51	E	NONE	ON	MOM ON									
24659-28	2TL1-61	E	MOM ON	OFF	NONE									

(REFER TO L191 FOR UL RATING)

(REFER TO L192 FOR UL RATING)





NOTES:
1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD.
2 - CIRCUIT DESIGNATION, MICRO SWITCH CATALOG LISTING AND "MS" NUMBER MARKED ON SIDE OF SWITCH.
3 - FURNISHED UNASSEMBLED.
4 - FOR TERMINAL COVER, SEE MICRO SWITCH CATALOG LISTING 5PA8.
5 - KEYWAY SHOWN ON LEFT SIDE.
6 - SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE OF TOGGLE LOCKING. SEE CHART FOR AVAILABLE LOCKING COMBINATIONS.
7 - APPLIES ONLY TO "ON" AND "MOMENTARY ON" POSITIONS.
8 - THESE SWITCHES ARE QUALIFIED UNDER MIL-S-3950.
9 - FROM BOTTOM OF KEYWAY TO MAJOR DIA. OF 15/32 THREAD.

15A-125, 250 OR 277 VAC
1/2 HP-125VAC; 1HP-250, 277VAC
5A-125VAC "L" CODE L191

10A-125, 250 OR 277 VAC
1/4HP-125VAC; 1/2HP-250, 277VAC
3A-125VAC "L" CODE L192

DESIGN UNITS: INCH
TOLERANCES UNLESS NOTED:

NO PLACES	X	±	-
ONE PLACE	.X	±	.03
TWO PLACE	.XX	±	.015
THREE PLACE	.XXX	±	.005
ANGLES	X	±	-

THIRD ANGLE PROJECTION

DRAWN	LSD	29JUN77
CHECK	GCH	07JUL77

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

INTERPRET PER ASME Y14.5M-1994
OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY

Pro/ENGINEER 3D

Honeywell

TITLE
SWITCH - TOGGLE

SIZE	TYPE	CAGE_CODE	DRAWING NAME	REV
C	1	-	2TL1 SERIES CHART 2	33

SCALE 2:1 WEIGHT: .15 LB. APPROX SHEET 1 OF 1