

CE


CHENYI ELECTRONICS

2W005 THRU 2W10**SINGLE PHASE GLASS
BRIDGE RECTIFIER****Voltage: 50 TO 1000V CURRENT:2.0A****FEATURES**

- Ideal for printed circuit board
- Surge overload rating: 60A peak
- High case dielectric strength

MECHANICAL DATA

- Terminal:** Plated leads solderable per
MIL-STD 202E, method 208C
- Case:** UL-94 Class V-0 recognized Flame Retardant Epoxy
- Polarity:** Polarity symbol marked on body
- Mounting position:** any

WOB**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

(Single-phase, half-wave, 60HZ, resistive or inductive load rating at 25 °C , unless otherwise stated,
for capacitive load, derate current by 20%)

	SYMBOL	2W005	2W01	2W02	2W04	2W06	2W08	2W10	units
Maximum Recurrent Peak Reverse Voltage	Vrrm	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	Vrms	35	70	140	280	420	560	700	V
Maximum DC blocking Voltage	Vdc	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified current at Ta=25 °C	If(av)	2.0							A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	Ifsm	60							A
Maximum Instantaneous Forward Voltage at forward current 2.0A DC	Vf	1.0							V
Maximum DC Reverse Voltage Ta=25°C at rated DC blocking voltage Ta=100 °C	Ir	10.0							μ A
		1.0							m A
Operating Temperature Range	Tj	-55 to +125							°C
Storage and operation Junction Temperature	Tstg	-55 to +150							°C

RATINGS AND CHARACTERISTIC CURVES 2W005 THRU 2W10

FIG.1-MAXIMUM FORWARD SURGE CURRENT




FIG.2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL REVERSE CHARACTERISTICS




FIG.4-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS

