



1. Mechanical Dimensions:



2. Schematic:



3. Electrical Specifications:

OCL: 100uH Typ @10KHz, 0.1V

ISat: 5.0Adc

DCR: 0.040 Ohms Max

ETop: 200V-uS

Engergy Storage: 1250uJ Min

Q: tbd Min @10KHz, 0.1V

Notes:

1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: $\pm 0.004"$ (0.102mm)
9. Moisture Sensitivity: Level 3
10. Electrical and mechanical specifications 100% tested
11. RoHS Compliant Component

DOC REV: A/1

XFMRS Inc. www.XFMRS.com		Title: Toroid Choke		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx ±0.010 Dimensions in Inch SHEET 1 OF 1		P/N: 2XF1006-VPM		REV. A
		DWN.	Juan Mao	Feb-28-05
		CHK.	YK Liao	Feb-28-05
		APP.	BW	Feb-28-05