




8		7	
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION	
© COPYRIGHT 20		20	
BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.			
PACIFIC VERSION TERMINATOR INTERFACE ADAPTER	PART NUMBER	REVISION	DESCRIPTION
	2-2151403-2	A	FINE CRIMP HEIGHT ADJUST
	2-2151403-5	A	FINE CRIMP HEIGHT ADJUST
	2-2151403-7	A	FINE CRIMP HEIGHT ADJUST
	7-2151403-7	A	CRIMP TOOLING KIT

APPLICATOR DATA		
CRIMP	SIZE	TYPE
WIRE	3.00 mm [.118]	F
INSUL	3.75 mm [.148]	OV
APPLICATOR INSTRUCTIONS  408-10389		

TERMINAL DATA: YAZAKI TERMINAL YAZAKI CRIMP SPECIFICATION			
TERMINAL NAME: 6.3mm YESC UNSEALED MALE TERMINAL			
WIRE STRIP LENGTH		INSULATION DIAMETER RANGE	
5.50-6.00 mm [.217-.236 IN]		Ø2.20-3.40 mm [.087-.134 IN]	
TERMINAL APPLICATION SPECIFICATION 	YPES-15-599E Rev 01	-	-
TERMINALS APPLIED 	-	-	-
TE TERMINAL	YAZAKI TERMINAL	TE TERMINAL	YAZAKI TERMINAL
1949106-1	7114-4121-02	-	-

WIRE SIZE		CRIMP HEIGHT mm [INCH]		CRIMP HEIGHT REFERENCE SETTING 
12 AWG OR 3.00mm2		1.80+/-0.05 [.071+/-0.002]		7.5
14 AWG OR 2.00mm2		1.80+/-0.05 [.071+/-0.002]		7.5
16 AWG OR 1.25mm2		1.55+/-0.05 [.061+/-0.002]		9.5
2x18 AWG OR 0.85mm2		1.65+/-0.05 [.065+/-0.002]		9.1
2X20 AWG OR 0.50mm2		1.65+/-0.05 [.065+/-0.002]		9.1

TERMINAL DATA: YAZAKI TERMINAL YAZAKI CRIMP SPECIFICATION			
TERMINAL NAME: 6.3mm YESC UNSEALED FEMALE TERMINAL			
WIRE STRIP LENGTH		INSULATION DIAMETER RANGE	
5.50-6.00 mm [.217-.236 IN]		Ø2.20-3.40 mm [.087-.134 IN]	
TERMINAL APPLICATION SPECIFICATION 	YPES-15-599E Rev 01	-	-
TERMINALS APPLIED 	-	-	-
TE TERMINAL	YAZAKI TERMINAL	TE TERMINAL	YAZAKI TERMINAL
1949107-1	7116-4121-02	-	-

WIRE SIZE		CRIMP HEIGHT mm [INCH]		CRIMP HEIGHT REFERENCE SETTING 
12 AWG OR 3.00mm2		1.85+/-0.05 [.073+/-0.002]		7.5
2x 2.50mm2		1.80+/-0.05 [.071+/-0.002]		7.5
14 AWG OR 2.00mm2		1.75+/-0.05 [.069+/-0.002]		8.4
16 AWG OR 1.25mm2		1.65+/-0.05 [.065+/-0.002]		9.1
18 AWG OR 0.85mm2		1.65+/-0.05 [.065+/-0.002]		9.1

*WARNING
ON INSTALLATION, SET WIRE DISC, ITEM 40 TO LARGEST WIRE SIZE SETTING. USE OF SETTINGS BELOW MINIMUM REQUIRED CRIMP HEIGHT SETTING WILL CAUSE DAMAGE TO CRIMP TOOLING.



-  RECOMMENDED SPARE PARTS
-  GREASE BEARING SURFACES LIGHTLY
3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.
-  APPLICATOR SPECIFIC DATA TO BE ENTERED INTO BLANK MEMORY CHIP AT ASSEMBLY. SEE BELOW FOR PART NUMBER:
PNEUMATIC FEED WITH "SMART APPLICATOR" CONVERSION: 8-2151403-4
SERVO FEED WITH "FINE CRIMP HEIGHT ADJUST": 8-2151403-5
5. ADJUSTMENT OF THE STRIPPER MAY BE REQUIRED WHEN MOVING THE APPLICATOR BETWEEN BENCH AND LEADMAKER APPLICATIONS.
-  APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEMS 62 & 180.
APPLY PART NUMBER 2-23419-6 LOCTITE TO THREADS OF ITEM 242.
-  GREASE THREADS, GROOVE AND O-RING ON ITEMS 139 & 152.
-  MAGNET MUST BE ORIENTED CORRECTLY IN ORDER TO PROPERLY ACTUATE THE COUNTER.
-  CRIMP HEIGHT REFERENCE SETTING WAS THE SETTING USED WHEN THE APPLICATOR WAS QUALIFIED AT THE FACTORY. ADJUSTMENT MAY BE NECESSARY WHEN RUNNING APPLICATOR IN THE FIELD.
-  TERMINAL PITCH NOT COMPATIBLE WITH MECHANICAL FEED.
-  TO CONVERT THE APPLICATOR TO A NON-CARRIER CUTTING STYLE, REMOVE ITEM 13 AND ATTACH TO THE LOCATION ON BACK SIDE OF THE HOUSING. REFER TO INSTRUCTION SHEET FOR ADDITIONAL INFORMATION.


-	1	1	1	2119782-1	FINE ADJUST HEAD ASM, PACIFIC STYLE	251
-	-	-	1	2119640-1	PUSH ROD, AIR FEED	250
-	-	-	1	2079988-1	BUSHING, LCH5-12, MISUMI	249
-	1	1	1	1-22279-3	SPRING, COMPRESSION	246
-77-27	-25	-22	PART NO	DESCRIPTION	ITEM NO	

PACIFIC VERSION
Shown on sheets 3 of 4 & 4 of 4
(Atlantic version shown on sheets 1 of 4 & 2 of 4)

SET UP GAUGE 2119599-1	LOC A	DIST 66	REVISIONS			
			P	LTR	DESCRIPTION	DATE
				-	SEE SHEET 1	-

-	1	1	1	2119082-4	CAM, SNAIL, INSULATION ADJUSTMENT	244
-	1	1	1	2079764-1	WASHER, WAVE SPRING, CREST-TO-CREST	243
 6	-	1	1	2119083-1	RETAINER, INSULATION DIAL	242
	-	1	1	7-18023-7	SCR, SKT HD CAP M3 X 4.0	241
	-	-	2	2168400-6	SHCS, LOW HEAD, RoHS, M5 X 16	240
	-	-	-	2063440-1	AIR FEED MODULE	238
	-	-	1	2119740-2	TAG, IDENTIFICATION	213
 6	-	-	1	1901094-3	SPACER, FEEDER	198
	-	1	1	2-1752354-2	STANDOFF, HOLD-DOWN	180
	-	1	1	993111-1	PIN, SLOTTED SPRING 3.0 X 20.0	177
	-	1	1	8-22280-7	SPRING, COMPRESSION	176
	-	1	1	1752353-2	GUIDE PIN, HOLDDOWN	175
	-	1	1	1901680-2	GUIDE PIN, HOLDDOWN	174
	-	-	-	21045-3	RING, RETAIN, EXTERN, 3/16 CRESCENT	172
	-	1	1	994969-1	MAGNET, RARE EARTH HIGH ENERGY	166
	-	REF	REF	994970-2	COUNTER, MAGNETIC	164
	-	-	-	240638-1	SPRING, FEED FINGER	163
	-	1	1	8-21084-1	O-RING, .801 ID, .070 DIA. MAT.	152
	-	-	-	2119641-2	FEED CAM, AIR FEED	151
	-	1	1	2119798-2	DETENT PIN	145
	-	1	1	2079383-8	SCR, BHSC, RoHS (M4 X 16)	144
	-	4	4	2168400-5	SHCS, LOW HEAD, RoHS, M4 X 20	143
	-	-	-	2119653-2	FEED CAM, POST FEED	142
	-	1	1	1-2119656-0	APPLICATOR BASIC ASSEMBLY, SF	141
	-	1	1	2119650-1	RAM, ASIAN STYLE, SIDE FEED	140
	-	1	1	2119092-2	BOLT, ADJUSTMENT	139
	-	-	-	3-23627-7	PIN, RETAIN, GRVD, 3/16 X .854	137
	-	-	-	2119799-1	HOLDER, FEED FINGER, AF	136
	-	-	REF	SEE NOTE 4	MEMORY CHIP, PROGRAMMED	135
	-	-	1	1633743-1	SERVO FEED LATCH ASM	133
	-	-	REF	2119944-1	FEED FINGER ASSEMBLY, SF	117
	-	1	1	318563-1	GUARD, FRONT CHIP	89
	-	1	1	455888-5	SPACER, CRIMPER	82
	-	2	2	2079383-4	SCR, BHSC, RoHS (M4 X 8)	79
	-	1	1	1803096-1	EXTENSION PLATE	78
	-	1	1	2119956-1	DOCUMENTATION PACKAGE	71
	-	1	1	2119791-5	DEPRESSOR, WIRE	70
	-	1	-	2119740-1	TAG, IDENTIFICATION	67
	-	2	2	2168078-1	SCREW, DRIVE, RH, RoHS, 2 x .188	66
 6	-	1	1	2119793-1	LIMITER, ADJUSTMENT BOLT	63
	-	3	3	992763-5	SCR, SET, SOC, CONE POINT, M3 x 4.0	62
	-	-	-	5-18022-5	SCR, HEX HD CAP, M4 X 6.0	59
	-	-	-	1338683-8	FEED PAWL	56
	-	1	1	1-5018030-0	NUT, HEX, REG, RoHS, M3.5	52
	-	1	1	1901681-9	HOLDDOWN, TERMINAL	51
	-	-	-	18023-9	SCR, SKT HD CAP M4 X 6.0	49
	-	1	1	2079383-7	SCR, BHSC, RoHS (M8 X 25)	41
	-	1	1	2119645-1	DISC, NUMBERED FA WIRE ADJUSTMENT	40
	-	1	1	2119957-1	APPLICATOR SHIM PACK	39
	-	1	1	1-2119644-2	RAM WASHER, PRECISION	38
	-	1	1	1752356-1	SUPPORT, TERMINAL	34
	-	2	2	2079383-5	SCR, BHSC, RoHS (M4 X 20)	33
	-	1	1	2161328-1	HEX HEAD, FLANGED, M5 x 8mm LONG	32
	-	1	1	1320908-1	SPACER, STRIP GUIDE	30
	-	1	1	2119959-2	ASSEMBLY, STRIP GUIDE	29
	-	1	1	455888-3	SPACER, CRIMPER	28
	-	1	1	1320928-4	STRIP GUIDE	24
	-	1	1	2168083-2	SCR, SKT HD CAP, RoHS, M4 X 8.0	21
	-	1	1	1-18028-2	WASHER, FLAT, REG M4	20
	-	1	1	2119533-1	STRIPPER, SIDE FEED	19
 1	-	1	1	2119806-1	INSERT, SHEAR	13
	-	1	1	3-22280-3	SPRING, COMPRESSION	12
	-	1	1	1-356885-4	STOP, SHEAR	11
 1	-	1	1	2119805-1	SHEAR HOLDER, FRONT	10
 1	-	1	1	454276-5	FLOATING SHEAR, FRONT	9
 1	1	1	1	1-1803056-8	ANVIL, COMBINATION	8
	-	-	-	-	-	7
	-	-	-	-	-	6
	-	1	1	2119757-8	DEPRESSOR, SHEAR	5
	-	1	1	238011-4	BLOCK, CRIMPER SPACER	4
 1	1	1	1	2-1633963-6	CRIMPER, INSULATION OVERLAP PREMIUM	3
	-	1	1	455888-5	SPACER, CRIMPER	2
 1	1	1	1	5-1633305-9	CRIMPER, WIRE PREMIUM	1
-77-27	-25	-22	PART NO	DESCRIPTION	ITEM NO	

THIS DOCUMENT IS CONTROLLED DOCUMENT AND THE INFORMATION CONTAINED HEREIN IS THE PROPERTY OF TYCO ELECTRONICS CORPORATION. IT IS SUBJECT TO CHANGE AND WITHOUT NOTICE, THE INFORMATION CONTAINED HEREIN MAY BE MODIFIED OR REVOKED WITHOUT NOTICE. NO PART OF THIS DOCUMENT SHALL BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM TYCO ELECTRONICS CORPORATION.		OWN BOB HIGMAN CHK G. BAILEY APVD G. BAILEY	13AUG2014 13AUG2014 13AUG2014	TE Connectivity Harrisburg, PA 17105-3608	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±.5 1 PLC ±0.13 2 PLC ±0.13 3 PLC ±0.013 4 PLC ±0.0001 ANGLES ±.5	PRODUCT SPEC	NAME Ocean Side Feed Applicator	SIZE A1	CAGE CODE 00779
MATERIAL -	FINISH -	APPLICATION SPEC	DRAWING NO ©=2151403	RESTRICTED TO -	SCALE 1:2
Customer Accessible Production Drawing		SHEET 3	OF 4	REV A	



FEED TRACK POSITION
GUIDE BY INSULATION BARREL

Shown on sheets 3 of 4 & 4 of 4
(Atlantic version shown on sheets 1 of 4 & 2 of 4)