

319-134

Composite EMI/RFI Ultra Low-Profile Shield Sock with Shrink Boot Porch and Self Locking Rotatable Coupling

A

CONNECTOR DESIGNATOR:

F MIL-DTL-38999 Series I, II
H MIL-DTL-38999 Series III and IV

SELF-LOCKING

ROTATABLE COUPLING

STANDARD PROFILE

**Finish
Symbol**
 (See Table III)

Product Series

319 - EMI/RFI
 Shield Sock
 Assemblies

Angle and Profile

S - Straight
T - 45° Elbow
W - 90° Elbow

**Connector
Dash
Number**
 (See
 Table II)

**Optional
Braid
Material**
 Omit for
 Standard
 (See
 Table IV)

Custom Braid Length
 Specify In Inches
 (Omit for Std. 12" Length)

Shrink Boot
 For S and B
 Angle Only
 (Omit for None)


319**H****W****134****XO****16****P****B****R****S****14**

Connector Designator
F and H

**Basic Part
Number**

Drain Hole Option
 (Omit "P" if Not
 Required)

Split Ring / Band Option
 Split Ring (687-749) and Band
 (600-057-1) supplied with **R** option
 (Omit for none)



319-134
Composite EMI/RFI Ultra Low-Profile Shield Sock
with Shrink Boot Porch and Self Locking Rotatable Coupling



Composite
Backshells

A

TABLE II: SHELL SIZE

Shell Size		E ± .06	F ± .09	G Max	H ± .03	J	K
F	H						
08	09	.72 (18.3)	.87 (22.1)	.63 (16.0)	1.042 (26.5)	.304 (7.7)	.160 (4.1)
10	11	.75 (19.1)	.93 (23.6)	.66 (16.8)	1.107 (28.1)	.432 (11.0)	.174 (4.4)
12	13	.75 (19.1)	1.00 (25.4)	.72 (18.3)	1.174 (29.8)	.546 (13.9)	.195 (5.0)
14	15	.76 (19.3)	1.03 (26.2)	.83 (21.1)	1.241 (31.5)	.670 (17.0)	.315 (8.0)
16	17	.78 (19.8)	1.05 (26.7)	.91 (23.1)	1.305 (33.1)	.796 (20.2)	.385 (9.8)
18	19	.79 (20.1)	1.06 (26.9)	.93 (23.6)	1.371 (34.8)	.902 (22.9)	.445 (11.3)
20	21	.82 (20.8)	1.09 (27.7)	1.04 (26.4)	1.438 (36.5)	1.027 (26.1)	.525 (13.3)
22	23	.86 (21.8)	1.13 (28.7)	1.12 (28.4)	1.505 (38.2)	1.152 (29.3)	.595 (15.1)
24	25	.89 (22.6)	1.16 (29.5)	1.18 (30.0)	1.572 (39.9)	1.276 (32.4)	.655 (16.6)

TABLE III: FINISH

Symbol	Finish Description
XM	2000 Hour Corrosion Resistant Electroless Nickel
XMT	2000 Hour Corrosion Resistant Ni-PTFE, Nickel-Fluorocarbon Polymer. <i>1000 Hour Grey™</i>
XW	2000 Hour Corrosion Resistant Cadmium Olive Drab Over Electroless Nickel

TABLE IV: BRAID TYPE

Symbol	Braid Type
A	100% AmberStrand®
B	75%/25% AmberStrand® Blend
L	100% ArmorLite™
Standard	Nickel/Copper 34awg
T	Tin/Copper 34awg

NOTES

1. 770-001S**-0 shrink boot supplied with T option. See shrink boot product page for more details.
2. Coupling nut supplied unplated.
3. See Table I in Intro for front end dimensional details.