High-current terminal block - PTPOWER 95-3L-F - 3260121

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



High-current terminal block, Blocked, Connection method: Push-in connection, Number of positions: 3, Cross section: 25 mm² - 95 mm², AWG: 4 - 3/0, Width: 75 mm, Height: 99.8 mm, Color: gray, Mounting type: ct screw connection

Product Features

- Quick and easy connection is now also possible for large conductors with the high-current terminal block
- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- The compact design enables wiring in a confined space
- In addition to using the existing test connection, pick-off terminal blocks can be connected, each of which can also accommodate two test cables

Key commercial data

Packing unit	1 pc
Minimum order quantity	3 pc
Weight per Piece (excluding packing)	620.0 GRM
Custom tariff number	85369010
Country of origin	Poland

Technical data

General

Number of levels	1
Number of connections	2
Color	gray
Insulating material	PA
Inflammability class according to UL 94	V0
Maximum load current	232 A (with 95 mm^2 conductor cross section)
Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III

High-current terminal block - PTPOWER 95-3L-F - 3260121

Technical data

General

Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Maximum load current	232 A (with 95 mm^2 conductor cross section)
Nominal current I_N	232 A
Nominal voltage U_N	1500 V
Maximum load current	232 A (with 95 mm^2 conductor cross section)
Open side panel	nein
Number of positions	3

Dimensions

Width	75 mm
Length	139.1 mm
Height	99.8 mm
Hole diameter	8 mm
Drill hole spacing	126.40 mm

Connection data

Connection in acc. with standard	IEC 60947-7-1
Connection method	Push-in connection
Conductor cross section solid min.	25 mm²
Conductor cross section solid max.	95 mm²
Conductor cross section AWG/kcmil min.	4
Conductor cross section AWG/kcmil max	3/0
Conductor cross section stranded min.	25 mm²
Conductor cross section stranded max.	95 mm²
Min. AWG conductor cross section, stranded	4
Max. AWG conductor cross section, stranded	4/0
Conductor cross section stranded, with ferrule without plastic sleeve min.	25 mm²
Conductor cross section stranded, with ferrule without plastic sleeve max.	95 mm²
Conductor cross section stranded, with ferrule with plastic sleeve min.	25 mm²
Conductor cross section stranded, with ferrule with plastic sleeve max.	95 mm²
Cross section with insertion bridge, solid max.	95 mm²
Cross section with insertion bridge, stranded max.	70 mm²
Cross section with insertion bridge, solid max.	95 mm²
Cross section with insertion bridge, stranded max.	70 mm²
Stripping length	40 mm

High-current terminal block - PTPOWER 95-3L-F - 3260121

Classifications

eCl@ss

eCl@ss 4.0	27141120
eCl@ss 4.1	27141120
eCl@ss 5.0	27141120
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120

ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC000897
ETIM 5.0	EC000897

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

High-current terminal block - PTPOWER 95-3L-F - 3260121

Approvals

UL Recognized

mm²/AWG/kcmil	4-4/0
Nominal current IN	230 A
Nominal voltage UN	1000 V

cUL Recognized

	C
mm²/AWG/kcmil	4-4/0
Nominal current IN	230 A
Nominal voltage UN	1000 V

EAC


cULus Recognized

Drawings

Circuit diagram



Dimensioned drawing



Phoenix Contact 2015 © - all rights reserved
http://www.phoenixcontact.com